



# 2018 CATALOG

INDUSTRIAL CARTS
WORKBENCHES I STORAGE

Manufactured by
Brennan Equipment and Manufacturing Company
www.LittleGiant-USA.com



# TABLE OF CONTENTS



# **Quick Reference Index**

Item			Page
Carts & Shelf Trucks	000		3-15
Platform Trucks, Wagons & Trailers	A A	000	16-27
Nursery Carts	6000		28-29
Bulk Handling			30-39
Storage, Security & Safety			40-52
Secondary Containment			53-55
Wire Reel Handling		1	56-59
Bar & Pipe, Sheet & Panel Handling			60-68
Dollies and Hand Trucks			69-77
Gas Cylinder Storage & Handling			78-81
Lean Manufacturing & Small Parts Storage		30 30	82-86
Workstations, Mobile Bench Cabinets & Mobile Tables			87-98
Workbenches & Shop Tables			99-109
Wheels & Model Number Index	<b>(3)</b>		110-111

# LITTLE

#### SHELF TRUCKS

#### **Mobile Instrument Cart**

This cushion-load cart is ideally suited for transporting delicate equipment or sensitive devices. Nonconductive and sound-deadening wood composite top shelf has a full perimeter non-marking bumper to protect walls and furniture. Both the top shelf and lower shelf are covered with a non-slip vinyl surface. Top shelf measures 22"W x 36"L x 35"H, Lower Shelf 21-3/4"W x 29"L. Powder coated gray finish. 1000 lbs. capacity.

Model No.	Casters	Shelf Clearance	Wt.
MIC-2436	9" x 3" Pneumatic 2-swivel & 2-rigid	20"	90
MIC-2436-5TL	5" x 1-1/4" Polyurethane 4-swivel with total lock	25"	83



#### **Instrument Cart with Hand Guard**

Full pneumatic 9" casters provide an air cushion ride. Top shelf height 34". Shelf edges available with 1-1/2" retaining lip, or flush edges. Shelf clearance 18" with lipped shelves, 19-1/2" with flush shelves. Non-slip vinyl shelf surfaces. Welded, ready for immediate use. 1200 lbs. capacity.

Shelf Size	LIP SHELVES	FLUSH SHELVES	Wt.
24 x 36	GL-2436-9PM	G-2436-9PM	99
24 x 48	GL-2448-9PM	G-2448-9PM	113
30 x 48	GL-3048-9PM	G-3048-9PM	134

Wheel brakes on swivel casters option, add: -BK



#### Flush-Handle Instrument Cart

Flush handle allows transporting of oversized items. Provides a cushioned ride with 9" pneumatic casters, 2 swivel, 2 rigid. Top shelf 34" high. Shelves are available with a 1-1/2" retaining lip or with flush edges. Available with non-slip vinyl shelf surfaces, or smooth steel. Shelf clearance 18" with lipped shelves, 19-1/2" with flush shelves. 1200 lbs. capacity.

Shelf Size	LIP SHELVES FLUSH SHELVES		Wt.	
Non-Slip Vinyl Shelf Surfaces				
24 x 36	GLF-2436-9PM	GF-2436-9PM	96	
24 x 48	GLF-2448-9PM	GF-2448-9PM	111	
30 x 48	GLF-3048-9PM	GF-3048-9PM	131	
Without Vin	yl Shelf Surfaces			
24 x 36	GLF-2436-9P	GF-2436-9P	92	
24 x 48	GLF-2448-9P	GF-2448-9P	106	
30 x 48	GLF-3048-9P	GF-3048-9P	124	

Wheel brakes on swivel casters option, add:  ${ extbf{-BK}}$ 



#### **Low Deck Instrument Cart**

Cushion load 9" pneumatic casters with a 26" top shelf height and 11-1/2" shelf clearance. Bottom shelf has 1-1/2" retaining lip. Top shelf available with flush edges or 1-1/2" retaining lips. Available with non-slip vinyl shelf surfaces, or smooth steel. All-welded construction with 12 gauge shelves. Powder coated gray finish. 1200 lbs. capacity.

Shelf Size	LIP SHELVES FLUSH SHELVES		Wt.	
Non-Slip Vinyl Shelf Surfaces				
24 x 36	LKL-2436-9PM	LK-2436-9PM	107	
24 x 48	LKL-2448-9PM	LK-2448-9PM	126	
30 x 48	LKL-3048-9PM	LK-3048-9PM	140	
Without Vin	yl Shelf Surfaces			
24 x 36	LKL-2436-9P	LK-2436-9P	105	
24 x 48	LKL-2448-9P	LK-2448-9P	123	
30 x 48	LKL-3048-9P	LK-3048-9P	135	

Wheel brakes on swivel casters option, add: -BK



#### **SHELF TRUCKS**











#### **Welded Service Carts**

1200 lbs. or 2000 lbs. Capacity

Little Giant durability in an economical shelf truck. These all-welded units ship fully assembled. Heavy 12 gauge shelves. Bottom shelf has retaining lip for small parts. Top shelf is available with lip up or down (flush top).

#### Available in either 1200 lbs. or 2000 lbs. Capacity

Durable powder coated finish. 2 swivel, 2 rigid polyurethane casters.

	1200 lb. Capacity - 35" OAH 5" Polyurethane with Brakes				apacity - 36" OAH olyurethane	ı
Shelf Size	LIP SHELVES	FLUSH TOP (& MIDDLE)	Wt.	LIP SHELVES	FLUSH TOP (& MIDDLE)	Wt.
2 SHEL	F 25" Shelf Cleara	ance				
18 x 24	LGL-1824-BRK	LG-1824-BRK	55	_	_	-
18 x 32	LGL-1832-BRK	LG-1832-BRK	65	_	_	_
24 x 36	LGL-2436-BRK	LG-2436-BRK	84	LGL-2436-6PY	LG-2436-6PY	97
24 x 48	LGL-2448-BRK	LG-2448-BRK	103	LGL-2448-6PY	LG-2448-6PY	116
30 x 48	LGL-3048-BRK	LG-3048-BRK	125	LGL-3048-6PY	LG-3048-6PY	138
30 x 60	LGL-3060-BRK	LG-3060-BRK	152	LGL-3060-6PY	LG-3060-6PY	165
3 SHEL	F 11-3/4" Shelf Cl	earance				
18 x 24	3LGL-1824-BRK	3LG-1824-BRK	72	_	-	-
18 x 32	3LGL-1832-BRK	3LG-1832-BRK	87	-	_	_
24 x 36	3LGL-2436-BRK	3LG-2436-BRK	115	3LGL-2436-6PY	3LG-2436-6PY	128
24 x 48	3LGL-2448-BRK	3LG-2448-BRK	150	3LGL-2448-6PY	3LG-2448-6PY	163
30 x 48	3LGL-3048-BRK	3LG-3048-BRK	177	3LGL-3048-6PY	3LG-3048-6PY	190
30 x 60	_	-	_	3LGL-3060-6PY	3LG-3060-6PY	230

#### With Storage Drawer - 1200 lbs. Capacity

Available with 1 or 2 drawers measuring 13"W x 17"D x 4-1/2" H.

	Shelf	5" Polyurethane		
	Size	LIP SHELVES	FLUSH TOP	Wt.
1 Drawer	24 x 36	LGL-2436-BK-DR	LG-2436-BK-DR	97
i Diawei	24 x 48	LGL-2448-BK-DR	LG-2448-BK-DR	116
2 Drawer	24 x 36	LGL-2436-BK-2DR	LG-2436-BK-2DR	84
2 Drawer	24 x 48	LGL-2448-BK-2DR	LG-2448-BK-2DR	103





#### **Service Cart**

800 lbs. Capacity

Cart is welded from 14 gauge shelves with 1-1/2" corner angles to create a solid and durable frame. The ergonomically designed "bolt on" handle allows for height adjustment from 33" – 37" in 2" increments to insure a safe and comfortable grip while reducing operator fatigue. Available in a 2 or 3 shelf configuration. Top (and middle) shelf available with flush edges or configured with 1-1/2" retaining lips. Bottom shelf has 1-1/2" retaining lips. Rides smoothly on 5" x 1-1/4" polyurethane wheels, with 2 rigid and 2 swivel bolted-on casters (hardware included). Uniquely sized to ship "small package" and save on freight cost. 29-1/4" top shelf height. 36" handle height.

	Shelf Size	FLUSH TOP (& CENTER)	LIP EDGE SHELVES	Wt.
2 SHELF	18 x 32	LG-1832-UPS	LGL-1832-UPS	51
20" Shelf Clearance	24 x 36	LG-2436-UPS	LGL-2436-UPS	65
3 SHELF	18 x 32	3LG-1832-UPS	3LGL-1832-UPS	67
9-1/4" Shelf Clearance	24 x 36	3LG-2436-UPS	3LGL-2436-UPS	88



### **Extra-Heavy-Duty Shelf Truck**

5000 lbs. Capacity

All-welded construction features flush 12 gauge steel shelves with extra reinforcement and 2" x 2" corner angles for increased capacity. Top shelf is 36" high. Clearance between shelves is 23" for 2-shelf models, and 10-1/2" for 3-shelf models. More maneuverable with heavy-duty 8" phenolic kingpinless casters. Durable powder coated finish.

2 RIGID, 2 SWIVEL CASTERS					
	2 SHELVES		3 SHELVES		
Shelf Size	Model No.	Wt.	Model No.	Wt.	
24 x 36	GH-2436-8PHK	144	3GH-2436-8PHK	177	
24 x 48	GH-2448-8PHK	167	3GH-2448-8PHK	209	
30 x 48	GH-3048-8PHK	190	3GH-3048-8PHK	242	
30 x 60	GH-3060-8PHK	216	3GH-3060-8PHK	280	
36 x 72	GH-3672-8PHK	275	3GH-3672-8PHK	365	

**4 SWIVEL CASTERS** 

2 with wheel brakes, and 2 with swivel locks that convert from swivel to rigid casters


	2 SHELVES		3 SHELVES	
Shelf Size	Model No.	Wt.	Model No.	Wt.
24 x 36	GH2436-8PHKBKPL	147	3GH236-8PHKBKPL	180
24 x 48	GH2448-8PHKBKPL	170	3GH248-8PHKBKPL	212
30 x 48	GH3048-8PHKBKPL	193	3GH348-8PHKBKPL	245
30 x 60	GH3060-8PHKBKPL	219	3GH360-8PHKBKPL	283
36 x 72	GH3672-8PHKBKPL	278	3GH372-8PHKBKPL	368

Floor Lock Option, add: -FL (Only available on 2 rigid and 2 swivel caster option)











Optional Floor Lock

### **Merchandise Collectors**

2400 lbs. to 3600 lbs. Capacity

Shelves are formed from 12 gauge steel with structural angle corners and shelf reinforcements on shelves longer than 36". Shelves are available with 1-1/2" lip, or with flush edges. Raised offset handle includes cross brace hand guard for added safety. These welded units are shipped set up and ready for immediate use, with 2 swivel and 2 rigid casters. Shelf clearance 18" with lipped shelves, 19-1/2" with flush shelves.

Capacity & Wheels	Shelf Size WxL	Lip Edge Shelves Model No.	Flush Edge Shelves Model No.	Wt.
8" x 2"	24 x 36	GL-2436-8PYBK	G-2436-8PYBK	111
Polyurethane	24 x 48	GL-2448-8PYBK	G-2448-8PYBK	136
w/Brakes 3600 lbs.	30 x 48	GL-3048-8PYBK	G-3048-8PYBK	154
Top Shelf 32" H	30 x 60	GL-3060-8PYBK	G-3060-8PYBK	180
8" x 2" Mold-on	24 x 36	GL-2436-8MR	G-2436-8MR	128
Rubber Tired	24 x 48	GL-2448-8MR	G-2448-8MR	153
2400 lbs.	30 x 48	GL-3048-8MR	G-3048-8MR	171
Top Shelf 32" H	30 x 60	GL-3060-8MR	G-3060-8MR	197
6" x 2"	24 x 36	GL-2436-6PY	G-2436-6PY	113
Polyurethane	24 x 48	GL-2448-6PY	G-2448-6PY	138
3600 lbs.	30 x 48	GL-3048-6PY	G-3048-6PY	156
Top Shelf 30" H	30 x 60	GL-3060-6PY	G-3060-6PY	182





Floor Lock Option, add: -FL Stops unwanted movement when loading or unloading



Lip Shelves

Flush Shelves "G-"

Models have flush shelves for easier loading and unloading of larger, more bulky items.

#### Lip Shelves "GL-"

Models feature 1-1/2" lip to retain small parts.

#### **SHELF TRUCKS**







#### **Cushion-Load Merchandise Collectors**

1200 lbs. to 1500 lbs. Capacity

Cushion-load casters for use over rough or uneven surfaces. Heavy gauge shelves with 1-1/2" lip or flush edges. Shelf clearance 18" with lipped shelves, 19-1/2" with flush shelves. Durable powder coated gray finish.

Capacity & Wheels	Shelf Size WxL	LIP SHELVES Model No.	FLUSH SHELVES Model No.	Wt.
9" x 3" Pneumatic	24 x 36	GL-2436-9P	G-2436-9P	95
1200 lbs.	24 x 48	GL-2448-9P	G-2448-9P	109
Top Shelf 34" H	30 x 48	GL-3048-9P	G-3048-9P	127
10" x 2.75"	24 x 36	GL-2436-10SR	G-2436-10SR	104
Puncture-Proof	24 x 48	GL-2448-10SR	G-2448-10SR	118
Rubber 1500 lbs.	30 x 48	GL-3048-10SR	G-3048-10SR	136
Top Shelf 34-1/2"H	30 x 60	GL-3060-10SR	G-3060-10SR	152





### **Heavy-Duty Shelf Truck**

3600 lbs. Capacity

12 gauge shelves handle the heaviest of loads. Shelves available with flush edges, or with 1-1/2" retaining lips. 2 swivel and 2 rigid casters with 6" x 2" hard tread phenolic wheels for added maneuverability under heavy loads. Swivel casters have wheel brakes to stop unwanted movement when loading and unloading. 36" overall height.

	WxLxH	LIP SHELVES 24" Clearance	FLUSH SHELVES 25-1/2" Clearance	Wt.
2 Shelf	24 x 36 x 36	2GL-2436-6PHBK	2G-2436-6PHBK	112
	24 x 48 x 36	2GL-2448-6PHBK	2G-2448-6PHBK	138
	30 x 48 x 36	2GL-3048-6PHBK	2G-3048-6PHBK	154
	30 x 60 x 36	2GL-3060-6PHBK	2G-3060-6PHBK	182
	WxLxH	LIP SHELVES 11" Clearance	FLUSH SHELVES 12" Clearance	Wt.
3 Shelf	24 x 36 x 36	3GL-2436-6PHBK	3G-2436-6PHBK	156
	24 x 48 x 36	3GL-2448-6PHBK	3G-2448-6PHBK	185
	30 x 48 x 36	3GL-3048-6PHBK	3G-3048-6PHBK	201
	30 x 60 x 36	3GL-3060-6PHBK	3G-3060-6PHBK	251

For 6" Mold-on Rubber with Brakes, add wheel code: **-6MRBK** (2000 lbs. Capacity) For 6" Polyurethane with Brakes, add wheel code: **-6PYBK** (3600 lbs. Capacity) Floor Lock Option, add: **-FL** 

# Model 2GL6W-2448-6PH



# **6 Wheeled Heavy-Duty Shelf Truck**

3600 lbs. Capacity

Designed for improved mobility, this all-welded shelf truck features 12 gauge steel shelves available flush or with 1-1/2" retaining lips. 4 swivel and 2 rigid 6" x 2" hard tread phenolic casters provide high maneuverability with a tighter turning radius. Durable powder coated gray finish. 36" Top Shelf Height.

		LIP SHELVES 24" Clearance		FLUSH SHELVES 25-1/2" Clearance	
	Shelf Size	Model No.	Wt.		Wt.
2 Shelf	24 x 36	2GL6W-2436-6PH	132	2G6W-2436-6PH	132
	24 x 48	2GL6W-2448-6PH	158	2G6W-2448-6PH	158
	30 x 48	2GL6W-3048-6PH	176	2G6W-3048-6PH	176
	30 x 60	2GL6W-3060-6PH	204	2G6W-3060-6PH	204
		LIP SHELVES		FLUSH SHELVES	
		11" Clearance		12" Clearance	
	Shelf Size	Model No.	Wt.		Wt.
3 Shelf	24 x 36	3GL6W-2436-6PH	176	3G6W-2436-6PH	176
	24 x 48	3GL6W-2448-6PH	205	3G6W-2448-6PH	205
	30 x 48	3GL6W-3048-6PH	231	3G6W-3048-6PH	231
	30 x 60	3GL6W-3060-6PH	273	3G6W-3060-6PH	273



#### **Ergonomic Shelf Trucks**

1200 lbs. Capacity

Ergonomic handle provides a more natural, comfortable grip that reduces wrist strain. Unique design also functions as a hand guard for added protection. The 2 swivel and 2 rigid 5" x 1-1/4" casters with non-marking polyurethane wheels provide the best combination of reduced rolling resistance and quiet operation. Wheel brakes on swivel casters are standard. All-welded construction with heavy 12 gauge shelves, these units ship fully assembled and ready for use. Bottom shelf has a 1-1/2" retaining lip for small parts. Top shelf is 35" above ground, and is available flush or with 1-1/2" retaining lips.

	Shelf Size	Lip Edge Shelves	Flush Top (& Center)	Wt.
2 SHELF	24 x 36	ERLGL-2436-BRK	ERLG-2436-BRK	85
25" Shelf	24 x 48	ERLGL-2448-BRK	ERLG-2448-BRK	104
Clearance	30 x 48	ERLGL-3048-BRK	ERLG-3048-BRK	126
	30 x 60	ERLGL-3060-BRK	ERLG-3060-BRK	155
3 SHELF	24 x 36	3ERLGL-2436-BRK	3ERLG-2436-BRK	124
11-3/4"	24 x 48	3ERLGL-2448-BRK	3ERLG-2448-BRK	154
Clearance	30 x 48	3ERLGL-3048-BRK	3ERLG-3048-BRK	183





# Heavy-Duty Ergonomic Shelf Trucks

3600 lbs. Capacity

Ergonomic handle provides a more natural, comfortable grip, and also functions as a hand guard for added protection. The 2 swivel and 2 rigid casters with non-marking 8" x 2" polyurethane wheels provide the best combination of reduced rolling resistance and quiet operation. Wheel brakes on swivel casters are standard. All-welded construction with heavy 12 gauge shelves, available with 1-1/2" lips or with flush edges. Shelf clearance 21" with lipped shelves, 22-1/2" with flush shelves. Top shelf height 35".

Shelf Size	Lip Edge Shelves	Flush Edge Shelves	Wt.
24 x 36	ERGL-2436-8PYBK	ERG-2436-8PYBK	112
24 x 48	ERGL-2448-8PYBK	ERG-2448-8PYBK	137
30 x 48	ERGL-3048-8PYBK	ERG-3048-8PYBK	155
30 x 60	ERGL-3060-8PYBK	ERG-3060-8PYBK	181













### **3-Inch Deep Shelf Trucks**

These trucks combine the convenience of 3" deep trays for accumulating and transporting smaller parts with the rugged durability of an all-welded unit. Shelves are formed from 12 gauge steel, with 3" high sides. 2 swivel and 2 rigid non-marking polyurethane casters for easy maneuverability and quiet operation.

**1200 lbs. Capacity;** 5" Polyurethane casters, 35" overall height **3600 lbs. Capacity;** 6" Polyurethane casters, 38" overall height

#### 2 Shelves

Clearance between shelves is 22-1/2".

	1200 LBS. CAPACITY		3600 LBS. CAPACITY	
Shelf Size	Model No.	Wt.	Model No.	Wt.
18 x 30	DS1830X3-5PY	71	DS1830X3-6PY	81
24 x 36	DS2436X3-5PY	95	DS2436X3-6PY	105
24 x 48	DS2448X3-5PY	122	DS2448X3-6PY	132
30 x 60	-	_	DS3060X3-6PY	181

#### 3 Shelves

Clearance between shelves is 10".

	1200 LBS. CAPACITY		
Shelf Size	Model No.	Wt.	
18 x 30	3DS1830X3-5PY	98	
24 x 36	3DS2436X3-5PY	134	
24 x 48	3DS2448X3-5PY	166	



# **6-Inch Deep Shelf Trucks**

The extra carrying capacity of the 6" high shelf lips, combined with the heavy 12 gauge welded construction, make these trucks ideal for heavier applications. Shelves are formed from a single sheet of steel and welded in place, resulting in an extremely rigid, durable unit. Polyurethane casters roll quietly and more easily under heavier load conditions. Clearance between shelves is 16-1/2".

1200 lbs. Capacity; 5" Polyurethane casters, 35" overall height 3600 lbs. Capacity; 6" Polyurethane casters, 38" overall height

	1200 LBS. CAPACITY		3600 LBS. CAPACITY	
Shelf Size	Model No.	Wt.	Model No.	Wt.
18 x 30	DS1830X6-5PY	87	DS1830X6-6PY	97
24 x 36	DS2436X6-5PY	116	DS2436X6-6PY	126
24 x 48	DS2448X6-5PY	147	DS2448X6-6PY	157



### 12-Inch Deep Shelf Truck

Shelves are all-welded 12 gauge. Top shelf has 12" high sides for maximum capacity, bottom shelf has 1-1/2" lip. Non-marking polyurethane casters are quiet rolling and move easier under heavier load conditions. Shelf clearance is 15".

1200 lbs. Capacity; 5" Polyurethane casters, 35" overall height 3600 lbs. Capacity; 6" Polyurethane casters, 38" overall height

	1200 LBS. CAPACITY		3600 LBS. CAPACITY	
Shelf Size	Model No.	Wt.	Model No.	Wt.
18 x 30	DS1830X12-5PY	91	DS1830X12-6PY	101
24 x 36	DS2436X12-5PY	122	DS2436X12-6PY	132
24 x 48	DS2448X12-5PY	155	DS2448X12-6PY	165



# **Cushion Load Deep Shelf Trucks**

1200 lbs. Capacity

Large, cushion-load wheels roll over rough and uneven surfaces, and deep top trays help to retain the load. All-welded construction with 12 gauge shelves. Ships fully assembled and ready for immediate use. Durable powder coated finish. 9" pneumatic casters, 36" overall height, 10" puncture-proof solid rubber casters, 36-1/2" overall height.

#### 3-Inch Deep Top Shelf

Bottom shelf 1-1/2" deep, 20" shelf clearance.

Shelf Size	9" x 3" Pneumatic Casters		10" x 2.75" Solid Rubber Puncture-Proof Casters	
WxL	Model No.	Wt.	Model No.	Wt.
24 x 36	DS-2436X3-9P	101	DS-2436X3-10SR	106
24 x 48	DS-2448X3-9P	127	DS-2448X3-10SR	132
30 x 60	DS-3060X3-9P	171	DS-3060X3-10SR	176

#### 6-Inch Deep Top Shelf

Bottom shelf 1-1/2" deep, 17" shelf clearance.

Shelf Size	9" x 3" Pneumatic Casters		10" x 2.75" Solid Rubbe Puncture-Proof Casters	r
WxL	Model No.	Wt.	Model No.	Wt.
24 x 36	DS-2436X6-9P	122	DS-2436X6-10SR	127
24 x 48	DS-2448X6-9P	136	DS-2448X6-10SR	141

#### 12-Inch Deep Top Shelf

Bottom shelf 1-1/2" deep, 11" shelf clearance.

Shelf Size	9" x 3" Pneumatic Casters		10" x 2.75" Solid Rubbe Puncture-Proof Casters	r
WxL	Model No.	Wt.	Model No.	Wt.
24 x 36	DS-2436X12-9P	135	DS-2436X12-10SR	140
24 x 48	DS-2448X12-9P	168	DS-2448X12-10SR	173







#### **SHELF TRUCKS**







#### **Tray Trucks**

800 lbs. Capacity

All-welded Tray Trucks ship set up and ready for immediate use. Heavy 12 gauge formed shelves are welded to 14 gauge tubular steel uprights with integral handles on both ends. Non-marking 5" x 1-1/4" polyurethane casters, 2 swivel and 2 rigid. Overall height is 36". Durable powder coated gray finish.

3" DEEP TRAYS 19" Shelf Clearance		e
Size	Model No.	Wt.
18 x 30	TT-1830-5PY	69
24 x 36	TT-2436-5PY	92

#### **Tray Trucks with Drawer**

800 lbs. Capacity

Available with large locking storage drawer that conveniently opens below the handle. Drawer measures 13"W x 17"L x 4-1/2"H.

Shelf Size	Model No.	Wt.
18 x 30	TT-1830-5PY-DR	87
24 x 36	TT-2436-5PY-DR	110

OPTIONS: -S with 4 swivel casters



### 12-inch Deep Shelf Truck with Mesh Sides

1200 lbs. Capacity

All-welded construction. Durable powder coated finish. Top shelf has 12" high clearview lip above the deck to help contain those big loads, bottom shelf has 1-1/2" lip. 15" shelf clearance. 2 swivel, 2 rigid casters with non-marking 5" x 1-1/4" polyurethane wheels. Ships fully assembled and ready for immediate use.

Shelf Size W x L		
18 x 30	DSX1830-X12-5PY	87
24 x 36	DSX2436-X12-5PY	106
24 x 48	DSX2448-X12-5PY	130

# **Deep Shelf Order Picking Truck** Sloped storage pocket under the 12" long writing shelf measures

14" wide x 12-1/2" long x 4-3/4" access height. Deep tray shelves help contain loads. Durable all-welded construction with 12 gauge shelves and a powder coated finish. Non-marking 6" x 2" polyurethane casters. 3600 lbs. capacity.

	Shelf Size	3" Deep Shelves 22-1/2" Shelf Clear	ance	6" Deep Shelves 16-1/2" Shelf Clear	ance	12" Deep Top Shelf 1-1/2" Deep Bottom 15" Shelf Clearance	Shelf
	WxL	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.
	18 x 30	DS1830X3-6PYWSP	101	DS1830X6-6PYWSP	117	DS1830X126PYWSP	121
	24 x 36	DS2436X3-6PYWSP	125	DS2436X6-6PYWSP	146	DS2436X126PYWSP	152
	24 x 48	DS2448X3-6PYWSP	152	DS2448X6-6PYWSP	177	DS2448X126PYWSP	185
WSP 🤎							



#### **Order Picking Truck**

1200 lbs. Capacity

Convenient 12" long writing shelf adds to the versatility of this truck. Bottom shelf has a 1-1/2" retaining lip, and the top shelf is available with flush edges or 1-1/2" retaining lip. 2 rigid and 2 swivel 5" polyurethane casters with brakes. Top shelf height 35", writing shelf height 39".

Shelf Size	LIP EDGE SHELVES	FLUSH EDGE TOP	Wt.		
Writing Shelf Only					
18 x 32	LGL-1832-WSBRK	LG-1832-WSBRK	80		
24 x 36	LGL-2436-WSBRK	LG-2436-WSBRK	101		
24 x 48	LGL-2448-WSBRK	LG-2448-WSBRK	120		
S	Writing Shelf & S torage pocket measures 14				
18 x 32	LGL-1832-WS-P-BK	LG-1832-WS-P-BK	90		
24 x 36	LGL-2436-WS-P-BK	LG-2436-WS-P-BK	111		
24 x 48	LGL-2448-WS-P-BK	LG-2448-WS-P-BK	130		
Writing Shelf & Storage Drawer Locking storage drawer measures 13"W x 17"D x 4-1/2"H					
24 x 36	LGL-2436-WSBKDR	LG-2436-WSBKDR	116		
24 x 48	LGL-2448-WSBKDR	LG-2448-WSBKDR	145		







Storage Pocket

Storage Drawer

#### **3-Shelf Order Picking Truck**

1200 lbs. Capacity

Convenience and versatility of our standard order-picking truck, with the added storage of a 3rd shelf. Bottom shelf has a 1-1/2" retaining lip, and the top 2 shelves are available with flush edges or 1-1/2" retaining lip. 2 rigid and 2 swivel 5" polyurethane casters with brakes. Top shelf height 35". Writing shelf height 39". 12" shelf clearance. Also available with storage pocket measuring 14" wide x 12-1/2" long.

Shelf Size	LIP EDGE SHELVES	FLUSH TOP (& CENTER)	Wt.
18 x 32	3LGL-1832-WSBRK	3LG-1832-WSBRK	97
24 x 36			
24 x 48	3LGL-2448-WSBRK	3LG-2448-WSBRK	162
	WITH STORAG	GE POCKET	
18 x 32	3LGL1832-WSP-BK	3LG-1832-WSP-BK	106
24 x 36	3LGL2436-WSP-BK	3LG-2436-WSP-BK	142
24 x 48	3LGL2448-WSP-BK	3LG-2448-WSP-BK	171



# **Instrument Cart with Writing Shelf and Storage Pocket**

1200 lbs. Capacity

Convenient writing shelf measures 21" wide x 12" long. Sloped storage pocket measures 14" wide x 12-1/2" long with 4-3/4" access height. 9" pneumatic casters, 2 swivel and 2 rigid. Top shelf height 34", overall height 39". Powder coated gray finish.

Shelf Size	LIP SHELVES	FLUSH SHELVES	Wt.		
Non-Slip Vinyl Shelf Surfaces					
24 x 36	GL-2436-9PM-WSP	G-2436-9PM-WSP	117		
24 x 48	GL-2448-9PM-WSP	G-2448-9PM-WSP	133		
Without Vi	Without Vinyl Shelf Surfaces				
24 x 36	GL-2436-9P-WSP	G-2436-9P-WSP	113		
24 x 48	GL-2448-9P-WSP	G-2448-9P-WSP	127		







#### **Multi-Shelf Trucks**

Storage Rack on Wheels

Heavy-duty trucks with three, four, or five shelves. All-welded 12 gauge steel shelves provide plenty of space to transport your large loads. Also used as portable storage racks that can be moved for cleaning, or to different locations as your storage requirements change. Two rigid and two swivel casters with 6" x 2" phenolic wheels. Comfortable formed 1" tubular steel push handle. Shelves available flush or with 1-1/2" retaining lip. 3600 lbs. capacity.

	WxL	LIP SHELVES 46-1/2" Overall Height	FLUSH SHELVES 45" Overall Height	Shelf Clearance	Wt.
	24 x 36	3ML-2436-6PH	3M-2436-6PH	16-1/2"	142
3	24 x 48	3ML-2448-6PH	3M-2448-6PH	16-1/2"	173
Shelf	30 x 48	3ML-3048-6PH	3M-3048-6PH	16-1/2"	204
	30 x 60	3ML-3060-6PH	3M-3060-6PH	16-1/2"	244
	WxL	LIP SHELVES 65" Overall Height	FLUSH SHELVES 63-1/2" Overall Height	Shelf Clearance	Wt.
	24 x 36	4ML-2436-6PH	4M-2436-6PH	16-1/2"	175
4	24 x 48	4ML-2448-6PH	4M-2448-6PH	16-1/2"	216
Shelf	30 x 48	4ML-3048-6PH	4M-3048-6PH	16-1/2"	256
	30 x 60	4ML-3060-6PH	4M-3060-6PH	16-1/2"	309
	WxL	LIP SHELVES 65" Overall Height	FLUSH SHELVES 63-1/2" Overall Height	Shelf Clearance	Wt.
	24 x 36	5ML-2436-6PH	5M-2436-6PH	12"	207
5	24 x 48	5ML-2448-6PH	5M-2448-6PH	12"	258
Shelf	30 x 48	5ML-3048-6PH	5M-3048-6PH	12"	307
	30 x 60	5ML-3060-6PH	5M-3060-6PH	12"	373

For 6" x 2" Polyurethane Casters, use wheel code -6PY (3600 lbs. Capacity)



### **Multi-Shelf Order Picking Truck**

3600 lbs. Capacity

Larger capacity to pick more orders means fewer trips. All-welded 12 gauge shelves available with retaining lip or flush edges. 12" long writing shelf is 21" wide on 24" wide trucks and 27" wide on 30" wide trucks. Sloped storage pocket measures 14" wide x 12-1/2" long with 4-3/4" access height. 6" x 2" phenolic casters.

	WxL	LIP SHELVES 46-1/2" Overall Height	FLUSH SHELVES 45" Overall Height	Shelf Clearance	Wt.
	24 x 36	3ML2436-6PH-WSP	3M-2436-6PH-WSP	16-1/2"	162
3	24 x 48	3ML2448-6PH-WSP	3M-2448-6PH-WSP	16-1/2"	193
Shelf	30 x 48	3ML3048-6PH-WSP	3M-3048-6PH-WSP	16-1/2"	233
	30 x 60	3ML3060-6PH-WSP	3M-3060-6PH-WSP	16-1/2"	273
	WxL	LIP SHELVES 65" Overall Height	FLUSH SHELVES 63-1/2" Overall Height	Shelf Clearance	Wt.
	24 x 36	4ML2436-6PH-WSP	4M-2436-6PH-WSP	16-1/2"	195
4	24 x 48	4ML2448-6PH-WSP	4M-2448-6PH-WSP	16-1/2"	236
Shelf	30 x 48	4ML3048-6PH-WSP	4M-3048-6PH-WSP	16-1/2"	285
	30 x 60	4ML3060-6PH-WSP	4M-3060-6PH-WSP	16-1/2"	338
	WxL	LIP SHELVES 65" Overall Height	FLUSH SHELVES 63-1/2" Overall Height	Shelf Clearance	Wt.
	24 x 36	5ML2436-6PH-WSP	5M-2436-6PH-WSP	12"	227
5	24 x 48	5ML2448-6PH-WSP	5M-2448-6PH-WSP	12"	278
Shelf	30 x 48	5ML3048-6PH-WSP	5M-3048-6PH-WSP	12"	327
	30 x 60	5ML3060-6PH-WSP	5M-3060-6PH-WSP	12"	393

For 6" x 2" Polyurethane Casters, use wheel code: -6PY (3600 lbs. Capacity)

# LITTLE

#### **SHELF TRUCKS**

#### **Welded 5-Shelf Service Cart**

1200 lbs. Capacity

Five all-welded steel shelves provide plenty of storage space and make transporting large quantity loads a breeze. 12" shelf clearance between shelves. Two rigid and two swivel casters with 5" non-marking polyurethane wheels. Comfortable formed 1" tubular steel push handle. Shelves are available with flush edges or 1-1/2" lips to retain load.

WxL	Lip Shelves 62" Overall Height	Flush Shelves 61-1/2" Overall Height	Wt.
18 x 32	5LML-1832-5PY	5LM-1832-5PY	125
24 x 36	5LML-2436-5PY	5LM-2436-5PY	174
24 x 48	5LML-2448-5PY	5LM-2448-5PY	223



### **Adjustable Height Multi-Shelf Truck**

800 lbs. Capacity Per Shelf

Shelves are uber-adjustable: height, slope, lip or flush edge. Available with either 2 or 3 adjustable 14 gauge shelves which can be bolted in place with their 1-1/2" lip edges facing either up or down. Shelves can be level, or positioned with a 7° or 15° slope. Bottom shelf is fixed with a 1-1/2" retaining lip. Shelf heights are adjustable in 2-1/4" increments on the 48" tall shelf supports. 2 swivel and 2 rigid casters have 6" x 2" non-marking polyurethane wheels.

Shelf	2 Adjustable Shelves and fixed base		3 Adjustable Shelves and fixed base	
Size	Model No.	Wt.	Model No.	Wt.
24 x 48	AM-2A-2448-6PY	167	AM-3A-2448-6PY	198
24 x 60	AM-2A-2460-6PY	191	AM-3A-2460-6PY	229







#### **SHELF TRUCKS**







#### **Bin Cart**

1200 lbs. Capacity

This dual-sided bin transport cart allows you to organize, store, and transport your small parts with one efficient cart. Dual-sided center welded louvered panels allow you to securely hang your polypropylene bins in any combination with easy access to either side. Heavy-duty 12 gauge steel shelves have 1-1/2" retaining lips for small parts. 34" overall height. 2 rigid and 2 swivel 5" non-marking polyurethane wheels with total lock brakes. All-welded, ships set up and ready to use. Powder coated gray finish. Cart only, bins not included.

Size	Model No.	Wt.
24 x 36	BC-2436-TL	71



# **Easy-Access Shelf Truck**

Welded service cart design with no corner upright posts allows easier access to contents on lower shelf. Heavy 12 gauge shelves provide 600 lbs. overall capacity. Two swivel, two rigid casters have non-marking polyurethane wheels with ball bearings for quiet, easy movement over most surfaces, including carpet. Overall height 35" with 26" clearance between shelves. Durable powder coated gray finish.

Shelf Size	Model No.	Wt.
18 x 24	EA-1824-5PY	56
18 x 32	EA-1832-5PY	63
24 x 36	EA-2436-5PY	85



# Welded Service Cart with Perforated Deck

1200 lbs. Capacity

The 12 gauge steel shelves have smooth perforations that allow unwanted debris & moisture to pass through. All-welded service carts feature 1-1/2" retaining lip. Non-marking 5" polyurethane casters wheel brakes. Overall height 35", shelf clearance 25". Powder coated gray finish.

Shelf Size W x L	Model No.	Wt.
24 x 36	LGLP-2436-BK	80
24 x 48	LGLP-2448-BK	97

#### SHELF TRUCKS



#### **Low Deck Truck**

1200 lbs. Capacity

Low top shelf minimizes bending. Available in either fixed height or adjustable height. Top shelf is available with flush edges or 1-1/2" retaining lips. Bottom shelf has 1-1/2" retaining lips. Rolls easily on 5" non-marking polyurethane casters, 2 swivel with wheel brakes and 2 rigid.

,					
FIXED HEIGHT Top Deck 24" High, 14" Shelf Clearance					
Shelf Size	Lip Shelves	Flush Top	Wt.		
18 x 24	LKL-1824-5PYBK	LK-1824-5PYBK	53		
18 x 32	LKL-1832-5PYBK	LK-1832-5PYBK	62		
24 x 36	LKL-2436-5PYBK	LK-2436-5PYBK	82		
24 x 48	LKL-2448-5PYBK	LK-2448-5PYBK	101		
30 x 48	LKL-3048-5PYBK	LK-3048-5PYBK	132		
30 x 60	LKL-3060-5PYBK	LK-3060-5PYBK	161		
	ADJUSTABLE	HEIGHT			
	Top Deck 25"- 33" High, 15'	" - 23" Shelf Clearance			
Shelf Size	Lip Shelves	Flush Top	Wt.		
18 x 32	LKL1832-5PYBKAH	LK1832-5PYBKAH	69		
24 x 36	LKL2436-5PYBKAH	LK2436-5PYBKAH	89		
24 x 48	LKL2448-5PYBKAH	LK2448-5PYBKAH	108		
30 x 48	LKL3048-5PYBKAH	LK3048-5PYBKAH	139		
30 x 60	LKL3060-5PYBKAH	LK3060-5PYBKAH	168		



### **Service Cart with Sloped Handle**

1200 lbs. Capacity

Little Giant durability in an economical shelf truck. These all-welded units ship fully assembled. Heavy 12 gauge shelves. Bottom shelf has retaining lip for small parts. 30" high top shelf is available with flush edges or 1-1/2" retaining lips. Offset handle for added comfort. 5" non-marking polyure-thane casters. 38-3/4" overall height.

Shelf Size	LIP SHELVES Model No.	FLUSH TOP SHELF Model No.	Wt.
18 x 32	LGLK-1832-5PY	LGK-1832-5PY	64
24 x 36	LGLK-2436-5PY	LGK-2436-5PY	84
24 x 48	LGLK-2448-5PY	LGK-2448-5PY	103
30 x 48	LGLK-3048-5PY	LGK-3048-5PY	134



Model

GCK-2436-6PH

# Sloped Handle Heavy-Duty Utility Cart

3600 lbs. Capacity

This ergonomically designed utility cart features a kick-back style handle to ensure a safe and comfortable grip while reducing operator fatigue. The heavy-duty construction features fully-welded 12 gauge shelves. Rolls easily on 2 rigid, and 2 swivel casters with 6" phenolic wheels. Available with flush edges or 1-1/2" retaining lip on the top shelf. 28" top shelf height. Available with wheel brakes on swivel casters or a floor lock to stop unwanted movement while loading and unloading.

Shelf	LIP SHELVES	FLUSH TOP SHELF	
Size	Model No.	Model No.	Wt.
24 x 36	GLK-2436-6PH	GCK-2436-6PH	115
24 x 48	GLK-2448-6PH	GCK-2448-6PH	140
30 x 48	GLK-3048-6PH	GCK-3048-6PH	158
30 x 60	GLK-3060-6PH	GCK-3060-6PH	184

For 8" x 2" Phenolic Casters, use wheel code: **-8PH** For Wheel Brakes, add: **-BRK** For Floor Lock, add: **-FL** 





Floor Lock













# Work-Height Platform Truck with Lower Shelf

2000 lbs. Capacity

12 gauge raised top deck reduces bending and back strain. Lower deck is 12 gauge with 1-1/2" retaining lips and provides secure storage when traveling. Fixed height models have a top deck height of 26". Adjustable height versions adjust from 25-1/2" to 35-1/2". Removable push-bar handle extends 14" above deck. 2 rigid, 2 swivel casters with longlasting 6" mold-on rubber wheels.

#### **Steel Deck**

Smooth 12 gauge steel with powder coated finish.

Top Deck	Lower Deck	Fixed Height		Adjustable Height	
Size	Size	Model No.	Wt.	Model No.	Wt.
24 x 48	24 x 36	RNB2-2448-6MR	140	RNB2-2448-6MRAH	150
24 x 60	24 x 48	RNB2-2460-6MR	163	RNB2-2460-6MRAH	172
30 x 48	30 x 36	RNB2-3048-6MR	163	RNB2-3048-6MRAH	172
30 x 60	30 x 48	RNB2-3060-6MR	187	RNB2-3060-6MRAH	197

For 6" Polyurethane Wheels, use wheel code: **-6PY** Floor lock option available, add: **-FL** 

#### **Hardboard over Steel Deck**

1/4" Hardboard surface over 12 gauge steel.

Top Deck	Lower Deck	Fixed Height		Adjustable Height	
Size	Size	Model No.	Wt.	Model No.	Wt.
24 x 48	24 x 36	RNH2-2448-6MR	148	RNH2-2448-6MRAH	158
24 x 60	24 x 48	RNH2-2460-6MR	173	RNH2-2460-6MRAH	182
30 x 48	30 x 36	RNH2-3048-6MR	173	RNH2-3048-6MRAH	182
30 x 60	30 x 48	RNH2-3060-6MR	200	RNH2-3060-6MRAH	210

For 6" Polyurethane Wheels, use wheel code: **-6PY** Floor lock option available, add: **-FL** 

#### Lip Edge Deck

12 gauge powder coated steel with 1-1/2" lip edge.

Top Deck	Lower Deck	Fixed Height	Adjustable Height		
Size	Size	Model No.	Wt.	Model No.	Wt.
24 x 48	24 x 36	RNL2-2448-6MR	140	RNL2-2448-6MRAH	150
24 x 60	24 x 48	RNL2-2460-6MR	163	RNL2-2460-6MRAH	172
30 x 48	30 x 36	RNL2-3048-6MR	163	RNL2-3048-6MRAH	172
30 x 60	30 x 48	RNL2-3060-6MR	187	RNL2-3060-6MRAH	197

For 6" Polyurethane Wheels, use wheel code: **-6PY** Floor lock option available, add: **-FL** 

#### 6" Deep Lip Edge Deck

12 gauge powder coated steel with 6" deep top deck and 1-1/2" deep lower deck.

Top Deck	Lower	Fixed Height		Adjustable Height	
Size	Size	Model No.	Wt.	Model No.	Wt.
24 x 48	24 x 36	RNL2X6-2448-6MR	164	RNL2X6-24486MRAH	174
24 x 60	24 x 48	RNL2X6-2460-6MR	191	RNL2X6-24606MRAH	200
30 x 48	30 x 36	RNL2X6-3048-6MR	191	RNL2X6-30486MRAH	200
30 x 60	30 x 48	RNL2X6-3060-6MR	217	RNL2X6-30606MRAH	227

For 6" Polyurethane Wheels, use wheel code: **-6PY** Floor lock option available, add: **-FL** 



# **Work-Height Platform Truck** with Open Base

2000 lbs. Capacity

Comfortable 12 gauge raised deck reduces bending and back strain. Removable pushbar handle extends 14" above the deck. Open base reduces weight and prevents accumulation of unnecessary materials. All-welded steel construction with durable powder coated finish ships fully assembled. 6" x 2" mold-on rubber casters, 2 swivel, 2 rigid.

#### **Steel Deck**

Smooth 12 gauge steel with powder coated finish.

	Fixed Deck Height 26" H		Adjustable Height 24	"-34" H
Deck Size	Model No.	Wt.	Model No.	Wt.
24 x 48	RNB-2448-6MR	116	RNB-2448-6MR-AH	123
24 x 60	RNB-2460-6MR	131	RNB-2460-6MR-AH	138
30 x 48	RNB-3048-6MR	131	RNB-3048-6MR-AH	138
30 x 60	RNB-3060-6MR	146	RNB-3060-6MR-AH	153

For 6" Polyurethane Wheels, use wheel code: -6PY Floor lock option available, add: -FL

#### **Hardboard over Steel Deck**

1/4" Hardboard surface over 12 gauge steel.

	Fixed Deck Height 26" H		Adjustable Height 24"-34"	
Deck Size	Model No.	Wt.	Model No.	Wt.
24 x 48	RNH-2448-6MR	123	RNH-2448-6MR-AH	130
24 x 60	RNH-2460-6MR	141	RNH-2460-6MR-AH	148
30 x 48	RNH-3048-6MR	141	RNH-3048-6MR-AH	148
30 x 60	RNH-3060-6MR	159	RNH-3060-6MR-AH	166

For 6" Polyurethane Wheels, use wheel code: **-6PY** Floor lock option available, add: **-FL** 

#### Lip Edge Deck

12 gauge powder coated steel with 1-1/2" lip edge.

	Fixed Deck Height 26" H*		Adjustable Height 24	"-34" H*
Deck Size	Model No.	Wt.	Model No.	Wt.
24 x 48	RNL-2448-6MR	116	RNL-2448-6MR-AH	123
24 x 60	RNL-2460-6MR	131	RNL-2460-6MR-AH	138
30 x 48	RNL-3048-6MR	131	RNL-3048-6MR-AH	138
30 x 60	RNL-3060-6MR	146	RNL-3060-6MR-AH	153

For 6" Polyurethane Wheels, use wheel code: **-6PY** Floor lock option available, add: **-FL** 

#### 6" Deep Lip Edge Deck

12 gauge powder coated steel with 6" deep top deck.

	Fixed Deck Height 26" H*		Adjustable Height 24	"-34" H*
Deck Size	Model No.	Wt.	Model No.	Wt.
24 x 48	RNLX6-2448-6MR	140	RNLX6-24486MRAH	147
24 x 60	RNLX6-2460-6MR	159	RNLX6-24606MRAH	166
30 x 48	RNLX6-3048-6MR	159	RNLX6-30486MRAH	166
30 x 60	RNLX6-3060-6MR	176	RNLX6-30606MRAH	183

For 6" Polyurethane Wheels, use wheel code: -6PY Floor lock option available, add: -FL











Floor Lock Option add **-FL** 

#### **PLATFORM TRUCKS**







### **Heavy-Duty Platform Trucks**

Capacities to 3600 lbs.

Sturdy all-welded unit is constructed of a formed 12 gauge steel deck with extra reinforcement on underside. Removable pipe handle is 1-5/16" OD and has two cross braces. Two swivel and two rigid casters with choice of wheels. Durable powder coated finish. Ships fully assembled and ready for use.



Floor Lock Option

CASTER SELECTION						
	6" x 2" MOLD-ON RUBBER 2000 lbs. Capacity		8" x 2" MOLD-ON RUBBER 2400 lbs. Capacity		8" x 2" POLYURETHANE NON-MARKING TREAD with Wheel Brakes* 3600 lbs. Capacity	
Deck Size	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.
24 x 36	NBB-2436-6MR	84	NBB-2436-8MR	88	NBB-2436-8PYBK	79
24 x 48	NBB-2448-6MR	95	NBB-2448-8MR	99	NBB-2448-8PYBK	90
24 x 60	NBB-2460-6MR	115	NBB-2460-8MR	119	NBB-2460-8PYBK	110
30 x 48	NBB-3048-6MR	115	NBB-3048-8MR	119	NBB-3048-8PYBK	110
30 x 60	NBB-3060-6MR	127	NBB-3060-8MR	131	NBB-3060-8PYBK	125
30 x 72	NBB-3072-6MR	140	NBB-3072-8MR	144	NBB-3072-8PYBK	135
36 x 60	NBB-3660-6MR	141	NBB-3660-8MR	145	NBB-3660-8PYBK	136
36 x 72	NBB-3672-6MR	157	NBB-3672-8MR	161	NBB-3672-8PYBK	152

OPTIONS: Floor Lock -FL, Wheel Brakes -BK

Extra handles, fixed handle, pipe stakes, and other

superstructures also available.

<sup>\*</sup> Note: Wheel brakes are not intended to stop moving equipment, or for use on ramps or inclines.



# Platform Trucks with Corner Bumpers

3600 lbs. Capacity

Heavy-duty formed 12 gauge steel deck with extra underside reinforcements. Choice of 2 different corner bumper options; rolling bumpers or L-style vinyl corner bumpers. Both offer great wall and door protection. Removable pipe handle is 1-5/16" OD and has two cross braces to help retain load. Two rigid and two swivel 8" non-marking polyurethane casters with wheel brakes. Durable powder coated gray finish. Ships fully assembled and ready for immediate use.

	Rolling Bumpers		L-Style Vinyl Bumpers	
Deck Size	Model No.	Wt.	Model No.	Wt.
24 x 36	NCB-2436-8PYBK	80	NLB-2436-8PYBK	81
24 x 48	NCB-2448-8PYBK	91	NLB-2448-8PYBK	92
24 x 60	NCB-2460-8PYBK	111	NLB-2460-8PYBK	112
30 x 48	NCB-3048-8PYBK	111	NLB-3048-8PYBK	112
30 x 60	NCB-3060-8PYBK	126	NLB-3060-8PYBK	127
30 x 72	NCB-3072-8PYBK	136	NLB-3072-8PYBK	137
36 x 60	NCB-3660-8PYBK	137	NLB-3660-8PYBK	138
36 x 72	NCB-3672-8PYBK	153	NLB-3672-8PYBK	154



### **Heavy-Duty Platform Trucks**

Capacities to 5000 lbs.

Trucks are formed into a solid unit with a 12 gauge steel deck welded to a structural steel frame. Sturdy removable pipe handle extends 29" above deck. Axle mounted load wheels are 12" x 2-1/2", swivel caster wheels are 8" x 2". Deck height 16-1/2".

CASTER SELECTION							
	RUBBER TIRED WHEELS 3000 lbs. Capacity		POLYURETHANE WHEELS 4000 lbs. Capacity		PHENOLIC WHEELS 5000 lbs. Capacity		
Deck Size	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.	
24 x 48	NBH-2448-MR	161	NBH-2448-PU	177	NBH-2448-PH	163	
30 x 48	NBH-3048-MR	170	NBH-3048-PU	186	NBH-3048-PH	172	
30 x 60	NBH-3060-MR	181	NBH-3060-PU	197	NBH-3060-PH	188	
30 x 72	NBH-3072-MR	190	NBH-3072-PU	207	NBH-3072-PH	192	
36 x 60	NBH-3660-MR	192	NBH-3660-PU	208	NBH-3660-PH	194	
36 x 72	NBH-3672-MR	205	NBH-3672-PU	221	NBH-3672-PH	207	



#### **Cushion-Load Platform Trucks**

Ideal for use over rough and uneven floor surfaces. 4-ply full pneumatic wheels absorb shock and reduce vibration. Inflation pressure of pneumatic tires can be adjusted to provide desired level of cushion. Solid rubber wheels are puncture-proof. Removable crossbar handle and 2 rigid, 2 swivel casters. Welded steel construction with powder coated finish ships fully assembled.

	9" x 3" PNEUMATIC 1200 lbs. Capacity		10" x 3.50" PNEUMATIC 1500 lbs. Capacity		10" x 2.75" SOLID RUBBER 1500 lbs. Capacity	
Deck Size	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.
24 x 36	NBB-2436-9P	90	NBB-2436-10P	98	NBB-2436-10SR	104
24 x 48	NBB-2448-9P	104	NBB-2448-10P	112	NBB-2448-10SR	118
24 x 60	NBB-2460-9P	113	NBB-2460-10P	121	NBB-2460-10SR	127
30 x 48	NBB-3048-9P	113	NBB-3048-10P	121	NBB-3048-10SR	127
30 x 60	NBB-3060-9P	131	NBB-3060-10P	139	NBB-3060-10SR	145
30 x 72	NBB-3072-9P	145	NBB-3072-10P	150	NBB-3072-10SR	157
36 x 72	NBB-3672-9P	150	NBB-3672-10P	159	NBB-3672-10SR	165



# **High-Deck Cushion Load Platform Trucks**

Built for heavier service and larger loads, these pneumatic tired steel platform trucks feature axle mounted load wheels with 1" roller bearings, and heavy service swivel caster brackets. Larger wheels increase mobility over the roughest terrain. High platform minimizes bending when loading.

	2500 lbs. CAPACI	TY		
	Deck Height 21" Load Wheels 16" dia. Caster Wheels 12" dia.			
Deck Size	Model No.	Wt.		
24 x 48	BB2448B	160		
30 x 48	BB3048B	180		
30 x 60	BB3060B	200		
36 x 60	BB3660B	210		
36 x 72	BB3672B	230		









#### **Steel Deck Platform Trucks**

1200 lbs. and 1600 lbs. Capacity

Fully assembled and ready for use, these all-welded steel platform trucks are built for long, trouble-free service in medium duty applications. Removable cross-brace handle extends 28" high above the reinforced formed steel deck. Available with either 6" mold-on rubber or 5" non-marking polyurethane casters.

	6" x 2" MOLD-ON RUBBER 1600 lbs. Capacity		5" POLYURETHANE 1200 lbs. Capacity		
Deck Size	Model No.	Wt.	Model No.	Wt.	
18 x 32	T500-1H	61	T700-1H	39	
24 x 36	T510-1H	71	T710-1H	48	
24 x 48	T520-1H	80	T720-1H	56	
24 x 60	T530-1H	88	T730-1H	63	

#### **Quick-Turn Platform Trucks**

Diamond caster pattern with center-mounted rigid casters allows for tighter turning radius and added maneuverability. Welded steel deck with removable handle. Available with either 6" mold-on rubber or 5" non-marking polyurethane casters.

	6" x 2" MOLD-ON RUBBER 1600 lbs. Capacity		5" POLYURETHANE 1000 lbs. Capacity	
Deck Size	Model No.	Wt.	Model No.	Wt.
24 x 36	T510-DIA-1H	71	T710-DIA-1H	48
24 x 48	T520-DIA-1H	80	T720-DIA-1H	56
24 x 60	T530-DIA-1H	88	T730-DIA-1H	63



### Platform Truck with Perforated Deck

Smooth 12 gauge perforated deck allows unwanted debris and moisture to pass through. Available with 1-1/2" lip, or flush edges. Removable pushbar handle with 2 swivel, 2 rigid casters. All-welded construction, ships fully assembled. Durable powder coated finish.

Deck W x L	Flush Edge	Lip Edge		
1200 lbs. Capacity, 5" x 1-1/4" Polyurethane casters				
24 x 36	T-710-P-1H-UPS	T-710-P-LU-UPS	44	
24 x 48	T-720-P-1H-UPS	T-720-P-LU-UPS	50	
1600 lbs. Ca	apacity, 6" x 2" Mold-On Ru	ıbber Casters		
24 x 36	T-510-P-1H	T-510-P-LU	44	
24 x 48	T-520-P-1H	T-520-P-LU	50	





### **Platform Trucks with Lip Edge**

Formed steel deck has 1-1/2" lips for better load retention. Removable cross-brace handle. Available with either 6" mold-on rubber or 5" non-marking polyurethane casters.

	6" x 2" MOLD-ON RUBBER 1600 lbs. Capacity		5" POLYURETHANE 1200 lbs. Capacity	
Deck Size	Model No.	Wt.	Model No.	Wt.
18 x 32	T500-LU	61	T700-LU	39
24 x 36	T510-LU	71	T710-LU	48
24 x 48	T520-LU	80	T720-LU	56
24 x 60	T530-LU	88	T730-LU	63



### **3-inch Lip Edge Platform Trucks**

1200 lbs. Capacity

Fully assembled and ready for use, these all-welded steel platform trucks feature a formed steel deck with 3" lips for better load retention. Removable cross-brace handle. 2 swivel and 2 rigid 5" non-marking polyurethane casters.

Deck Size	Model No.	Wt.
18 x 32	T700-X3	43
24 x 36	T710-X3	53
24 x 48	T720-X3	62



### 3-inch Lip Edge Platform Truck

The formed steel 12 gauge deck has 3" high lips for better load retention. All-welded construction and ready for immediate use. Removable pushbar handle with 2 swivel and 2 rigid casters. Durable powder coated finish.

CASTER SELECTION					
	6" x 2" MOLD-ON F 2000 lbs. Capacity	UBBER	6" x 2" POLYURETH 3600 lbs. Capacity	IANE	
Deck Size	Model No.	Wt.	Model No.	Wt.	
24 x 36	NBX3-2436-6MR	91	NBX3-2436-6PY	83	
24 x 48	NBX3-2448-6MR	103	NBX3-2448-6PY	95	
30 x 60	NBX3-3060-6MR	135	NBX3-3060-6PY	127	



# "Combo Cart" Combination Shelf and Platform Truck

1200 lbs. Capacity

This unique cart combines the storage capacity of multiple shelves with the utility of an open deck platform truck. All-welded construction with 12 gauge steel deck and shelves for optimum strength. Clearance between shelves is 12", overall height is 36". 2 swivel and 2 rigid 5" x 1-1/4" polyurethane casters with wheel brakes. Durable powder coated finish.

Platform Size W x L	Shelf Size W x L	Model No.	Wt.
24 x 48	24 x 22-1/2	CC-2448-5PYBK	84
30 x 60	30 x 26-1/2	CC-3060-5PYBK	157









#### **Double End Rack Platform Truck**

Welded steel construction with 2 removable lattice-style end racks. End racks extend 36" above the deck. Ideal for bulky packages and roll goods. 12 gauge reinforced steel deck - 9" deck height. Rolls quietly on 2 swivel and 2 rigid casters with non-marking 6" x 2" polyurethane wheels. Sturdy 3600 lbs. capacity.

Deck Size	Model No.	Wt.
24 x 48	DR-2448-6PY	108
24 x 60	DR-2460-6PY	121
30 x 48	DR-3048-6PY	123
30 x 60	DR-3060-6PY	138
30 x 72	DR-3072-6PY	153



Optional Floor Lock -FL



### **Double End Rack Platform** Truck with Side Rack

3600 lbs. Capacity

Heavy-duty platform truck enclosed on three sides with removable side and end racks for the ultimate in configurable load carrying. 12 gauge powder coated steel deck measures 9" from the floor. The two removable end racks measure 36" high from the deck surface. The side rack extends 24" from the deck. Rolls smoothly on 2 swivel and 2 rigid casters with 6" x 2" non-marking polyurethane wheels

Deck Size	Model No.	Wt.
24 x 48	DRB-2448-6PY	126
24 x 60	DRB-2460-6PY	142
30 x 48	DRB-3048-6PY	142
30 x 60	DRB-3060-6PY	159



#### **Double Handle Platform Truck**

2000 lbs. to 3600 lbs. Capacity

Handles at both ends for load retention and versatility. Sturdy all-welded unit is constructed of a formed 12 gauge steel deck with extra reinforcement on the underside. Two removable pipe handles are 1-5/16" O.D. and have two cross-braces. Two swivel and two rigid casters with choice of wheels. Durable powder coated finish. Ships fully assembled and ready for use.

CASTER SELECTION						
	6" x 2" MOLD-ON RUBBER 2000 lbs. Capacity		8" x 2" POLYURETHANE 3600 lbs. Capacity			
<b>Deck Size</b>	Model No. Wt.		Model No.			
24 x 36	NBB-2436-6MR-2H	98	NBB-2436-8PY-2H	93		
24 x 48	NBB-2448-6MR-2H	109	NBB-2448-8PY-2H	104		
24 x 60	NBB-2460-6MR-2H	129	NBB-2460-8PY-2H	124		
30 x 48	NBB-3048-6MR-2H	130	NBB-3048-8PY-2H	125		
30 x 60	NBB-3060-6MR-2H	142	NBB-3060-8PY-2H	140		
30 x 72	NBB-3072-6MR-2H	155	NBB-3072-8PY-2H	150		
36 x 60	NBB-3660-6MR-2H	157	NBB-3660-8PY-2H	152		
36 x 72	NBB-3672-6MR-2H	173	NBB-3672-8PY-2H	168		





#### **High-End Platform Truck**

With Non-Marking Polyurethane Wheels 2000 lbs. Capacity

Narrow 16-inch wide steel deck is ideal for busy aisles, or 24-inch for more loading capacity. Six-wheel design is fully maneuverable with two 8" x 2" rigid center wheels, and four 5-inch corner mounted swivel casters with ball bearing wheels. All wheels are non-marking polyurethane tread for added maneuverability. Two removable pipe handles extend 48" above the deck for taller loads, which means fewer trips.

Deck Size	Model No.	Wt.
16 x 48	HE-1648	105
16 x 60	HE-1660	115
16 x 72	HE-1672	124
24 x 48	HE-2448	124
24 x 60	HE-2460	188



# **High-End Platform Truck**

1500 lbs. Capacity

Ideal for narrow aisles and tight corners, this Little Giant high end platform truck features a narrow 16 inch, 12 gauge steel deck. The six-wheel design provides a zero turning radius. Two 6" rigid center wheels and four 5" swivel casters with ball bearing wheels for added maneuverability. All wheels are non-marking polyurethane. Two removable pipe handles extend 48" above the deck.

Deck Size	Model No.	Wt.
16 x 48	HEE-1648	96
16 x 60	HEE-1660	103



#### **6-Wheel Platform Trucks**

3600 lbs. Capacity

Reinforced 12 gauge steel deck has center mounted rigid casters for a tighter turning radius. Swivel casters under all 4 corners provide greater load support and stability. Removable pipe handle with cross braces extends 29" high above the deck. All wheels are 6" x 2" non-marking polyurethane. Also available in a 2 handle model.

	1 HANDLE MODEL		2 HANDLE MODEL		
Deck Size	Model No. Wt.		Model No.	Wt.	
24 x 48	NB6W-2448-6PY	114	NB6W2448-6PY-2H	128	
24 x 60	NB6W-2460-6PY	124	NB6W2460-6PY-2H	138	
30 x 48	NB6W-3048-6PY	130	NB6W3048-6PY-2H	145	
30 x 60	NB6W-3060-6PY	149	NB6W3060-6PY-2H	164	
30 x 72	NB6W-3072-6PY	167	NB6W3072-6PY-2H	182	
36 x 60	NB6W-3660-6PY	162	NB6W3660-6PY-2H	178	
36 x 72	NB6W-3672-6PY	182	NB6W3672-6PY-2H	198	





#### **Caster Steer Trailers**

2000 lbs. Capacity


This versatile unit can be used as an independent platform truck for manual order picking and then quickly connected into a train of trailers. The caster steer design means wheels stay under the load at all times, providing better stability with unevenly distributed loads. The two swivel casters rotate 360°, providing excellent maneuverability even in tight areas.

- Reinforced 12 gauge steel deck is 11" high
- · 8" x 2" mold-on rubber wheels with cast iron centers and roller bearings
- Removable pipe rack/pushbar handle extends 29" above the deck
- · Ring drawbar stays in upright position for manual operation as a platform truck
- Pin and clevis coupler at rear











Model

CS-3060-8MRHD

Wishbone half of coupler stands upright when not in use.

Deck Size	Model No.	Wt.
30 x 60	CS-3060-8MRHD	160
30 x 72	CS-3072-8MRHD	175
36 x 60	CS-3660-8MRHD	178
36 x 72	CS-3672-8MRHD	195



### **Caster Steer Wagon**

2000 lbs. Capacity

Built with a "T"-style pull handle for ergonomics and maneuverability. All-welded unit is constructed of a formed 12 gauge steel deck with 1-1/2" lip and extra reinforcement on the underside. Two swivel and two rigid casters with 8" x 2" mold-on rubber wheels. Handle pivots up and down and has vinyl hand grips. Durable powder coated finish.

<b>Bed Size</b>	Model No.	Wt.
24 x 48	CSW-2448-8MR	80
30 x 48	CSW-3048-8MR	91
30 x 60	CSW-3060-8MR	111
30 x 72	CSW-3072-8MR	122
36 x 60	CSW-3660-8MR	135
36 x 72	CSW-3672-8MR	136



# Tracking Trailer


2000 lbs. Capacity

The pivoting axles of these trailers are connected by a tie rod which turns the front and rear wheels in opposite directions. This design provides agile maneuvering of individual or multiple trailers in narrow aisles and around tight corners. A rear hitch on the four wheel steering trailer allows multiple trailers to track in the path of the lead trailer.

- 12 gauge steel deck with boxed edges has reinforced understructure.
- · 16" pneumatic wheels with 1" roller bearings.
- · 2-1/2" ID Ring Drawbar with Pin and Clevis Rear Hitch

Overall W x L x H	Model No.	Wt.
36 x 60 x 19	CT-3660-16P	251

- · Not intended for speeds above 5 mph.
- Increased trailer loading or trailer quantity decreases braking capability of tow vehicle



Minimum Aisle Width 8 feet (up to 3 trailers).



Model CT-3660-16P





Ring Drawbar Hitches to Pin and Clevis.

### 8-Wheeler Wagon Truck

3000 lbs. Capacity

8 wheels distribute the load over greater surface area. 16" x 4" pneumatic wheels are 4 ply with roller bearings and 1 inch axles. 12 gauge steel deck is available with flush edges or a 1-1/2" retaining lip. Ring Drawbar/T-Handle has 2-1/2" I.D. ring allows for intermittent low speed towing.

Size	Lip Edge Model No.	Flush Deck Model No.	Wt.
30 x 48	CD-3048-16P-CR	CD-3048-16PFD-CR	155
30 x 60	CD-3060-16P-CR	CD-3060-16PFD-CR	170
36 x 60	CD-3660-16P-CR	CD-3660-16PFD-CR	187
36 x 72	CD-3672-16P-CR	CD-3672-16PFD-CR	202







# HEAVY-DUTY Wagon Trucks

Up to 3500 lbs. Capacity

Fifth wheel steering describes a type of steering where the front wheels and axle assembly pivot on a center point, which is referred to as the fifth wheel. Because the steering wheels encounter less friction when turning than would be encountered in a swivel caster, wagon trucks with fifth wheel steering can be easier to maneuver under heavier load conditions. This is especially true when softer, wider pneumatic wheels are required because of use on rough or uneven surfaces. Wagon Trucks with this type of steering are typically pulled, but can also be pushed. T-handle with vinyl handgrips allows two man operation.

- Heavy 12 gauge reinforced steel decks with 1-1/2" retaining lip, or flush edge.
- Full 1-inch diameter axles and roller bearing wheels.
- Structural channel undercarriage for heavier loads and durability.





riush Deck with Moid-On Rubber Wheels

WHEEL SELECTION							
	12" x 2-1/2" Mold-On Rubber 3500 lbs. Capacity Deck Height: 16-1/2"		Mold-On Rubber Pneumatic 3500 lbs. Capacity 3000 lbs. Capacity		12" x 3-1/2" Pneumatic 2000 lbs. Capacity Deck Height: 16-1/2"		
Size	Model No.*	Wt.	Model No.*	Wt.	Model No.*	Wt.	
24 x 36	CH-2436-12MR	175	CH-2436-16P	123	CH-2436-12P	113	
24 x 48	CH-2448-12MR	185	CH-2448-16P	133	CH-2448-12P	123	
30 x 48	CH-3048-12MR	201	CH-3048-16P	149	CH-3048-12P	140	
30 x 60	CH-3060-12MR	216	CH-3060-16P	165	CH-3060-12P	155	
36 x 60	CH-3660-12MR	224	CH-3660-16P	182	CH-3660-12P	172	
36 x 72	CH-3672-12MR	251	CH-3672-16P	198	CH-3672-12P	187	

For Flush Steel Deck, add: -FSD to model number



Model CH-2448-X6-16P

# HEAVY-DUTY Deep Lip Wagon Trucks

Additional carrying capacity is provided by the higher lip edge on these heavy-duty 12 gauge steel decks. Available in either a 3" or 6" deep deck, these units are perfect for transporting smaller parts and components.

WHEEL SELECTION						
	12" x 2-1/2" 16" x 4"  Mold-On Rubber Pneumatic 3500 lbs. Capacity 3000 lbs. Capac			12" x 3-1/2' Pneumatic 2000 lbs. Capa		
Size	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.
	3" LIP EDGE DECK					
24 x 48	CH-2448-X3-12MR	189	CH-2448-X3-16P	137	CH-2448-X3-12P	127
30 x 60	CH-3060-X3-12MR	221	CH-3060-X3-16P	170	CH-3060-X3-12P	160
6" LIP EDGE DECK						
24 x 48	CH-2448-X6-12MR	205	CH-2448-X6-16P	153	CH-2448-X6-12P	143
30 x 60	CH-3060-X6-12MR	241	CH-3060-X6-16P	190	CH-3060-X6-12P	180



#### **Wagon Trucks**

1200 lbs. Capacity

Fifth wheel steering combined with choice of puncture-proof solid rubber wheels, or cushion load pneumatic wheels make these trucks ideal for maneuvering over rough surfaces. Pull handle has vinyl hand grip. Deck size is 24" wide x 36" long. Available with a flush deck or with a 1-1/2" lip-up. All models ship via UPS. Durable powder coated red finish.

#### Steel Deck

Welded 12 gauge steel for maximum durability. Available with 1-1/2" retaining lip, or with flush edges for easier sliding on and off. **Ships fully assembled, ready for immediate use.** 

Deck	Model No.	Capacity (lbs.)	Wheel Type	Wt.
	LW-2436-8S	1200	8 x 2.50 Solid Rubber	70
Lip-Up	LW-2436-10	1200	10 x 2.75 Solid Rubber	76
	LW-2436-10P	1200	10 x 3.50 Pneumatic	67
	LW-2436-8S-FSD	1200	8 x 2.50 Solid Rubber	70
Flush	LW-2436-10-FSD	1200	10 x 2.75 Solid Rubber	76
	LW-2436-10P-FSD	1200	10 x 3.50 Pneumatic	67

#### **Perforated Steel Deck**

Smooth perforated 12 gauge steel deck with 1-1/2" lip allows dirt and moisture to pass through, but has no expanded metal ends to stick up and scratch or puncture load. **Ships fully assembled, ready for immediate use.** 

W x L Deck	Model No.	Capacity (lbs.) Wheel Type		Wt.
24 x 36	LWP-2436-10	1200	10 x 2.75 Solid Rubber	73
	LWP-2436-10P	1200	10 x 3.50 Pneumatic	63

#### Steel Deck Trucks with 6" Sides

Provides additional carrying capacity. 6" high sides are formed from a single sheet of 12 gauge steel and welded into place. Easy assembly of wheels and handle to welded unit. Available with either solid steel deck or perforated steel deck.

#### **Solid Steel Deck**

	W x L Deck	Model No.	Capacity (lbs.)	Wheel Type	Wt.
24 x 36	24 v 36	LDW2436-X6-10	1200	10 x 2.75 Solid Rubber	92
	LDW2436-X6-10P	1200	10 x 3.50 Pneumatic	83	

#### **Perforated Steel Deck**

W x L Deck	Model No.	Capacity (lbs.)	Wheel Type	Wt.
24 x 36	LDWP2436-X6-10	1200	10 x 2.75 Solid Rubber	89
24 X 30	LDWP2436-X6-10P	1200	10 x 3.50 Pneumatic	80



#### **NURSERY CARTS**







#### **Nursery Wagon with Perforated Deck**

1200 lbs. Capacity

Smooth perforated 12 gauge steel deck with 1-1/2" lip allows debris and moisture to pass through. Deck is stronger and more durable than expanded metal, with no metal ends to stick up and scratch or puncture the load. Powder coated green finish. Ships fully assembled, ready for immediate use.

W x L Deck Model No.		Capacity (lbs.)	Wheel Type	Wt.
<b>24 x 36</b> LWP-2436-10-G		1200	10 x 2.75 Solid Rubber	73
	LWP-2436-10P-G	1200	10 x 3.50 Pneumatic	63



# Raised Height Nursery Platform Truck

1200 lbs. Capacity

Perforated 14 gauge steel deck allows debris and moisture to pass through, but has no expanded metal ends to stick up and scratch or puncture load. Ergonomic deck height is 16" with a 1-1/2" lip-up. Two 12" load wheels and two 10" swivel caster wheels with pneumatic tires can easily transport heavy loads over rough or uneven surfaces. Removable handle that stands 20" above deck, and can be inserted into handle pockets on either end. Overall height 36". Powder coated green finish.

Deck Size	Model No.	Wt.
24 x 48	NP-2448-G	87



### **Two-Shelf Nursery Cart**

1200 lbs. Capacity

All-welded 12 gauge perforated steel shelves have a 1-1/2" retaining lip. Cushion load pneumatic tires with 12" load wheels, 9" front swivel casters and extended loop handle for maneuverability. Ships fully assembled with durable green powder coated finish. 36" overall height. Capacity 600 lbs. per shelf.

Deck Size	Model No.	Wt.
24 x 36	NP2-2436-G	100
24 x 48	NP2-2448-G	116



### **Service Cart with Perforated Deck**

1200 lbs. Capacity

Perforated 12 gauge shelves allow debris and moisture to pass through. Shelves have 1-1/2" retaining lip. 2 swivel and 2 rigid casters with 9" pneumatic wheels for a cushioned ride. Flush handle mounted at swivel end. Shelf clearance is 19". Overall height is 35".

Deck Size	Model No.	Wt.
24 x 36	LGLP-2436-9P-G	80
24 x 48	LGLP-2448-9P-G	97



# 2-Shelf Wagon Truck with Perforated Deck

1200 lbs. Capacity

Rugged, all-welded steel construction. 12 gauge steel shelves with round perforations - ideal for cleaning and drainage. 5th wheel style steering with ergonomic handle. Ships fully assembled. Powder coated green finish.

W x L Deck	Model No.	Wheel Type	Wt.
24 x 36	2LDWP2436-10-G	10" Solid Rubber Tire	101
	2LDWP2436-10P-G	10" Pneumatic	92
24 x 48	2LDWP2448-10-G	10" Solid Rubber Tire	117
	2LDWP2448-10P-G	10" Pneumatic	108



# **Nursery Platform Truck** with Perforated Deck

1200 lbs. Capacity

Smooth perforated 12 gauge steel deck allows debris and moisture to pass through, but has no expanded metal ends to stick up and scratch or puncture load. Available with 1-1/2" lip or flush deck. Available with 9" cushion-load pneumatic wheels or 10" solid rubber. Removable handle stands 28" above deck. Powder coated green finish.

9" x 3" PNEUMATIC WHEELS 11" Deck Height					
Deck Size	Lip Deck	Wt.	Flush Deck	Wt.	
24 x 36	T810P-9PN-G-LU	59	T810P-9PN-G	59	
24 x 48	T820P-9PN-G-LU	71	T820P-9PN-G	71	
	10" x 2.75" SOL 12" D	ID RUB eck He			
Deck Size	Lip Deck	Wt.	Flush Deck	Wt.	
24 x 36	T810P-10SR-G-LU	67	T810P-10SR-G	67	
24 x 48	T820P-10SR-G-LU	79	T820P-10SR-G	79	



### **Multi-Shelf Nursery Truck**

Up to 2000 lbs. Capacity (400 lbs. per shelf)

All-welded construction and powder coated finish - ideal for nursery applications! Heavy-duty 14 gauge steel shelves are perforated for easy cleaning/spraying down. Shelves have 1-1/2" lip all around for retaining objects. Comfortable formed 1" tubular steel push handle. Rolls smoothly and quietly on 2 rigid and 2 swivel casters with 6 x 2 mold-on rubber wheels.

	Overall W x D x H	Model No.	Shelf Clearance	Wt.
3 Shelf	24 x 48 x 63	3MLP-2448-6MR-G	24-3/4"	141
3 Shell	30 x 60 x 63	3MLP-3060-6MR-G	24-3/4"	188
4.0116	24 x 48 x 63	4MLP-2448-6MR-G	16"	170
4 Shelf	30 x 60 x 63	4MLP-3060-6MR-G	16"	232
E Chalf	24 x 48 x 63	5MLP-2448-6MR-G	11-1/2"	194
5 Shelf	30 x 60 x 63	5MLP-3060-6MR-G	11-1/2"	270









Model DET4-2448-6PY

# 2-Sided Shelf Trucks 3600 lbs. Capacity

Expanded metal ends improve visibility, allow 2-way access to material. End panels extend 48" high above deck. All-welded construction with 12 gauge steel shelves. Available in 2, 3, or 4 shelf configurations. Non-marking, quiet 6" polyurethane wheels, 2 swivel, 2 rigid. Overall height 57". Capacity 3600 lbs.

SHELF SIZE	2 SHELVES 22-1/2" Clearance Model No.	Wt.	3 SHELVES 15" Clearance Model No.	Wt.	4 SHELVES 12" Clearance Model No.	Wt.
	FLUSH SHELVES					
24 x 48	DET2-2448-6PY	154	DET3-2448-6PY	196	DET4-2448-6PY	238
24 x 60	DET2-2460-6PY	175	DET3-2460-6PY	217	DET4-2460-6PY	269
30 x 48	DET2-3048-6PY	178	DET3-3048-6PY	229	DET4-3048-6PY	281
30 x 60	DET2-3060-6PY	204	DET3-3060-6PY	268	DET4-3060-6PY	332
		L	IP UP SHELVES			
24 x 48	DET2L-2448-6PY	154	DET3L-2448-6PY	196	DET4L-2448-6PY	238
24 x 60	DET2L-2460-6PY	175	DET3L-2460-6PY	217	DET4L-2460-6PY	269
30 x 48	DET2L-3048-6PY	178	DET3L-3048-6PY	229	DET4L-3048-6PY	281
30 x 60	DET2L-3060-6PY	204	DET3L-3060-6PY	268	DET4L-3060-6PY	332



### 2-Sided Adjustable Shelf Truck

3600 lbs. Capacity

Expanded metal ends extend 48" high above the deck, improve visibility, and allow 2-way access to material. All-welded construction with 12 gauge steel shelves. Standard with one or two shelves that are adjustable on 3-1/2" centers, and can be positioned with 1-1/2" lips either up or down. Additional adjustable shelves also available. 2 swivel and 2 rigid casters with quiet, non-marking 6" polyurethane wheels. Overall height 57". Capacity 3600 lbs.

Size W x D	1 Adjustable Shelf Model No.	Wt.	2 Adjustable Shelves Model No.	Wt.
24 x 48	DET2-A-2448-6PY	184	DET3-A-2448-6PY	226
24 x 60	DET2-A-2460-6PY	205	DET3-A-2460-6PY	257
30 x 48	DET2-A-3048-6PY	208	DET3-A-3048-6PY	259
30 x 60	DET2-A-3060-6PY	234	DET3-A-3060-6PY	297



#### 2-Sided Box Truck

1200 lbs. Capacity

This heavy-duty two-sided truck features mesh sides which extend 20" above the 20" high deck. 1-1/2" retaining lips on both deck and lower shelf. 11" shelf clearance provides ample room for additional storage and transport. Rolls smoothly on 2 rigid, and 2 swivel 5" x 1-1/4" non-marking polyurethane casters. Tubular handle for added comfort during operation.

Platform Size	Model No.	Wt.
18 x 32	2RP2X-1832-5PY	76
24 x 36	2RP2X-2436-5PY	100
24 x 48	2RP2X-2448-5PY	115





#### **3-Sided Shelf Trucks**

Heavy 12 gauge shelves are enclosed on 3 sides, 48" high above the deck in sturdy 1-1/2" angle iron corners and top trim. Mesh sides and slat-type sides allow visibility and air circulation. 2 swivel, 2 rigid 6" x 2" polyurethane casters with 3600 lbs. capacity. Shelves are available with a 1-1/2" retaining lip or flush front edge. Overall height 57" with flush shelves, 58-1/2" with lipped shelves.

**MESH SIDES -** 13 gauge flattened expanded metal **SLAT-TYPE SIDES -** 1-1/2" x 3/16" slats







	SIZE	2 SHELVES 22-1/2" Clearance			3 SHELVES 15" Clearance		
	WxL	Flush Shelves	Lipped Shelves	Wt.	Flush Shelves	Lipped Shelves	Wt.
Mesh	24 x 48	T2-2448-6PY	T2L-2448-6PY	173	T3-2448-6PY	T3L-2448-6PY	219
Sides	24 x 60	T2-2460-6PY	T2L-2460-6PY	198	T3-2460-6PY	T3L-2460-6PY	250
	30 x 48	T2-3048-6PY	T2L-3048-6PY	200	T3-3048-6PY	T3L-3048-6PY	251
	30 x 60	T2-3060-6PY	T2L-3060-6PY	229	T3-3060-6PY	T3L-3060-6PY	293
Slat	24 x 48	S2-2448-6PY	S2L-2448-6PY	198	S3-2448-6PY	S3L-2448-6PY	234
Sides	24 x 60	S2-2460-6PY	S2L-2460-6PY	226	S3-2460-6PY	S3L-2460-6PY	272
	30 x 48	S2-3048-6PY	S2L-3048-6PY	233	S3-3048-6PY	S3L-3048-6PY	274
	30 x 60	S2-3060-6PY	S2L-3060-6PY	267	S3-3060-6PY	S3L-3060-6PY	319

### **Forkliftable Order Picking Truck**

3600 lbs. Capacity

Large capacity, three shelf truck designed to securely attach to your order picker. Two full-width fork pockets on 24" centers and 1-1/2" steel grab bar make attachment easy. Shelves have 19" clearance. Overall height is 69". 2 rigid and 2 swivel 6" polyurethane casters assure smooth rolling, even with a full load of 3600 lbs. 48" width allows the unit to fit down any aisle! Custom configurations are available.

Size L x W	Model No.	Wt.
24 x 48	T3-2448-6PYFP60	258
30 x 48	T3-3048-6PYFP60	295







# **3-Sided Adjustable Shelf Trucks**

3600 lbs. Capacity

3 sides extend 48" high above deck to help contain loads. Interior shelves are adjustable on 3-1/2" centers for versatility, and can be positioned with 1-1/2" lips either up or down. Shelves are 12 gauge steel. 3600 lbs. overall capacity with non-marking, long-lasting 6" x 2" polyurethane casters, 2 swivel, 2 rigid. Overall height is 57". Durable powder coated gray finish.

	DECK SIZE W x L	1 ADJUSTABLE SHELF Model No.	Wt.	2 ADJUSTABLE SHELVES Model No.	Wt.
Mesh	24 x 48	T2-A-2448-6PY	203	T3-A-2448-6PY	245
Sides	24 x 60	T2-A-2460-6PY	228	T3-A-2460-6PY	280
	30 x 48	T2-A-3048-6PY	230	T3-A-3048-6PY	284
	30 x 60	T2-A-3060-6PY	259	T3-A-3060-6PY	322
Slat	24 x 48	S2-A-2448-6PY	218	S3-A-2448-6PY	260
Sides	24 x 60	S2-A-2460-6PY	256	S3-A-2460-6PY	308
	30 x 48	S2-A-3048-6PY	263	S3-A-3048-6PY	317
	30 x 60	S2-A-3060-6PY	297	S3-A-3060-6PY	360



### **Drop-Shelf Trucks**

3600 lbs. Capacity

3-sided truck converts in seconds. Upper shelf drops down and out of the way to make room for extra large items, or it can be removed completely. Sides extend 48" above deck, with drop-shelf positioned 30" above deck. Rolls easily on 6" x 2" non-marking polyurethane casters, 2 swivel and 2 rigid. 3600 lbs. capacity.

**MESH SIDES -** 13 gauge flattened expanded metal **SLAT-TYPE SIDES -** 1-1/2" x 3/16" slats

	DECK SIZE W x L	SHELF SIZE W x L	Model No.	Wt.
Mesh	24 x 48	21 x 44	T1-2448-6PY-DS	181
Sides	24 x 60	21 x 56	T1-2460-6PY-DS	206
	30 x 48	27 x 44	T1-3048-6PY-DS	209
	30 x 60	27 x 56	T1-3060-6PY-DS	237
Slat	24 x 48	21 x 44	S1-2448-6PY-DS	198
Sides	24 x 60	21 x 56	S1-2460-6PY-DS	225
	30 x 48	27 x 44	S1-3048-6PY-DS	234
	30 x 60	27 x 56	S1-3060-6PY-DS	271



#### **Pick-Pack Truck**

with sloped shelves and divider 1600 lbs. Capacity

Upper shelves are sloped, bottom shelf has 1-1/2" retaining lip. 14 gauge shelves have 14" shelf clearance. Diamond caster pattern with 6" x 2" mold-on rubber casters, 1600 lbs. capacity.

Size	Model No.	Shelf Size	Wt.
28 x 48	PPT-2848-6M	14 x 48	225
28 x 60	PPT-2860-6M	14 x 60	255



# 3 Sided Bulk Truck - 36" Interior Height

3600 lbs. Capacity

Ideal for transporting bulky material, these 3 sided bulk trucks feature mesh sides and a 12 gauge deck. The 36" mesh sides allow for better visibility and airflow. 2 swivel and 2 rigid, 8" x 2" non-marking polyurethane casters with a pushbar handle allow for easy transport. All-welded units have a powder coated gray finish and ship fully assembled and ready for immediate use.

Deck Size D x W	Model No.	Wt.
24 x 48	CA-2448-8PPY	140
24 x 60	CA-2460-8PPY	159
30 x 48	CA-3048-8PPY	160
30 x 60	CA-3060-8PPY	175



### **Removable Drop-Gate Truck**

3600 lbs. Capacity

3-Sided bulk handling truck converts into a 4 sided box truck with the addition of a removable half "Drop-Gate" panel. Hinged in the center, it can easily be lowered to provide better access while loading or unloading, or raised and latched to secure contents for transport or storage. Expanded metal sides allow better visibility and airflow. Interior height 36" above deck. 2 swivel, 2 rigid 8" x 2" non-marking polyurethane casters. Sold as a complete unit. Panel also sold separately for use with our 36" Interior Height 3 sided mesh bulk trucks.

Deck Size D x W	Model No.	Wt.
24 x 48	CARD-2448-8PY	166
24 x 60	CARD-2460-8PY	191
30 x 48	CARD-3048-8PY	186
30 x 60	CARD-3060-8PY	206

To purchase panel separately use the following model numbers:

For 48" Long Decks: **CA-RD48-PNL** For 60" Long Decks: **CA-RD60-PNL** 



**Drop-Gate removed** 

# **Welded Drop Gate Truck**

3600 lbs. Capacity

Ideal for transporting or staging of bulkier materials. All models have a 12 gauge reinforced deck, and 2 swivel, 2 rigid 6" polyurethane casters with a pushbar handle on the swivel caster end. These all-welded units have a powder coated finish and ship fully assembled. Side panels are 13 gauge flattened expanded metal with 1-1/2" angle iron corners and top edge. Front drop-gate with spring latches provide easy access. Interior height - 36" above deck.

Size	Model No.	Wt.
24 x 48	CAWD-2448-6PY	160
24 x 60	CAWD-2460-6PY	185
30 x 48	CAWD-3048-6PY	180
30 x 60	CAWD-3060-6PY	200













#### 3 Sided Bulk Trucks

3600 lbs. Capacity

Ideal for transporting or staging of bulkier materials. All models have a 12 gauge reinforced deck with flush or 1-1/2" lip edge, and a pushbar handle on swivel caster end. 2 swivel and 2 rigid 6" x 2" non-marking polyurethane casters provide smooth transport. All-welded units have a powder coated finish and ship fully assembled. Overall height 57" with flush shelves, 58-1/2" with lipped shelves.

#### **MESH SIDES**

48" interior height, 13 gauge flattened expanded metal with 1-1/2" angle iron corners and top trim.

Deck Size	FLUSH EDGE DECK		1-1/2" LIP EDGE DECK	
D x W	Model No.	Wt.	Model No.	Wt.
24 x 48	T1-2448-6PPY	139	T1L-2448-6PPY	139
24 x 60	T1-2460-6PPY	155	T1L-2460-6PPY	155
30 x 48	T1-3048-6PPY	157	T1L-3048-6PPY	157
30 x 60	T1-3060-6PPY	174	T1L-3060-6PPY	174

#### **TUBULAR STEEL SIDES**

48" interior height, 1.05" O.D. x 14 gauge round steel tubing.

Deck Size	FLUSH EDGE DECK		1-1/2" LIP EDGE DECK	
D x W	Model No.	Wt.	Model No.	Wt.
24 x 36	OT-2436-6PPY	108	OTL-2436-6PPY	108
24 x 48	OT-2448-6PPY	126	OTL-2448-6PPY	126
24 x 60	OT-2460-6PPY	143	OTL-2460-6PPY	143
30 x 48	OT-3048-6PPY	139	OTL-3048-6PPY	139
30 x 60	OT-3060-6PPY	157	OTL-3060-6PPY	157

#### **SLAT-TYPE SIDES**

48" interior height, 1-1/2" x 3/16" slats.

Deck Size	FLUSH EDGE DECK		1-1/2" LIP EDGE DECK		
D x W	Model No.	Wt.	Model No.	Wt.	
24 x 48	S1-2448-6PY	156	S1L-2448-6PY	156	
24 x 60	S1-2460-6PY	174	S1L-2460-6PY	174	
30 x 48	S1-3048-6PY	182	S1L-3048-6PY	182	
30 x 60	S1-3060-6PY	208	S1L-3060-6PY	208	





# High End Truck with Removable Shelf

2000 lbs. Capacity

Narrow 16" wide, 12 gauge steel deck is perfect for narrow aisles. Each corner has 5" polyurethane swivel wheels. Two 8" center wheels allow the unit to pivot within its own radius. All wheels are non-marking polyurethane. Two removable handles extend 48" above the deck to contain taller loads. The shelf can be mounted in three different heights (7-1/2", 21-1/2", 35-1/2" from the deck) on the upright cross braces. Shelf capacity 200 lbs.

Size Model No.		Wt.
16 x 48	HE-1648-RS	127
16 x 60	HE-1660-RS	142



### **High End 6-Wheeled Shelf Truck**

2000 lbs. Capacity

Narrow width is ideal for busy aisles and two shelves create twice the loading area! 12 gauge shelves have 24" clearance. Six-wheel design is fully maneuverable with two 8" x 2" rigid center wheels and four 5" swivel corner wheels. Non-marking polyurethane tread prevents wheel marks on your floor. End panels extend 48" high for extra capacity and are constructed from 1-1/2" x 3/16" slats for extra visibility.

Size	Model No.	Wt.
16 x 48	HE2-1648	118
16 x 60	HE2-1660	129
16 x 72	HE2-1672	152
24 x 48	HE2-2448	152
24 x 60	HE2-2460	190



### **Narrow Aisle Order Picking Truck**

2000 lbs. Capacity

Six-wheel design creates a versatile two-shelf truck that is perfect for use in warehouses and distribution centers where you need large capacity and zero turn maneuverability. The large writing shelf, measuring 21" wide and 12" deep, and storage pocket provide the work surface needed to fill out paperwork while picking orders. Constructed from 12 gauge steel and 1-1/2" angle, this workhorse is built to withstand the rigors of the most demanding facilities. The bottom shelf has 24" clearance and the end panels extend 48" above the deck. 8" rigid and 5" swivel non-marking polyurethane casters provide a smooth ride.

Size	Model No.	Wt.
24 x 48	HE2-2448-WSP	172
24 x 60	HE2-2460-WSP	210













# **Raised Platform Box Trucks** with Open Base

Raised 12 gauge steel platform is 20" high to help minimize bending. Sides extend 20" high above the deck to help contain those big loads and small parts. All-welded construction ships fully assembled and ready for immediate use. 2 swivel, 2 rigid casters with non-marking polyurethane wheels.

1200 lbs. Capacity - 5" ball bearing wheels 2000 lbs. Capacity - 6" roller bearing wheels

#### Solid Sides

14 gauge steel sides.

Platform		3-SIDED MODEL		4-SIDED MOD	EL
Size	Capacity	Model No.	Wt.	Model No.	Wt.
18 x 32	1200 lbs.	RP3S-1832-5PY	94	RP4S-1832-5PY	109
24 x 36	1200 lbs.	RP3S-2436-5PY	114	RP4S-2436-5PY	133
24 x 48	1200 lbs.	RP3S-2448-5PY	134	RP4S-2448-5PY	154
24 x 36	2000 lbs.	RP3S-2436-6PY	124	RP4S-2436-6PY	143
24 x 48	2000 lbs.	RP3S-2448-6PY	134	RP4S-2448-6PY	154
30 x 48	2000 lbs.	RP3S-3048-6PY	175	RP4S-3048-6PY	195
30 x 60	2000 lbs.	RP3S-3060-6PY	198	RP4S-3060-6PY	224

#### **Expanded Metal Sides**

3/4" expanded metal sides for greater visibility and airflow.

Platform		3-SIDED MOD	EL	4-SIDED MODEL	
Size	Capacity	Model No.	Wt.	Model No.	Wt.
18 x 32	1200 lbs.	RP3X-1832-5PY	73	RP4X-1832-5PY	78
24 x 36	1200 lbs.	RP3X-2436-5PY	93	RP4X-2436-5PY	100
24 x 48	1200 lbs.	RP3X-2448-5PY	120	RP4X-2448-5PY	128
24 x 36	2000 lbs.	RP3X-2436-6PY	102	RP4X-2436-6PY	110
24 x 48	2000 lbs.	RP3X-2448-6PY	124	RP4X-2448-6PY	132
30 x 48	2000 lbs.	RP3X-3048-6PY	156	RP4X-3048-6PY	165

### **Raised Platform Box Trucks** with Lower Shelf

1200 lbs. Capacity

All the great features of our open base raised platform box trucks with an added benefit of a lower shelf. Lower deck is 12 gauge with 1-1/2" retaining lips to provide secure storage when traveling. All-welded construction ships fully assembled and ready for immediate use.

#### **Solid Sides**

14 gauge steel sides.

Platform	3-SIDED MODE	L	4-SIDED MODEL		
Size	Model No.	Wt.	Model No.	Wt.	
18 x 32	2RP3S1832-5PY	101	2RP4S1832-5PY	117	
24 x 36	2RP3S2436-5PY	128	2RP4S2436-5PY	147	
24 x 48	2RP3S2448-5PY	155	2RP4S2448-5PY	175	

#### **Expanded Metal Sides**

3/4" expanded metal sides for greater visibility and airflow.

Platform	3-SIDED MODE	L	4-SIDED MODEL	
Size	Model No.	Wt.	Model No.	Wt.
18 x 32	2RP3X1832-5PY	81	2RP4X1832-5PY	86
24 x 36	2RP3X2436-5PY	107	2RP4X2436-5PY	114
24 x 48	2RP3X2448-5PY	123	2RP4X2448-5PY	131



## Raised Platform Box Trucks with Drop-Gate

Hinged Drop-Gate provides easier access when loading and unloading. Spring latches secure gate in upright position to retain load. Raised 12 gauge platform is 20" high to minimize bending, and sides extend 20" above platform. 2000 lbs. capacity with 6" x 2" polyurethane casters, 2 swivel and 2 rigid.

#### **SOLID SIDES**

14 gauge steel sides.

Platform Size	Model No.	Wt.
24 x 36	RPDS-2436-6PY	143
24 x 48	RPDS-2448-6PY	152
30 x 48	RPDS-3048-6PY	195

#### **EXPANDED METAL SIDES**

3/4" expanded metal for greater visibility and airflow.

Platform Size	Model No.	Wt.
24 x 36	RPDX-2436-6PY	110
24 x 48	RPDX-2448-6PY	124
30 x 48	RPDX-3048-6PY	156



Model RPDS-2436-6PY



Model RPDX-2436-6PY

## Raised Platform Box Trucks with Drop-Gate and Lid

Hinged Drop-Gate provides easier access when loading and unloading. Spring latches secure gate in upright position to retain load. Hinged top cover has padlock hasp for security. Raised 12 gauge platform is 20" high to minimize bending, and sides extend 20" above platform. 2000 lbs. capacity with 6" x 2" polyurethane casters, 2 swivel and 2 rigid. All-welded construction ships fully assembled and ready for immediate use. Available with solid or mesh steel sides.

#### **EXPANDED METAL SIDES**

3/4" expanded metal for greater visibility and airflow.

Platform Size	Model No.	Wt.
24 x 36	RPDXL-2436-6PY	180
24 x 48	RPDXL-2448-6PY	211

#### **SOLID SIDES**

14 gauge steel sides.

Platform Size	Model No.	Wt.
24 x 36	RPDSL-2436-6PY	183
24 x 48	RPDSL-2448-6PY	215











#### **Box Trucks**

2000 lbs. Capacity

Bulk storage and transport trucks have 24" interior height. Overall height is 33". Available with 2 swivel and 2 rigid, 6" x 2" mold-on rubber or non-marking polyurethane casters.

#### SHEET STEEL TRUCKS

14 gauge steel sides in angle iron frame.

	6" MOLD-ON RUBBER		6" NON-MARKING POLYURETHANE	
<b>Deck Size</b>	Model No.	Wt.	Model No.	Wt.
24 x 36	BTS2436-6MR	149	BTS2436-6PY	141
24 x 48	BTS2448-6MR	175	BTS2448-6PY	167
30 x 48	BTS3048-6MR	192	BTS3048-6PY	184
30 x 60	BTS3060-6MR	217	BTS3060-6PY	209

#### **EXPANDED METAL TRUCKS**

Angle iron frame with 3/4" expanded metal sides for greater visibility and airflow.

	6" MOLD-ON RUBBER		6" NON-MARKING POLYURETHANE	
Deck Size	Model No.	Wt.	Model No.	Wt.
24 x 36	BTX2436-6MR	101	BTX2436-6PY	93
24 x 48	BTX2448-6MR	117	BTX2448-6PY	109
30 x 48	BTX3048-6MR	130	BTX3048-6PY	122
30 x 60	BTX3060-6MR	145	BTX3060-6PY	137





### **Box Trucks with Hinged Lid**

2000 lbs. Capacity

Bulk storage and transport trucks have 24" interior height. Hinged top cover has padlock hasp for security. Overall height is 35". Available with 2 swivel and 2 rigid 6" x 2" mold-on rubber or non-marking polyurethane casters.

#### SHEET STEEL TRUCKS

14 gauge steel sides in angle iron frame provides maximum durability.

	6" MOLD-ON RUBBER		6" NON-MARKING POLYURETHANE	
<b>Deck Size</b>	Model No.	Wt.	Model No.	Wt.
24 x 36	BTSL2436-6MR	173	BTSL2436-6PY	165
24 x 48	BTSL2448-6MR	206	BTSL2448-6PY	198
30 x 48	BTSL3048-6MR	230	BTSL3048-6PY	222
30 x 60	BTSL3060-6MR	264	BTSL3060-6PY	256

#### **EXPANDED METAL TRUCKS**

Angle iron frame with 3/4" expanded metal sides for greater visibility and airflow.

	6" MOLD-ON RUBBER		6" NON-MARKING POLYURETHANE	
<b>Deck Size</b>	Model No.	Wt.	Model No.	Wt.
24 x 36	BTXL2436-6MR	117	BTXL2436-6PY	109
24 x 48	BTXL2448-6MR	139	BTXL2448-6PY	131
30 x 48	BTXL3048-6MR	155	BTXL3048-6PY	147
30 x 60	BTXL3060-6MR	174	BTXL3060-6PY	166





### **Low-Profile Hopper Truck – 12" Deep**

2000 lbs. Capacity

All-welded construction. Angled "scoop" side allows for use under machinery. Designed to catch chips, cutoff, and scraps produced by metalworking. Two swivel, two rigid casters with 6" x 2" phenolic wheels allow for smoother rolling of heavy loads. Hopper height is 21". Removable handle is 40" high. Powder coated finish.

Overall W x D x H*	Model No.	Cubic Yard Capacity	Wt.
48 x 59 x 21	HT-4857-6PH	2/3 Yard	206

<sup>\*</sup> Includes handle pockets, but does not include handle dimensions.



### **Low-Profile Hopper Truck - 16" Deep**

2000 lbs. Capacity

All-welded construction. Angled "scoop" side allows for use under machinery. Designed to catch chips, cutoff, and scraps produced by metalworking. Hopper height is 25". Removable handle is 40" high, and can be placed on any of the three sides. Four swivel casters with 6" x 2" phenolic wheels for maneuverability under equipment overhangs/under machinery. Powder coated finish.

Overall			
W x D x H*	Model No.	Cubic Yard Capacity	Wt.
54 x 38 x 25	HT-3651-6PH	1/3 Yard	183

<sup>\*</sup> Includes handle pockets, but does not include handle dimensions.



### **Hopper Truck**

2000 lbs. Capacity

14 gauge, fully welded, leakproof construction. 3/4 cubic yard capacity. 2 rigid and 2 swivel casters with 6" polyurethane wheels provide a smooth rolling truck even when fully loaded. Top edge is reinforced with 1" angle for extra durability. 3/16" thick dumping knees offer two-step dumping action. Two 1" diameter handles won't cut into your operators' hands when lifting. Heavy-duty gray powder coated finish.

Overall W x D x H	Model No.	Outin Yourd Compains	Wt.
WXDXH	woder No.	Cubic Yard Capacity	Wt.
27 x 56-3/4 x 42	HT-2751-6PY	3/4 Yard	149



### **Hopper Truck with Ergonomic Handle**

2000 lbs. Capacity

Fully welded 14 gauge steel construction. The hopper has leak-proof construction with a drain plug to make draining liquids easy. 1/3 cubic yard capacity. Two rigid and two swivel casters with 6" x 2" mold-on rubber wheels ensure smooth rolling over rough floors or metal chips. The ergonomic handle is positioned 38" from the ground to provide a more comfortable grip and reduced strain while transporting. Lower handle is 1" in diameter to make dumping easier on the operators hands. Durable gray powder coated finish.

Overall			
LxWxH	Model No.	Cubic Yard Capacity	Wt.
45 x 24" x 38"	HT-2439-6MR	1/3 Yard	135



### **STORAGE & SECURITY**







## VISIBLE CONTENT Mobile Storage Locker

2000 lbs. Capacity

The small 3/4" x 1-3/4" diamond shaped openings and heavy gauge of the steel on this truck provide maximum security for even the smallest items, while still allowing good visibility and air circulation. The double doors swing open a full 270 degrees, back to the sides and out of the way, and have a padlockable slide latch. Interior height 46-1/2", overall height 56" with 2 swivel and 2 rigid 6" x 2" non-marking polyurethane wheels. Durable gray powder coated finish.

Interior*	No Center Shelf		1 Center She	lf	2 Center Shelves		
D x W	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.	
24 x 48	SCN-2448-6PPY	186	SC-2448-6PPY	216	SC2-2448-6PPY	246	
24 x 60	SCN-2460-6PPY	196	SC-2460-6PPY	228	SC2-2460-6PPY	266	
30 x 48	SCN-3048-6PPY	196	SC-3048-6PPY	230	SC2-3048-6PPY	267	
30 x 60	SCN-3060-6PPY	245	SC-3060-6PPY	275	SC2-3060-6PPY	320	
30 x 72	SCN-3072-6PPY	291	SC-3072-6PPY	343	SC2-3072-6PPY	418	
36 x 60	SCN-3660-6PPY	292	SC-3660-6PPY	345	SC2-3660-6PPY	420	
36 x 72	SCN-3672-6PPY	350	SC-3672-6PPY	392	SC2-3672-6PPY	451	

Floor Lock Option, add: -FL



### **Adjustable Shelf Models**

Mobile Storage Locker with one center shelf, adjustable on 3-1/2" centers. Shelf is also removable.

Interior* D x W	Model No.	Wt.
24 x 48	SC-A-2448-6PPY	242
24 x 60	SC-A-2460-6PPY	252
30 x 48	SC-A-3048-6PPY	258
30 x 60	SC-A-3060-6PPY	303

Floor Lock Option, add: -FL

<sup>\*</sup> Note: For Outside Dimensions- Depth add 3", Width add 1"

<sup>\*</sup> Note: For Outside Dimensions- Depth add 3", Width add 1"





### **Security Box Truck**

1200 lbs. to 3600 lbs. Capacity

Heavy-duty, all-welded 1-1/2" angle frame with 13 gauge expanded metal panels provide a durable truck to secure and transport your materials or cargo. Expanded metal sides and top allows easy visibility of contents. Doublehinged top cover has padlock hasp for added security. Front drop-gate with spring latches provides easy access. Interior height - 36". Choose wheels based on rolling surface and capacity required. Available in 6" non-marking polyurethane, 9" pneumatic, and 10" solid

rubber. Durable powder coated gray finish.



	6" x 2" POLYURETHANE 3600 lbs. Capacity 46" OAH		9" x 3" PNEUMATION 1200 lbs. Capacity 49-1/2" OAH	;	10" x 2-3/4" SOLID RUBBER 1500 lbs. Capacity 50" OAH		
Deck Size	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.	
24 x 48	SB-2448-6PY	173	SB-2448-9P	176	SB-2448-10SR	185	
24 x 60	SB-2460-6PY	195	SB-2460-9P	198	SB-2460-10SR	207	
30 x 48	SB-3048-6PY	196	SB-3048-9P	199	SB-3048-10SR	208	
30 x 60	SB-3060-6PY	220	SB-3060-9P	223	SB-3060-10SR	232	

Floor Lock Option, add: -FL (available on 6" casters)

### **Security Box Truck** with Solid Sides

Heavy-duty, all-welded 1-1/2" angle frame with 14 gauge all-welded steel construction protects your items from view and offers complete security. Drop-gate front permits easy access to contents. User-friendly, double-hinged cover folds down and back. Padlock hasp provides extra security. Interior height of 36". For rolling over smooth surfaces

choose the 6" x 2" mold-on rubber wheels. For rolling over rough surfaces, the 10" solid rubber version is the perfect choice. Gray powder coated finish.



Model

	6" x 2" MOLD-ON RU 2000 lbs. Capacity	JBBER	10" x 2-3/4" SOLID RUBBER 1500 lbs. Capacity			
Deck Size	Model No.	Wt.	Model No.	Wt.		
24 x 48	SBS-2448-6MR	272	SBS-2448-10SR	284		
30 x 60	SBS-3060-6MR	349	SBS-3060-10SR	361		

Floor Lock Option, add: -FL (available on 6" casters)

### **STORAGE & SECURITY**







### 3 COMPARTMENT Mobile Storage Locker

2000 lbs. Capacity

Heavy-duty mobile storage locker provides 3 extra-large, 18" high openings with ample storage space for tools, supplies and equipment. The 3 double doors have padlockable slide latches and swing open a full 270 degrees. Contents remain visible for quick inventory of items. 2 swivel, 2 rigid 6" non-marking polyurethane wheels. 67-1/2" overall height. Powder coated gray finish.

Shelf D x W	Model No.	Wt.
24 x 48	SC2-6D-2448-6PY	289
30 x 48	SC2-6D-3048-6PY	314

<sup>\*</sup> Note: For Outside Dimensions- Depth add 3", Width add 1"



## **Tool Security Cart with Pegboard Tool Storage**

2000 lbs. Capacity

Heavy-duty mobile tool locker features a 16 gauge steel pegboard with holes 1" on center (uses standard pegboard hooks). Expanded metal provides secure, visible storage for all your tools. Doors swing open a full 270 degrees and feature a padlockable slide latch. 2 rigid, 2 swivel non-marking polyurethane wheels. Interior height 46-1/2", overall height 56". Available with or without 1 center shelf. Fully welded, ships set up and ready for immediate use. Durable powder coated gray finish.

	No Center Shel	f	1 Center Shelf			
Shelf D x W	Model No.	Wt.	Model No.	Wt.		
24 x 48	SCN-2448-6PY-PB	206	SC1-2448-6PY-PB	236		
24 x 60	SCN-2460-6PY-PB	221	SC1-2460-6PY-PB	253		

For Louvered Panel, replace -PB with -LP



## 2-Sided Mobile Maintenance Cart with Pegboard or Louvered Panels

3600 lbs. Capacity

Heavy-duty, double-sided tool bench cart with either pegboard or louvered panel separator to organize your tools or parts so they are ready when you need them. Two sided construction keeps your tools or parts in easy reach. 13 gauge expanded metal ends and secure 14 gauge perforated doors make locating the right tool easy while maintaining secure storage when not in use. Doors on both sides have padlockable slide latch. 6" polyurethane wheels provide smooth rolling for easy maneuverability. 33" overall height.

	Pegboard Pane	l	Louvered Panel		
Size	Model No.	Wt.	Model No.	Wt.	
24 x 48	ST-2448-6PY-PB	215	ST-2448-6PY-LP	215	

Floor Lock Option, add: -FL

<sup>\*</sup> Note: For Outside Dimensions- Depth add 3", Width add 1"





### **All-Welded Mobile Storage Lockers**

2000 lbs. Capacity

13 gauge expanded metal provides secure, visible storage for larger, bulkier items. Doors swing open a full 270 degrees and feature a padlockable slide latch. 2 swivel, 2 rigid 6" non-marking polyurethane casters. Floor lock to stop unwanted movement. 72" interior height, 81" overall height. Welded unit ships set up and ready for immediate use. Durable powder coated gray finish.

Interior*	No Center Shelf		1 Center She	elf	2 Center Shelves		
D x W	Model No. Wt.		lodel No. Wt. Model No. Wt.		Wt. Model No.		
30 x 48	SLN-3048-6PYFL	279	SL1-3048-6PYFL	308	SL2-3048-6PYFL	345	
30 x 60	SLN-3060-6PYFL	314	SL1-3060-6PYFL	358	SL2-3060-6PYFL	395	

Interior*	1 Adjustable Shelf		2 Adjustable Shelves			
D x W	Model No.	Wt.	Model No.	Wt.		
30 x 48	SL1A-3048-6PYFL	344	SL2A-3048-6PYFL	375		
30 x 60	SL1A-3060-6PYFL	386	SL2A-3060-6PYFL	425		

<sup>\*</sup> Note: For Outside Dimensions- Depth add 3", Width add 1"



Model SL1-3048-6PYFL



### **Job Site Security Box**

Heavy-duty security locker with 10" solid rubber tires permit easy rolling over rough surfaces such as construction sites or other less than perfect floors. Fully welded 1-1/2" angle frame and 13 gauge expanded metal secures your tools and supplies while providing good visibility. The doors open a full 270 degrees to allow complete access. Available with fixed height or adjustable height shelves. Padlockable slide latch keeps your items safe. Interior height 46-1/2", overall height 60". 1500 pounds total capacity. Durable powder coated gray finish.

Interior* No Center Shelf		1 Center Sho	elf	2 Center Shelves		
D x W	D x W Model No. Wt.		. Model No. Wt.		Model No.	Wt.
24 x 48	SCN-2448-10SR	198	SC-2448-10SR	228	SC2-2448-10SR	258
24 x 60	SCN-2460-10SR	208	SC-2460-10SR	240	SC2-2460-10SR	278
30 x 48	SCN-3048-10SR	208	SC-3048-10SR	242	SC2-3048-10SR	279

<sup>\*</sup> Note: For Outside Dimensions- Depth add 3", Width add 1"

### **Adjustable Shelf Models**

Interior* D x W	Model No.	Wt.
24 x 48	SC-A-2448-10SR	254
24 x 60	SC-A-2460-10SR	264
30 x 48	SC-A-3048-10SR	270

<sup>\*</sup> Note: For Outside Dimensions- Depth add 3", Width add 1"















Model SL2-A-3048

### **All-Welded Storage Lockers**

Secure, visible storage for larger, bulkier items. Welded steel construction has small 3/4" x 1-3/4" diamond-shaped openings. Doors swing open a full 270 degrees and feature a padlockable slide latch. 4" underclearance for transporting with pallet truck or fork lift. 72" interior height, 78" overall height. Welded unit ships set up and ready for immediate use. Powder coated gray finish.

Interior*	No Center Sh	elves	1 Center SI	1 Center Shelf		2 Center Shelves		elves
D x W	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.
24 x 48	SLN-2448	230	SL1-2448	253	SL2-2448	283	SL3-2448	325
24 x 60	SLN-2460	258	SL1-2460	287	SL2-2460	324	SL3-2460	376
30 x 48	SLN-3048	241	SL1-3048	270	SL2-3048	307	SL3-3048	361
30 x 60	SLN-3060	276	SL1-3060	312	SL2-3060	357	SL3-3060	420
30 x 72	SLN-3072	307	SL1-3072	372	SL2-3072	447	SL3-3072	522
36 x 60	SLN-3660	309	SL1-3660	374	SL2-3660	449	SL3-3660	524
36 x 72	SLN-3672	357	SL1-3672	435	SL2-3672	524	SL3-3672	613

<sup>\*</sup> Note: For Outside Dimensions- Depth add 3", Width add 1"

### **Adjustable Shelf Models**

Welded storage locker with 1, 2, or 3 adjustable center shelves. Shelves are adjustable on 3-1/2" centers, from 12" to 60" above the bottom deck, and are also removable.

Interior*	1 Adjustable Center Shelf		1			3 Adjustable Center Shelves		
D x W	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.		
24 x 48	SL1-A-2448	289	SL2-A-2448	313	SL3-A-2448	355		
24 x 60	SL1-A-2460	323	SL2-A-2460	354	SL3-A-2460	406		
30 x 48	SL1-A-3048	306	SL2-A-3048	337	SL3-A-3048	391		
30 x 60	SL1-A-3060	348	SL2-A-3060	387	SL3-A-3060	450		

<sup>\*</sup> Note: For Outside Dimensions- Depth add 3", Width add 1"

#### Model SLC-2-3060



### Combination Cabinets with Two Half Shelves

Two center half-shelves for neatly storing smaller items, and one full-height opening for your larger, bulkier items. Expanded metal provides both visibility and ventilation. Doors open 270 degrees back to the sides and out of the way. All-welded unit ships set up and ready to use. 78" overall height, with 4" underclearance. Interior height 72". Padlockable slide latch. Durable powder coated finish.

Interior* D x W	Model No.	Wt.
24 x 48	SLC-2-2448	284
24 x 60	SLC-2-2460	319
30 x 48	SLC-2-3048	304
30 x 60	SLC-2-3060	347

<sup>\*</sup> Note: For Outside Dimensions- Depth add 3", Width add 1"



Model SL5-2424-78

### **ALL-WELDED COMPACT Storage Locker**

Compact all-welded storage locker has five 14 gauge shelves and a heavyduty padlockable slide latch. High-visibility 13 gauge expanded metal siding. Footpads have holes for lagging to floor. Right hand door swings 270° flush to side. 78" overall height. 4" underclearance. Durable powder coated gray finish.

Interior* D x W	Model No.	Wt.
24 x 24	SL5-2424-78	223

Shelf clearance from bottom to top: 16.5", 16.5", 12", 10", 10".

<sup>\*</sup> Note: For Outside Dimensions- Depth add 3", Width add 1"





### VISIBLE CONTENTS Welded Storage Cabinet

2000 lbs. Capacity

These stationary security cabinets measure 52" overall height. Small diamond shaped openings and heavy gauge steel provide maximum security for items. The double doors swing open 270 degrees, and feature padlockable slide latch. 46-1/2" interior cabinet height. Footpads have lag holes. 4" underclearance. All-welded steel construction with durable powder coated finish. Available with or without fixed shelves or an adjustable center shelf. The adjustable center shelf adjusts in 3-1/2" increments and is fully removable.



Interior*	No Center Shelf		1 Fixed Center SI	helf	2 Fixed Center Sh	elves	1 Adjustable Center Shelf	
D x W	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.
24 x 48	SCN-2448-NC	174	SC-2448-NC	204	SC2-2448-NC	234	SC-A-2448-NC	230
24 x 60	SCN-2460-NC	184	SC-2460-NC	216	SC2-2460-NC	254	SC-A-2460-NC	240
30 x 48	SCN-3048-NC	184	SC-3048-NC	218	SC2-3048-NC	255	SC-A-3048-NC	246
30 x 60	SCN-3060-NC	233	SC-3060-NC	263	SC2-3060-NC	308	SC-A-3060-NC	291
30 x 72	SCN-3072-NC	284	SC-3072-NC	331	SC2-3072-NC	406	-	_
36 x 60	SCN-3660-NC	280	SC-3660-NC	333	SC2-3660-NC	408	_	_
36 x 72	SCN-3672-NC	338	SC-3672-NC	380	SC2-3672-NC	439	_	_

<sup>\*</sup> Note: For Outside Dimensions- Depth add 3", Width add 1"

## All-Welded Compact Storage Cabinet

This all-welded stationary security lockers is an ideal solution for added security and storage where space is a premium. One welded center shelf provides abundant storage. The single door swings open a full 270 degrees, and features a padlockable slide latch. Footpads have lag holes. 4" underclearance. Durable powder coated finish. 52" overall height. 46-1/2" interior cabinet height. Clearance between shelves is 22-1/2".

Interior* D x W	Model No.	Wt.
24 x 24	SC-1D-2424-NC	124

<sup>\*</sup> Note: For Outside Dimensions- Depth add 3", Width add 1"



## **Two Compartment Compact Storage Locker**

This all-welded storage locker provides two separate locking compartments, perfect for securing tools or supplies on multiple shifts. Doors swing open 270 degrees, and feature padlockable slide latches. Footpads have lag hole for securing to the floor. Durable powder coated gray finish. 4" underclearance for transporting with a pallet jack or forklift. 78" overall height. Clearance between shelves is 34".

Interior* D x W	Model No.	Wt.
24 x 24	SL1-2D-2424	140

<sup>\*</sup> Note: For Outside Dimensions- Depth add 3", Width add 1"



### **STORAGE & SECURITY**





Model SL1-2448-PB

## **Tool Storage Locker**with Pegboard or Louvered Panel

Perfect for your "lean manufacturing" shop. Efficiently organize your tools, supplies, and equipment without clutter. The 16 gauge steel pegboard or louvered panel measures 48" high and accepts most standard hooks and bins and allows you to customize this locker to fit your needs. The 13 gauge steel mesh provides both visibility and security. Doors fully open 270 degrees and feature a padlockable slide latch. One center shelf located directly under pegboard or louvered panel. 72" interior height. 78" overall height with 4" leg clearance to allow transporting by pallet truck or fork lift. (Pegs and bins not included.)

Interior*	Pegboard Panel		Louvered Panel	
D x W	Model No.	Wt.	Model No.	Wt.
24 x 48	SL1-2448-PB	296	SL1-2448-LP	296
24 x 60	SL1-2460-PB	339	SL1-2460-LP	339
30 x 48	SL1-3048-PB	312	SL1-3048-LP	312
30 x 60	SL1-3060-PB	364	SL1-3060-LP	364



Model SL1-2448-LP



Model SSL-LP-2448-LPD



## **High Capacity Storage Bin Cabinet**

All-welded, heavy-duty 12 gauge steel cabinet features built-in 16 gauge louvered panels on back and doors for your hanging bins. Doors swing open 180 degrees to allow complete access. Keyed handle with 3-point locking system secures doors at the top, center, and bottom. Durable powder coated finish. Overall height 78" with 5-1/2" underclearance to permit movement by pallet truck. Bins not included.

			Louvered Panel Dimensions		
Interior D x W	Model No.	Wt.	Door W x H	Cabinet Back W x H	
24 x 48	SSL-LP-2448-LPD	557	18 x 60	48 x 72	
24 x 60	SSL-LP-2460-LPD	667	18 x 60	60 x 72	
30 x 48	SSL-LP-3048-LPD	613	18 x 60	48 x 72	
30 x 60	SSL-LP-3060-LPD	731	18 x 60	60 x 72	





## **High Capacity Storage Cabinet** with Pegboard Doors

All-welded, heavy-duty, 12 gauge steel cabinet. Each door has built-in 16 gauge steel pegboard panels for additional storage. Doors fully open 180 degrees to allow complete access. The pegboards have round holes on 1" centers that accept most common hooks and are perfect for keeping your tools visible and easy to grab. Available with 2 or 3 adjustable 14 gauge shelves that adjust on 3-1/2" increments. Keyed handle with 3-point locking system keeps doors secure. Gray powder coated finish.

Interior D x W	2 Adj. Shelves Model No.	Wt.	3 Adj. Shelves Model No.	Wt.
24 x 48	SSL2-A-2448-PBD	531	SSL3-A-2448-PBD	561
24 x 60	SSL2-A-2460-PBD	612	SSL3-A-2460-PBD	649
30 x 48	SSL2-A-3048-PBD	593	SSL3-A-3048-PBD	630
30 x 60	SSL2-A-3060-PBD	682	SSL3-A-3060-PBD	728



Model SSL2-A-2448-PBD

## Cabinet Style Work Center with Pegboard or Louvered Back

All-welded, heavy-duty, 12 gauge steel cabinet features either a 16 gauge steel pegboard or louvered panel and a 42" high hardboard work surface to efficiently organize, store, and work in one convenient location. 250 lb. capacity drawer measures 26"W x 20"D x 6"H and provides ample storage for loose or hard to hang tools. The heavy-duty drawer features heavy-duty rollers, a full-width recessed handle, and a padlock hasp. Clearance under drawer is 23-1/2". Keyed handle with 3-point locking system keeps doors secure. 5-1/2" ground clearance permits movement by pallet truck.

Interior D x W	Pegboard Panel Model No.	Wt.	Louvered Panel Model No.	Wt.
24 x 48	SSW-2448-HD-PB	517	SSW-2448-HD-LP	517
24 x 60	SSW-2460-HD-PB	604	SSW-2460-HD-LP	604



SSW-2448-HD-PB

### **STORAGE & SECURITY**





### **High Capacity Storage Cabinet**

Rugged, 12 gauge, all-welded cabinet is designed for long term use in the most demanding environments. Secure 3-point latching system with keyed handle secures the doors at the top, center, and bottom. 14 gauge shelves are adjustable in 3-1/2" increments. Doors swing open 180 degrees, allowing complete access to the interior. 1500 lb. shelf capacity. Durable powder coated gray finish. Overall height 78".

	2 Adj. Shelves Model No.	Wt.	3 Adj. Shelves Model No.		4 Adj. Shelves Model No.	Wt.
24 x 48	SSL2-A-2448	446	SSL3-A-2448	476	SSL4-A-2448	506
24 x 60	SSL2-A-2460	527	SSL3-A-2460	564	SSL4-A-2460	601
30 x 48	SSL2-A-3048	502	SSL3-A-3048	539	SSL4-A-3048	576
30 x 60	SSL2-A-3060	591	SSL3-A-3060	637	SSL4-A-3060	683



Model SSL2-A-2448



### **High Visibility Storage Cabinet**

Diamond shaped perforated doors allow visibility to the contents inside while maintaining security and organization. Three-point locking system with keyed handle. 14 gauge shelves adjust in 3-1/2" increments. Doors open 180 degrees allowing full access to the contents inside. Overall height is 78" with 5-1/2" of underclearance to permit movement by pallet truck. Durable gray powder coated finish.

	2 Adj. Shelves Model No.		3 Adj. Shelves Model No.		4 Adj. Shelves Model No.	Wt.
24 x 48	SSLP2-A-2448	437	SSLP3-A-2448	467	SSLP4-A-2448	497
24 x 60	SSLP2-A-2460	518	SSLP3-A-2460	555	SSLP4-A-2460	592
30 x 48	SSLP2-A-3048	493	SSLP3-A-3048	530	SSLP4-A-3048	567
30 x 60	SSLP2-A-3060	582	SSLP3-A-3060	628	SSLP4-A-3060	674





### **HEAVY-DUTY Welded Steel Closed Shelving**

Heavy-duty reinforced 12 gauge steel shelves have 2000 lbs. capacity per shelf and are enclosed on three sides to help protect and store your items. Solid steel sided shelving provides a clean and uniform look. 2" x 2" x 3/16" corner angles have footpads with anchor hole. 72" overall height with 3-1/2" bottom shelf clearance. 3 center shelves with 15" clearance between shelves. Built to last. Durable powder coated gray finish.

Shelf		
D x W	Model No.	Wt.
18 x 32	5SE-1832-72	263
24 x 36	5SE-2436-72	335
24 x 48	5SE-2448-72	429
24 x 60	5SE-2460-72	504



### **HEAVY-DUTY**

### Welded Steel Wall Storage Cabinet

All-welded, heavy-duty 14 gauge steel cabinet with your choice of center shelf, 16 gauge pegboard panel or louvered back panel. Mounting holes on 4" centers at top and bottom for secure wall attachment. Doors swing open 180 degrees to allow complete access. Keyed handle with 3-point locking system secures doors at the top, center, and bottom. Durable powder coated gray finish. Ships set up and ready for immediate use.

Overall Center Shelf		Pegboard Panel		Louvered Panel		
DxWxH	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.
10 x 36 x 24	HC2-36	97	HC-36-PB	103	HC-36-LP	103
10 x 48 x 24	HC2-48	119	HC-48-PB	128	HC-48-LP	128



Model HC2-36



### **HEAVY-DUTY** Tool and Die Shelving

1000 lbs. per shelf Capacity

Two roll-out shelves extend 100% for ease of access. Great for heavy tooling, dies, and large parts that require an overhead crane or forklift to load and unload.

The frame is built of 1/4" thick structural angle. Roll-out shelves are reinforced with 7 gauge steel and 12 gauge decks. Roll-out shelves measure 48" wide x 36" deep. Fixed top shelf provides additional storage space. Shelf clearance is 22". Unit comes with lag holes for anchoring to the floor. Ships partially set up. Some assembly required. Powder coated gray finish.

Overall		
WxDxH	Model No.	Wt.
53 x 36 x 60	HRS-3648-3	585



HRS-3648-3







### HEAVY-DUTY Welded Steel Shelving

Reinforced 12 gauge steel shelves with 2000 lbs. capacity per shelf.  $2" \times 2" \times 3/16"$  corner angles have footpads with anchor. 72" overall height. Boxed angles under bottom shelf and 3-1/2" underclearance. Ships set up and ready for immediate use.

Shelf	4 Shelf Shelf 20-3/4" Shelf Clearance		5 Shelf 15" Shelf Clearance		6 Shelf 11-3/4" Shelf Clearance	
D x W	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.
18 x 32	4SH-1832-72	156	5SH-1832-72	179	6SH-1832-72	206
24 x 36	4SH-2436-72	195	5SH-2436-72	227	6SH-2436-72	268
24 x 48	4SH-2448-72	253	5SH-2448-72	299	6SH-2448-72	352
24 x 60	4SH-2460-72	298	5SH-2460-72	356	6SH-2460-72	421
30 x 48	4SH-3048-72	291	5SH-3048-72	364	6SH-3048-72	426
30 x 60	4SH-3060-72	344	5SH-3060-72	414	6SH-3060-72	491
30 x 72	4SH-3072-72	421	5SH-3072-72	511	-	_
36 x 60	4SH-3660-72	394	5SH-3660-72	475	_	_
36 x 72	4SH-3672-72	478	5SH-3672-72	583	_	_



### WELDED 12 GAUGE Perforated Steel Shelving

Reinforced perforated 12 gauge steel shelves provide abundant storage while allowing dirt and debris to pass through. 1500 lbs. capacity per shelf. 2" x 2" x 3/16" corner angles have footpads with anchor holes for securing to the floor. 72" overall height. Boxed angles under bottom shelf and 3-1/2" underclearance. Fully welded and ready for immediate use.

Shelf	4 Shelf 20-3/4" Shelf Clearance		5 Shelf 15" Shelf Clearance		6 Shelf 11-3/4" Shelf Clearance	
D x W	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.
18 x 32	4SHP-1832-72	131	5SHP-1832-72	144	6SHP-1832-72	164
24 x 36	4SHP-2436-72	160	5SHP-2436-72	182	6SHP-2436-72	214
24 x 48	4SHP-2448-72	208	5SHP-2448-72	255	6SHP-2448-72	286
24 x 60	4SHP-2460-72	248	5SHP-2460-72	296	6SHP-2460-72	346
30 x 48	4SHP-3048-72	241	5SHP-3048-72	287	6SHP-3048-72	351
30 x 60	4SHP-3060-72	289	5SHP-3060-72	349	6SHP-3060-72	413
30 x 72	4SHP-3072-72	361	5SHP-3072-72	441	_	-
36 x 60	4SHP-3660-72	334	5SHP-3660-72	405	_	-
36 x 72	4SHP-3672-72	413	5SHP-3672-72	508	_	_



## HEAVY-DUTY Adjustable Steel Shelving

12 gauge reinforced steel shelves are adjustable on 3-1/2" centers. Fixed top and bottom shelf adds rigidity and strength to prevent any unwanted movement. Your choice of 1, 2, or 3 adjustable center shelves provide a versatile storage solution. 1500 lbs. capacity per shelf. 2" x 2" x 3/16" corner angles have footpads with anchor holes for securing to the floor. 72" overall height. Boxed angles under bottom shelf and 3-1/2" underclearance.


1 Adj. Shelf Shelf 3 Total Shelves		2 Adj. Center Shelf 4 Total Shelves		3 Adj. Center Shelf 5 Total Shelves		
D x W	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.
18 x 32	3SH-A-1832-72	151	4SH-A-1832-72	177	5SH-A-1832-72	203
24 x 36	3SH-A-2436-72	179	4SH-A-2436-72	215	5SH-A-2436-72	251
24 x 48	3SH-A-2448-72	229	4SH-A-2448-72	276	5SH-A-2448-72	323
24 x 60	3SH-A-2460-72	262	4SH-A-2460-72	321	5SH-A-2460-72	380





## SOLID STEEL Rack Decking

Smooth, 14 gauge steel surface with durable powder coated finish. 12 gauge reinforcing channels on underside fit 1-5/8" step beams. 1-1/2" waterfall on front & back edges. Each decking section has a load capacity of 3000 lbs.





Model RD-4846-4

### **Sloped Steel Rack Decking**

1500 lbs. Capacity

Smooth, 14 gauge, powder coated steel that is sloped at 10 degrees to ensure your product is conveniently located and visible to the users. A 1-1/2" lip on each end to retain load. The decking is designed to fit in standard 1-5/8" step beam racking. Each sloped deck is 46" W and available in 3 standard rack depths – 36", 42" and 48".

Deck Size D x W	Model No.	Wt.
36 x 46	RDS-3646-4	63
42 x 46	RDS-4246-4	72
48 x 46	RDS-4846-4	81



### **Punched Steel Rack Decking**

3000 lbs. Capacity

14 gauge steel deck with 1" diameter holes. Deck measures 46" wide. Available in 3 standard rack depths - 36", 42", 48". Durable powder coated gray finish.

Deck Size D x W	Model No.	Wt.
36 x 46	RDP-3646-3	54
42 x 46	RDP-4246-3	60
48 x 46	RDP-4846-4	77




### **Perforated Rack Deck Channels**

Helps you comply with NFPA and Fire Code Regulations

These 14 gauge perforated channels have been designed to meet NFPA and fire code regulations. These 11-1/2" wide rack deck sections are available in 3 standard rack depths - 36", 42", and 48". Durable powder coated finish.

Depth	Model No.	Wt.
36	RDCP-36	10
42	RDCP-42	12
48	RDCP-48	14









#### **Fixed Rack Deck Clearance Bars**

Fixed Rack Deck Bars are used to provide fork truck clearance to non-palletized loads. The unit fits over your pallet racking beams with a 2-1/2" waterfall that is pre-drilled to accept a locating screw. The 3 - 12 gauge supports are securely welded to the frame providing fixed spacing between the supports, making loading and unloading easier. The bars are 46" wide and are available in 3 standard racking depths - 36", 42", 48".

D x W	Model No.	Wt.
36 x 46	FRDB-3646	62
42 x 46	FRDB-4246	70
48 x 46	FRDB-4846	78



#### **Rack Deck Bars**

#### **Rack Deck Clearance Bar**

Provides support for and access to non-palletized loads and can be used for supporting bulky products. The bars are available in 3 standard rack depths - 36", 42", and 48" deep.

#### **Rack Deck Channel**

Rack deck channels are used to locate and support the legs of a basket or container in standard pallet racks. The channels are all welded, 12 gauge steel and powder coated gray. Available in 3 standard rack depths - 36", 42", and 48" deep.

	Rack Deck Channel		Rack Deck Clearance Ba	rs
Depth	Model No.	Wt.	Model No.	Wt.
36	RDC-36	13	RDCB-36	13
42	RDC-42	15	RDCB-42	15
48	RDC-48	17	RDCB-48	17



### **Adjustable Spring Safety Gate**

Adjustable width 22-1/2" to 36". Set screws secure at desired width. Stainless steel torsion spring closes the gate automatically. Spring is tension adjustable, and reversible. Meets OSHA 1910.23b requirements. Powder coated red finish (except spring). Outside tubing 1.37" OD x 12 gauge wall. Mounting channel is 2" x 1" with three mounting holes (hardware not included). Also available with easy mount kit to mount directly on your existing hand rail. Two bolt together clamps hold unit securely to hand rail. No drilling required.

Overall W x D x H	Model No.	Includes	Wt.
24 x 3 x 24	SGS-R	Gate Only	18
24 x 3 x 24	SGS-R-EM	Gate with Easy Mount Kit	20



### **Hydraulic Arm Safety Gate**

Adjustable width 15" to 31". Set screw used to secure at desired width. Gate arm uses hydraulic pressure to smoothly close without slamming. Closing tension is adjustable. Mounting plate is 1-3/8" x 6" with two mounting holes (hardware not included). Mount to the left only. Durable powder coated red finish. Meets OSHA 1910.23b requirements.

Overall W x D x H	Model No.	Wt.
21 x 3-1/2 x 6	SGH-R	10







## Rack Decking with Spill Control Sump

Designed to fit with your existing pallet racks, this spill control platform installs quickly and will contain liquids from dripping below. Top grating is 51" deep x 49" wide with two sump sizes to fit either 42" or 48" deep pallet racks. Both sizes have a 66 gallon sump capacity to help you comply with EPA regulations. Includes drain plug.

Deck W x L x H	Model No.	Description	Wt.
51 x 49 x 8-1/2	SS-RD-5149-42	Fits 42" deep pallet racks	254
51 x 49 x 7-1/2	SS-RD-5149-48	Fits 48" deep pallet racks	240



## **Spill Control Platform for Cabinets**

Gain an extra measure of spill control for your safety cabinets. Constructed from heavy-duty 12 gauge steel, this all-welded sump measures 20" deep x 45" wide x 6" high. Designed to accept most 18" D x 43" W safety cabinets, the platform will contain up to 25 gallons securely and keep any leakages off your floor. Your cabinet sits recessed in the platform by 1" which will allow the cabinet doors to fully open. The low profile design and steel braces in back ensure easy loading of your empty cabinet. Durable gray powder coated finish.

Sump Cap.	Overall W x L	Model No.	Wt.
25 Gallon Cap.	20-1/4 x 45-1/4	SSF-2045	80



### **Spill Control Cart**

3000 lbs. Capacity

This mobile containment cart allows you to store and transport up to four 55 gallon drums. Durable, welded steel construction – stronger than plastic and noncombustible. Sump has removable steel bar grating deck for easy clean-ups. Chemical resistant 6" nonmarking polyurethane casters, two rigid and two swivel. Removable pipe handle with cross brace extends 25" above top of sump.

	2-DRUM with wheel brakes		4-DRUM with floor lock	
Sump Cap.	Model No.	Wt.	Model No.	Wt.
33 Gallon Cap.	SSB-5125-6PYBK	170	_	-
66 Gallon Cap.	SSB-512566-6PYBK	203	SSB-5151-6PYFL	341





### **Spill-Control Platforms**

Heavy-gauge steel construction holds up in applications where plastic units just won't do, either for durability reasons, or when materials being stored are not compatible with plastic. Welded steel bar grating is removable for easy clean-up. Drip channels "hook" units of same heights together, and help prevent drainage between units. Optional ramps available in 2 heights. All models help you comply with EPA and OSHA requirements; models with 66 and 99 gallon capacity help you comply with Uniform Fire Code.

#### **FORKLIFTABLE MODELS**

4-way fork entry with 4" underclearance.

	SUMP CAP.	DIMENSIONS W x L x H	Model No.	Ship Wt.	Capacity Lbs. UDL
2-Drum	33 gal.	51 x 26 x 10.5	SST-5125	138	2000
2-Drum	66 gal.	51 x 26 x 16	SST-5125-66	171	2000
4-Drum	66 gal.	51 x 51 x 10.5	SST-5151	259	4000
6-Drum	99 gal.	76 x 51 x 10.5	SST-5176	381	6000
Ramp*	_	33 x 42 x 10.5	SST-RAMP	95	1500
Drip Channels	-	25-1/2" L	DCC	2	_

<sup>\*</sup>Ramp not for use with SST-5125-66



All platforms feature full height internal support channels with flow-through vents.



Low platform height offers easy access to stored materials, easier loading and unloading of drums.

	SUMP CAP.	DIMENSIONS W x L x H	Model No.	Ship Wt.	Capacity Lbs. UDL
2-Drum	33 gal.	51 x 26 x 6.5	SSB-5125	125	3000
2-Drum	66 gal.	51 x 26 x 12	SSB-5125-66	158	3000
4-Drum	66 gal.	51 x 51 x 6.5	SSB-5151	233	6000
6-Drum	99 gal.	76 x 51 x 6.5	SSB-5176	358	9000
Ramp*	-	33 x 36 x 6.5	SSB-RAMP	70	1500
Drip Channels	-	25-1/2" L	DCC	2	-

<sup>\*</sup>Ramp not for use with SSB-5125-66



Model SSB-5125

# Model SSP-5151



## Spill-Control Platform with Pallet Supports

An economical spill control platform that works with your palletized drums to store liquids while controlling leaks and spills. Deck is constructed from 12 gauge steel with flow through pallet supports to allow fluids to evenly distribute. Each unit is fully welded and powder coated.

	SUMP CAP.	DIMENSIONS W x L x H	Model No.	Ship Wt.	Capacity Lbs. UDL
4-Drum	66 gal.	51 x 51 x 9.75	SSP-5151	213	4000

### SECONDARY CONTAINMENT



## IBC Containment & Dispensing Station

Heavy-gauge steel construction for durability and extended life. Large 400 gallon sump capacity with 10,000 lbs. load capacity. Steel grating deck panels are easily removable for cleaning. Includes drain plug and grounding screw for safer handling of flammable liquids. Helps you comply with EPA requirements.

#### SINGLE IBC UNIT

Large deck surface has room for additional storage. Three-piece steel grating deck is 29" high. "Convertible" deck allows IBC to be positioned for internal dispensing within sump area. Included pail holder shelf attaches conveniently to inside or outside of sump.

Model No.	Overall Size	Capacity	Wt. (lbs.)
SST-IBC	51"W x 76"L x 29"H	400 gal	625

#### **DOUBLE IBC UNIT**

Convenience of storing 2 IBC's side by side, and a lower profile for easier access. Four piece removable grating deck is 23" high. Includes 2 removable pail holder shelves.

Model No.	Overall Size	Capacity	Wt. (lbs.)
SST-IBC-2	51"W x 99"L x 23"H	400 gal	702



Left: Positioned lengthwise with IBC moved back, there is sufficient room to hang pail shelf on inside of sump (one decking panel is removed).

> Below: Positioned widthwise, Pail Shelf can be hung outside of sump, allowing extra storage space on deck.



Model SST-IBC



Model SST-IBC-2

#### **All-Welded IBC Stand**

This all-welded, heavy-duty IBC Stand is built to fit most standard IBC containers and offer a much safer and easier point of access to all IBC connections and valves. The 12 gauge deck stands 34" high and features a 1-1/2" lip on all outside corners to contain the unit while still allowing easy access to the dispensing valve. The unit measures 52"W x 52"L overall.

Model No.	Overall Size	Wt.
IBCS-5252	52"W x 52"L x 35.5"H	163



## Spill Control Platform with Drum Rack

Heavy-gauge steel construction in a drum storage system that positions the drums ready for dispensing. 1- Drum unit has 33 gallon sump capacity and 2- Drum unit has 66 gallon sump capacity. Both include 4 way forkliftable access.

<b>Drum Capacity</b>	Dimensions W x L x H	Model No.	Wt.
1-Drum	26 x 51 x 22	SST-5125-1D	105
2-Drum	51 x 51 x 22	SST-5151-2D	170



### WIRE REEL HANDLING





### **All-Welded Wire Reel Rack**

Sturdy, welded steel reel storage rack features 3 levels. The two upper levels each have three 5/8" dia. spindles, and the lower level includes a single 1" diameter spindle and two 5/8" diameter spindles. Each spindle has 33" of useable width. 150 lbs. capacity per spindle. Welded construction means no assembly. Removable wire guides. Footpads have lag holes to secure to floor. Powder coated finish.

Overall W x D x H	Model No.	Wt.
36 x 30 x 72	RR-3036	178



## Maintenance Cart with Wire Reel Storage

12 gauge shelves have a 1-1/2" lip. Top shelf measures 24"W x 36"L x 35"H. Bottom shelf measures 24"W x 48"L, providing a 12" extension for upright storage and transport. Hanger bar on side of cart for convenient ladder storage. Casters are 5" polyurethane, 2 rigid and 2 swivel with total lock wheel brakes. Overall length is 54". Powder coated gray finish. Ships assembled. Includes five 36" long spool holder rods.

Model No.	Wt.
RCS-2448-5PYTL	163



### Wire Reel Wagon

Wagon type steering combined with choice of cushion-load pneumatic tires or puncture-proof rubber wheels make these trucks ideal for transporting wire spools over the roughest surfaces. 8" long spool rods with cotter pins are up to 14" above the deck spaced 8" apart. Welded unit has 12 gauge steel deck, powder coated finish and ships assembled. Deck measures 24"W x 36"L.

Wheel Type	Model No.	Capacity (lbs)	Wt.
10 x 2.75 Solid Rubber	LWRW2436-10-FSD	1200	96
10 x 3.5 Pneumatic	LWRW2436-10P-FSD	1200	87





#### **Wire Reel Cart**

12 gauge shelves have a 1-1/2" lip. Top shelf 24"W x 36"L x 35"H. Bottom shelf measures 24"W x 48"L, providing a 12" extension for upright storage and transport. Hanger bar on side of cart for convenient ladder storage. Casters are 5" polyurethane, 2 swivel with totallock wheel brakes and 2 rigid. Overall length is 54". Powder coated gray finish. Ships assembled. Includes five 36" long spool holder rods.

Model No.	Wt.
RC2448-5PYTL	139

#### **Wire Reel Cart with Drawers**

Includes two locking storage drawers and three 36" long spool holder rods. Locking drawers measure 13"W x 17"L x 4-1/2"H inside.

Model No.	Wt.
RC2448-5PYTL2DR	175



### Wire Reel Cart with Pegboard or Louvered Panel

Your choice of either 16 gauge louvered or pegboard panel on the welded handle end provides additional tool or small parts storage. Tubular handle extends 17" allowing for ample hand space when bins and tools are stored. 12 gauge shelves have a 1-1/2" lip. Top shelf 24"W x 36"L x 35"H. Bottom shelf measures 24"W x 48"L, providing a 12" extension for upright storage and transport. Hanger bar on side of cart for convenient ladder storage. Cart rolls smoothly on 2 rigid and 2 swivel 5" non-marking polyurethane wheels. The swivel casters lock both the wheel and the swivel to stop movement and position unit securely in place. Overall length is 65". Powder coated gray finish. Ships fully assembled and ready for immediate use. Includes five 36" long spool holder rods.

	Model No.	Wt.
Pegboard	RCPB-2448-5TL	156
Louvered	RCLP-2448-5TL	156



## Wire Reel Cart with Pegboard or Louvered Panels

Double-sided pegboard or louvered panels allow you to transport and store your wire reels, tools, small parts and accessories on one convenient cart. Your choice of factory installed 16 gauge pegboard or louvered panels allow you to customize the cart to meet your need. Tubular handle extends 17" allowing for ample hand space while bins and tools are stored. 1-1/2" retaining lips on both shelves help contain load. Seven 38" wide rods for holding multiple wire reel configurations. Overall height 41-1/2"H. All-welded. Durable powder coated gray finish.

	Overall W x D x H	Model No.	Wt.
Pegboard Panels	24 x 54-1/4 x 41-1/2	RL-PB-2436-TL	164
Louvered Panels	24 x 54-1/4 x 41-1/2	RL-LP-2436-TL	164



### WIRE REEL HANDLING





Model RT4-8S

### **Wire Reel Caddy**

300 lbs. Capacity

Welded frame wire reel caddy comes with four 16" wide rods for holding multiple wire reel configurations with 7 available positions. Wheels are off the ground while standing so it does not "walk" while pulling wire. Full-width handle. Convenient tool tray for storage and transport of hand-tools. Heavy-duty angle iron frame. Wheels are 8" x 2-1/2" solid rubber with ball bearings. Durable powder coated gray finish. Ships via UPS!

Overall W x D x H	Model No.	Wt.
25 x 19-1/2 x 45	RT4-8S	54







### **Heavy-Duty Reel Caddy**

Three (3) heavy-duty steel spindles are 1" diameter bar stock secured with set screws, and will accept reels up to 12" diameter and 21" wide. For larger diameter spools, simply remove 1 or more of the spindles. Large 12" diameter pneumatic wheels have roller bearings for transporting over rough surfaces. Save space, use and store vertically or horizontally. Capacity 150 lbs. per spindle. Three wire guides for dispensing. Convenient top tray measures 10" x 24". Welded unit has a powder coated finish and ships set up and ready for immediate use.

Overall W x D x H	Model No.	Wt.
36 x 31 x 45	RT3-12P	90





### Wire Reel Cart with Cabinet

12 gauge shelves have a 1-1/2" lip. Top shelf is 24"W x 36"L x 35"H. Storage cabinet with locking door and keyed handle measures 16"W x 23"D x 25"H. Bottom shelf is 24"W with a 12" extension for upright storage and transport of long material. Hanger bar on side of cart for ladder storage. 5" polyurethane casters, 2 swivel with total lock wheel brakes and 2 rigid. Overall length is 54". Durable powder coated gray finish. Includes five 15" long spool holder rods.

Model No.	Wt.
RCM2448-5PYTL	152



#### Wire Reel Cart

Mobile Wire Reel Cart is ideal for transporting your spools of wire and other materials from job to job. Four 16" wide rods with 7 available positions hold multiple wire reel configurations. Solid bottom shelf allows additional storage. Rolls smoothly on 5" non-marking polyurethane wheels. 2 rigid and 2 swivel casters with total lock brakes secure the unit in place and keep it from "walking" while in use. Available with an open back or 16 gauge louvered panel back.

**OPEN BACK** – allows unrestricted access to storage on the 18" x 32" deck.

Model No.	Wt.
RT4-5TL	56



RT4-5TL

**LOUVERED PANEL BACK** – 18"W x 36"H 16 gauge louvered panel allows you to add your own hanging bins for additional small parts storage.

Model No.	Wt.
RT4-5TL-LP	65



### **Maintenance Cart** with Cabinet and Drawers

1200 lbs. Capacity

All-welded, 12 gauge construction. Top work surface measures 24" x 36" and features a front flush edge and 1-1/2" retaining lips on sides and back. 4 locking storage drawers measuring 13"W x 17"L x 4-1/2"H. 27"H enclosed cabinet with locking door. 12" extension on the bottom for upright storage and transport. Hanger bar on side of cart for ladder storage. Casters are 5" polyurethane, 2 swivel with total lock wheel brakes and 2 rigid. Overall length is 54". Gray powder coated finish.

Model No.	Wt.
RCM2448-TL-4DR	236











Single Sided Frame Shown with Optional Shelves AFS-2440-6PH



A-Frame Only AFS-3640-6PH



AF-ARM 4 attachments shown

### **Adjustable Tray A-Frame Shelf Trucks**

2000 lbs. Capacity

Use in your Lean Manufacturing facility to transport and store components or finished products where and when you need them. Slotted steel uprights accept shelves, arms, trays, and pegboard panels making this a versatile ergonomic product. Mix and match to fit your exact requirements. Since it is adjustable, you can reconfigure the truck as your needs change. Available as a single-sided or double-sided unit. All-welded construction with a durable powder coated finish and 2 rigid and 2 swivel 6" phenolic wheels.

		Phenolic Wheels		Polyurethane Wheels	3
A-Frame Only	WxDxH	Model No.	Wt.	Model No.	Wt.
Single-sided	40 x 24 x 67	AFS-2440-6PH	72	AFS-2440-6PY	70
Double-sided	40 x 36 x 67	AFS-3640-6PH	92	AFS-3640-6PY	90
Double-sided w/bottom shelves	40 x 36 x 67	AFSF-3640-6PH	116	AFSF-3640-6PY	114

#### ALL SHELVES AND ACCESSORIES SOLD SEPARATELY

9" DEEP TRAYS are 3" high on 3 sides. Open front side available with a 1" lip, or flush edge.

**15" DEEP TRAYS** are 6" high on 3 sides with handles on both ends. Open front side available with 1" lip, or a flush edge.

**FLUSH SHELVES** have a 1-1/2" lip along the back, flush edge on 3 sides. Ideal for long and oversize items.

**PEGBOARD AND LOUVERED PANELS** are 16 gauge formed steel panels that accept most standard hooks and bins. (Pegs and bins not included.)

**ROUND TUBING ARM ATTACHMENTS (AF-ARM)** are 1-1/4" OD, 8" inside length and adjustable on 3-1/2" increments. Perfect for carrying tubing and bar stock.

		Front	Max per frame		
Tray Model No.	WxDxH	Edge	1-sided	2-sided	Wt.
AF-SHELF-9	36 x 9 x 3	flush	8	16	25
AF-SHELF-9-LU	36 x 9 x 3	1" lip	8	16	25
AF-SHELF-15	36 x 15 x 6	flush	5	10	33
AF-SHELF-15-LU	36 x 15 x 6	1" lip	5	10	33
AF-SHELF-FLUSH	36 x 15 x flush	flush	16	32	19
AF-PB	36 x 1 x 24	NA	2	4	17
AF-LP	36 x 1 x 24	NA	2	4	17
AF-ARM*	8" inside length	_	7 pairs	14 pairs	3

<sup>\*</sup> Order each individually

### **Adjustable Shelf Rack**

Configure this rack to your exact "lean manufacturing" requirements. Standard model includes two 15" deep x 36" wide shelves that are adjustable on 3-1/2" increments. Add optional accessories to customize the rack to fit your needs. The 9-1/4" high deck surface measures 9" deep x 42" across with 1" retaining lip. All-welded construction with 2 swivel and 2 rigid 6" phenolic wheels and powder coated surface.

W x D x H Model No.		Wt.
40 x 36 x 67	ABS-3640-6PH	154

#### **Additional Flush Shelves**

1-1/2" lip along the back, flush edge on 3 sides. Ideal for long and oversize items.

Model No.	Wt.
AF-SHELF-FLUSH	19





### ERGONOMIC Bar Cradle Truck

3000 lbs. Capacity

Ergonomic 20" Bed Height - Less bending means easier loading and unloading, and keeps material closer to most machine heights.

Highly Maneuverable - Four swivel casters with 6" hard tread phenolic wheels allow movement in any direction. Useful in tight work areas with long loads and when moving around corners.

3000 lbs. Capacity Each - Use for both transport and storage. Combine multiple units for greater capacity and to support longer loads. Loads on single units must be centered on truck.

Overall W x L x H	Cradle ID W x H	Model No.	Wt.
24 x 24 x 34	21" x 14"	ERBST-2424-6PH	75
24 x 36 x 34	21" x 14"	ERBST-2436-6PH	83
24 x 48 x 34	21" x 14"	ERBST-2448-6PH	91



### **Portable Bar & Pipe Truck**

Rugged, all-welded construction with 3 load levels. Structural channel uprights with 1-1/2" square tube arms have 4-1/2" high stops on ends for load retention. 12 gauge steel lower deck stores and transports smaller parts, packages, etc. Platform height 11", overall height 59".

Available with your choice of either 4 swivel casters with wheel brakes, or 2 rigid and 2 swivel casters with a floor lock. 8" x 2" phenolic wheels for ease of movement.

Capacity 3600 lbs. overall, 2000 lbs. per level evenly distributed. Horizontal storage space (each side): Top = 7-1/2", Middle = 11", Bottom = 15"

	4 Swivel Casters with Brakes		2 Swivel, 2 Rigid Cas with Floor Lock	sters
Deck Size	Model No. Wt.		Model No.	Wt.
36 x 48	BRT-3648-8PHBK	195	BRT3648-2R8PHFL	198
36 x 60	BRT-3660-8PHBK	215	BRT3660-2R8PHFL	218
36 x 72	BRT-3672-8PHBK	236	BRT3672-2R8PHFL	239



### **Big Wheel Cradle Truck**

Carries a variety of loads, including lumber, tool boxes, and pipe up to 20" diameter. Extra large 16" pneumatic wheels with roller bearings and 4-ply tires roll over the roughest surfaces. Carrier bed is constructed of 3/16" plate and measures 30" long x 12" x 12".

Offset "T" handle allows for 2 hand grip and greater control of load.

Model No.	Capacity	Wt.
TB-1	1000 lbs.	90





### **BAR & PIPE HANDLING**





Model CBR-2448





### WELDED Cantilever Rack

4000 lbs. Capacity

This single-sided rack allows for efficient storage of bar stock, tubing, angles, and other long and bulky materials. The all-welded steel construction features structural channel frame, base, and arms. Removable retainer pipes at ends of arms extend 5" high to provide secure load retention. Each bay provides 15" of vertical storage space. Powder coated finish. 1500 lbs. capacity per level, not to exceed 4000 lbs. overall.

**Stationary Models:** 51" overall height, with lag holes in base for anchoring to floor.

**Mobile Models:** 8" x 2" Phenolic casters, 2 swivel with wheel brakes, 2 rigid, 61" overall height.

				Base	Us	eable De	epth
<b>Stationary</b>		Mobile		Overall	Base	Arı	ms
Model No.	Wt.	Model No.	Wt.	D x W		Center	Upper
CBR-2448	150	CBR-2448-8PHBK	185	24 x 48	17	13	10
CBR-3060	186	CBR-3060-8PHBK	221	30 x 60	23	19	16



#### **Vertical Bar Rack**

Frees up floor space by storing odd shapes & lengths vertically. Bays are 10-1/2" wide with security chain and hooks. Capacity 1500 lbs. per bay. Overall height 60". Available in 3, 4, and 5 bay versions. Base has holes for mounting to floor.

3 Bays		4 Bays		5 Bays	
36"W x 24"I	36"W x 24"D 48"W x 24"D		48"W x 24"D		D
Model No.	Wt.	Model No.	Wt.	Model No.	Wt.
BR-2436-60	77	BR-2448-60	87	BR-2460-60	98



### **Vertical Bar Rack**

24" D x 36" W 12 gauge steel base. Includes 3 trays - 6", 9-1/2", and 13" deep to hold loose items. Uprights are 1-1/2" angle with an overall height of 84". The three bays are 10" wide and include security chains and hooks. Base has punched holes ready for mounting to the floor. All-welded construction, ships fully assembled and ready for use. Durable powder coated gray finish.

Overall W x D x H	Model No.	Wt.
36 x 24 x 84	BR-2436-84	120



### **Pipe Stake Trucks**

Ideal for transporting roll goods and other long, bulky loads. Removable 1-5/16" diameter pipe stakes extend 30" above the reinforced 12 gauge deck. 2 rigid and 2 swivel casters with brakes.

	8" x 2" MOLD-ON R 2400 lbs. Capacity	UBBER	8" x 2" POLYURETH 3600 lbs. Capacity	IANE
Deck Size	Model No. Wt.		Model No.	Wt.
24 x 36	NBP-2436-8MRBK	88	NBP-2436-8PUBK	79
24 x 48	NBP-2448-8MRBK	99	NBP-2448-8PUBK	90
24 x 60	NBP-2460-8MRBK	118	NBP-2460-8PUBK	109
30 x 48	NBP-3048-8MRBK	119	NBP-3048-8PUBK	110
30 X 60	NBP-3060-8MRBK	131	NBP-3060-8PUBK	125
36 X 72	NBP-3672-8MRBK	161	NBP-3672-8PUBK	152



### **6-Wheel Pipe Stake Trucks**

Two center-mount rigid and four swivel casters for maneuverability and load stability. Deck is 9" high with 1/2" tilt.

	6" x 2" POLYURETHANE 3600 lbs. Capacity			
<b>Deck Size</b>	Model No.	Wt.		
24 x 48	NBP6W-2448-6PY	117		
24 x 60	NBP6W-2460-6PY	127		
30 x 48	NBP6W-3048-6PY	132		
30 X 60	NBP6W-3060-6PY	151		
36 X 72	NBP6W-3672-6PY	182		



### **Heavy-Duty Pipe Stake Trucks**

Center mounted 12" x 2-1/2" load wheels with two 8" x 2" swivel casters arranged in a diamond pattern. Deck is 14" high with 1/2" tilt.

	RUBBER TREAD ON STEEL WHEELS 3000 lbs. Capacity		POLYURETHANE TO ON STEEL WHEELS 4000 lbs. Capacity	
Deck Size	Model No.	Wt.	Model No.	Wt.
24 x 48	R-2448-DIA-4PS	173	DT-2448-DIA-4PS	190
30 x 48	R-3048-DIA-4PS	181	DT-3048-DIA-4PS	198
30 X 60	R-3060-DIA-4PS	192	DT-3060-DIA-4PS	209
30 X 72	R-3072-DIA-4PS	201	DT-3072-DIA-4PS	219
36 X 60	R-3660-DIA-4PS	202	DT-3660-DIA-4PS	219
36 X 72	R-3672-DIA-4PS	215	DT-3672-DIA-4PS	232




### **Roll Goods Truck**

3600 lbs. Capacity

Welded uprights on two sides of the 12 gauge steel deck are heavy 1-5/16" O.D. tubing. Uprights extend 48" above the deck, with a welded top cross brace for additional strength and rigidity. 2 swivel and 2 rigid casters with 6" x 2" non-marking polyurethane wheels. Durable powder coated finish.

Deck	Model No.	Wt.
24 x 48	OE-2448-6PY	136
24 x 60	OE-2460-6PY	148
30 x 48	OE-3048-6PY	145
30 x 60	OE-3060-6PY	161





### **SHEET & PANEL HANDLING**





#### **Lumber & Panel Cart**

3600 lbs. Capacity

Versatile truck transports plywood panels and drywall, as well as lumber, pipe, and other long bulky products. Uprights are 27" and 36" high above the 12 gauge steel deck. Uprights are spaced 6" apart on 24"W deck, 6" and 12" on 30"W deck. Non-marking 6" x 2" polyurethane wheels with 2 rigid and 4 swivel casters. Overall height 45".

Deck	Model No.	Wt.
24 x 48	LC-2448-6PY	99
30 x 48	LC-3048-6PY	109



#### **Perforated Deck Lumber Cart**

2000 lbs. Capacity

Four swivel casters with 6" polyurethane wheels for maneuverability in the tightest spaces. Perforated steel deck prevents accumulation of moisture and debris. Inside rail height 34", outside rail height 24" above deck. Inside rail spacing 9", outside rail spacing 5-1/2". Powder coated gray finish.

Overall W x L	Model No.	Wt.
24 x 36	LCP-2436-S-6PY	96



### **Adjustable Bar Rack Truck**

Double sided A-Frame configuration creates a versatile workhorse for a variety of load requirements. The 9-1/4" high deck surface measures 9" deep x 42" across with 1" retaining lip. Includes 2 pair (4 total) of 1-1/4" OD tubular hooks that are 9" deep and adjustable on 3-1/2" increments. Perfect for carrying tube, bar stock, panels and anything you can think of with this versatile product. All-welded construction with 2 swivel and 2 rigid 6" phenolic casters.

WxDxH	Model No.	Overall Capacity	Wt.
40 x 36 x 67	ABR-3640-6PH	2000 lbs.	119

#### Additional 1-1/4 Round Tubing Arm

Model No.	Pair Capacity	Wt.
AF-ARM	200 lbs.	3





### **Adjustable Sheet & Panel Truck**

Ideal for large or small quantities of plywood, drywall, or other sheet material. Includes two heavy-duty uprights that extend 27" above the deck and can be placed in any of four positions. Also great for rolled goods, office partition panels, folding tables or use as a standard platform truck. Two rigid and two swivel casters with choice of wheels provide plenty of carrying capacity.

Wheel type	Deck Size	Model No.	Wt.
6" x 2"	24 x 36	APT-2436-6PY	99
Non-marking	24 x 48	APT-2448-6PY	117
Polyurethane Wheels	24 x 60	APT-2460-6PY	134
3600 lbs	30 x 48	APT-3048-6PY	132
Capacity	30 x 60	APT-3060-6PY	150
Capacity	30 x 72	APT-3072-6PY	170
	36 x 60	APT-3660-6PY	165
	36 x 72	APT-3672-6PY	187

For 6" Phenolic Wheels, use wheel code: **-6PH** (3600 lbs. Capacity) For 6" Mold-On Rubber, use wheel code: **-6MR** (2000 lbs. Capacity) For Wheel Brakes on Swivel Casters, add: **-BK** 

### Additional Uprights for added storage and Optional Pushbar Handle

	Model No.	Size W x L	Wt.
Additional	004-0011	for 36" long decks	15
Uprights	004-0024	for 48" long decks	18
	004-0023	for 60" long decks	21
	004-0223	for 72" long decks	24
Pushbar	003-0129	for 24" wide decks	13
Handles	003-0131	for 30" wide decks	14
	003-0132	for 36" wide decks	15

**LIP ATTACHMENT**– Optional 1-1/2" lip attachment inserts into deck and allows improved access from side of truck.

Model No. Size		Wt.
APT-LIP-36	for 36" long decks	5
APT-LIP-48	for 48" long decks	6
APT-LIP-60	for 60" long decks	7
APT-LIP-72	for 72" long decks	9



## Adjustable Sheet & Panel Truck with Perforated Deck

2000 lbs. Capacity

Versatile panel truck is great for moving sheets of plywood, drywall, or any other sheet material. Heavy-duty 12 gauge deck with round perforations. Includes two upright dividers that extend 27" above the deck. Uprights can be placed in 4 positions. Two rigid and two swivel casters with 6" x 2" non-marking polyurethane wheels. Additional uprights, pushbar handle, or lip attachment are available.

Deck Model No.		Wt.
24 x 36	APTP-2436-6PY	95
24 x 48	APTP-2448-6PY	111









Model APT6W-2460-6PY

### 6-Wheel Adjustable Sheet & **Panel Truck**

3600 lbs. Capacity

Perfect for moving plywood, drywall, or any sheet products in tight quarters. Six-wheel design ensures high maneuverability and "zero turn" capability. Rolls smoothly on 6" nonmarking polyurethane wheels. Includes two heavy-duty uprights that extend 27" above the deck and are adjustable in four positions. Additional uprights are also available.

Deck Size	Model No.	Wt.
24 x 48	APT6W-2448-6PY	131
24 x 60	APT6W-2460-6PY	148
30 x 48	APT6W-3048-6PY	146
30 x 60	APT6W-3060-6PY	164
30 x 72	APT6W-3072-6PY	184
36 x 60	APT6W-3660-6PY	179
36 x 72	APT6W-3672-6PY	201



### **Adjustable Sheet & Panel Rack**

Ideal for stationary storage of panels and sheet material. Smooth 12 gauge steel deck has 4" underclearance. Supplied with 3 upright dividers that extend 27" above the deck. Legs have foot pads with anchor holes.

Deck Size		
D x W	Model No.	Wt.
30 x 48	ASR-3048	137
30 x 60	ASR-3060	160
36 x 60	ASR-3660	176

Additional uprights may be ordered separately.

Model No.	Size W x L	Wt.
004-0024	for 48" long decks	18
004-0023	for 60" long decks	21



### **Vertical Sheet Rack**

Welded construction with 1-5/16" OD tubular dividers on a base of square tubing and angle iron that includes lag down holes and keeps stored materials up off the floor. Storage bays (4 total) are 7" wide with 1500 lbs. capacity each. Upright dividers are 27", 36", and 42" high. Frame and uprights are all-welded and coated in a durable gray powder coat for long-lasting performance.

Overall		
WxDxH	Model No.	Wt.
48 x 36 x 43-1/2	SR-3648	95

### **Adjustable Sheet Rack**

Upright dividers adjust on 2" increments allowing the user to configure the rack to their individual specifications. Ships knocked down to save on freight.

Overall		
WxDxH	Model No.	Wt.
48 x 36 x 43-1/2	SR-3648-KD	94





#### "A" Frame Sheet & Panel Truck

2000 lbs. Capacity

Panels can be loaded on both sides, with room between the uprights to transport additional materials.12 gauge deck has a 1-1/2" retaining lip on each side. Frame is 48" above deck with uprights 12" apart at the base. 6" phenolic casters, 2 swivel and 2 rigid, or 4 swivel for maneuverability.

	4 Swivel Casters		2 Swivel/2 Rigid Casters	
Size	Model No.	Wt.	Model No.	Wt.
24 x 36	AF2436	108	AF2436-2R	107
24 x 48	AF2448	122	AF2448-2R	121
24 x 60	AF2460	137	AF2460-2R	136
30 x 48	AF3048	134	AF3048-2R	134
30 x 60	AF3060	150	AF3060-2R	149
30 x 72	AF3072	167	AF3072-2R	166
36 x 72	AF3672	184	AF3672-2R	183

Floor Lock: Available on models with 2 rigid casters, add: **-FL** For 6" x 2" Polyurethane Casters, use wheel code: **-6PY** 



Floor Lock

## "A" Frame Sheet & Panel Truck with Back Shelf Storage

2000 lbs. Capacity

Combine the great features of our "A" Frame Truck with 4 storage shelves on the back side to store larger parts or tools. Deck has a 1-1/2" retaining lip on front side. Frame is 51" above deck. 2 rigid and 2 swivel casters with 6" polyurethane wheels mean smooth transport through your facility. A floor lock is mounted on the swivel caster end to securely position the unit. 60" overall height.

Size	Model No.	Wt.
24 x 36	AF4S-2436-6PYFL	192
24 x 48	AF4S-2448-6PYFL	219
24 x 60	AF4S-2460-6PYFL	247



## Convertible Sheet and Panel Truck

2000 lbs. Capacity

This is a versatile sheet and panel truck that offers a 16" x 45" drop-down shelf to handle small parts and tools in addition to large sheets when transporting loads. The tray easily drops down out of the way when used as a conventional panel truck. To use the shelf, you simply raise the shelf up and engage the two shelf hooks along the back edge. The 24" x 48", 12 gauge steel deck has a 1-1/2" retaining lip on the front and is open on the ends to allow oversized loads. 6" non-marking polyurethane wheels are mounted on 2 rigid and 2 swivel casters. The floor lock is mounted on the swivel caster end and prevents movement when loading and unloading. This all-welded unit ships fully assembled and ready for use. Durable gray powder coated finish.

Size	Model No.	Wt.
24 x 48	BOP-2448-6PYFL	147





### **SHEET & PANEL HANDLING**





### **Panel Truck**

1000 lbs. Capacity

For transporting panels, roll goods, and other long items. Three removable uprights extend 27" above the deck. Load space between uprights is 9-1/2". Swivel casters have 5" non-marking polyurethane wheels. Available with choice of wood or carpet covered wood rails to protect the load.

	Model No.	Size W x L	Wt.
Wood Ends	PT-2436-5PY	24 x 36	78
Carpeted Ends	PTC-2436-5PY	24 x 36	80



### **Drywall Cart**

2000 lbs. Capacity

The open steel deck is 12 gauge 14" x 44" and is sloped back to help retain the load. Heavy-duty panel cart designed to easily transport heavy panels such as drywall or plywood. Available with your choice of casters: four swivel or 2 swivel and 2 rigid with a floor lock. Overall 24"W x 44"L x 51"H.

4 Swivel		2 Rigid, 2 Swivel & Floor Lock	
Model No.	Wt.	Model No.	Wt.
DC-2444-8PY	98	DC-2444-2R8PYFL	103



## **Drywall Cart** with Steel Bumper Frame

2000 lbs. Capacity

All the great features of our standard drywall cart with the added protection of a tubular steel bumper frame surrounds the perimeter to protect doorways and walls. Steel deck is 12 gauge,14" x 44" and sloped to help retain the load. Available with your choice of casters: four swivel or 2 swivel and 2 rigid with a floor lock. 8" x 2" non-marking polyurethane wheels. Overall 26"W x 54"L x 51"H.

	4 Swivel		2 Rigid, 2 Swivel & Floor Lock	
	Model No.	Wt.	Model No.	Wt.
•	DCB-2654-8PY	136	DCB2654-2R8PYFL	141





#### **Pallet Dollies**

Convenient, easy-rolling maneuverability for pallets and crates. Four swivel casters with 6" x 2" phenolic wheels and 3600 lbs. capacity. Welded steel construction with durable powder coated finish ships fully assembled. Deck height is 9". Available with double floor locks to prevent unwanted movement. Also available with removable pipe handle that extends 29" above the deck.

SIZE	Model No.	Wt.	Model No.	Wt.
WxL	Dolly Only		Dolly With Floor Locks	
40 x 48	PD-4048-6PH	75	PD-4048-6PH2FL	85
42 x 48	PD-4248-6PH	76	PD-4248-6PH2FL	86
48 x 48	PD-4848-6PH	77	PD-4848-6PH2FL	87
SIZE	<b>Dolly With Handle</b>		With Handle & Floor Locks	
40 x 48	PDH-4048-6PH	87	PDH-4048-6PH2FL	97
42 x 48	PDH-4248-6PH	88	PDH-4248-6PH2FL	98
48 x 48	PDH-4848-6PH	89	PDH-4848-6PH2FL	99

Also available with Corner Load Retainers to keep pallet in position; add **-LR** 





### **Pallet Dolly with T-Handle**

All-welded pallet dolly with "T-handle" for easy pulling of loaded dolly. Includes two vinyl handgrips for comfortable grip. 2 swivel, 2 rigid 6" x 2" phenolic casters. 3600 lbs. capacity.

SIZE	Dolly with Pull Handle			
WxL	Model No.	Wt.	Model No.	Wt.
40 x 48	PDT-4048-6PH	81	PDT-4048-6PHFL	86
42 x 48	PDT-4248-6PH	82	PDT-4248-6PHFL	87
48 x 48	PDT-4848-6PH	83	PDT-4848-6PHFL	88

For Corner Load retainers; add -LR



### **Pallet Dolly with Fork Pockets**

This all-welded 12 gauge solid deck pallet dolly features two full-length fork pockets with 6" wide fork openings on 24" centers. Deck is 14-1/4" high. Four swivel, 6" phenolic casters with two floor locks to keep your load stationary while loading and unloading. All-welded steel construction. Durable powder coated gray finish. 3600 lbs. capacity.

	Without Floor Locks		With Floor Locks	
Deck Size	Model No.	Wt.	Model No.	Wt.
40 x 48	PDS-40-6PHFP	110	PDS-40-6PHFP2FL	120
42 x 48	PDS-42-6PHFP	113	PDS-42-6PHFP2FL	123
48 x 48	PDS-48-6PHFP	133	PDS-48-6PHFP2FL	143

For Corner Load retainers; add -LR









### **Solid Deck Pallet Dolly**

Pallet-sized dollies with a solid deck. Available with optional push handle. Decks are 12 gauge steel. 6" high-capacity phenolic wheels on four swivel casters are long-lasting and easy rolling on smooth floors. Order with 2 floor locks when you need to keep dolly in place while loading or unloading. Also available with removable pipe handle that extends 29" above the deck.

SIZE	Model No.	Wt.	Model No.	Wt.
WxL	Dolly Only		Dolly With Floor Locks	
40 x 48	PDS-4048-6PH	115	PDS-4048-6PH2FL	125
42 x 48	PDS-4248-6PH	118	PDS-4248-6PH2FL	128
48 x 48	PDS-4848-6PH	128	PDS-4848-6PH2FL	138
SIZE	Dolly With Handle		With Handle & Floor	Locks
40 x 48	PDSH-4048-6PH	127	PDSH4048-6PH2FL	137
42 x 48	PDSH-4248-6PH	130	PDSH4248-6PH2FL	140
48 x 48	PDSH-4848-6PH	140	PDSH4848-6PH2FL	150



Also available with Corner Load Retainers to keep pallet in position; add **-LR** 



## **Solid Deck Pallet Dolly with T-Handle**

All-welded, solid deck, steel pallet dolly with bolt-on "T-handle" for improved maneuverability. Deck height - 9". Two rigid and two swivel casters with 6" phenolic wheels. Available with an optional floor lock. Gray powder coated finish.

SIZE	Dolly with Pull Handle		Dolly with Pull Handle & One Floor Lock	
WxL	Model No.	Wt.	Model No.	Wt.
40 x 48	PDST-4048-6PH	121	PDST-4048-6PHFL	126
42 x 48	PDST-4248-6PH	124	PDST-4248-6PHFL	129
48 x 48	PDST-4848-6PH	134	PDST-4848-6PHFL	139

For Corner Load retainers; add -LR



## **Towable Solid Deck Pallet Dollies**

2400 lbs. Capacity

All-welded, solid 12 gauge towable pallet dolly with pin and clevis rear coupler features 1" load retainers on all four corners to keep the pallet in place during transport. The versatile ring type wishbone coupler with 2-1/2" I.D. ring can also be used with most pintle hitches. Two swivel, two rigid 8" mold-on rubber wheels. Caster steer design keeps the wheels under the load for better stability. The reinforced steel deck is 11" high. Durable powder coated gray finish.

Deck Size Model No.		Wt.
40 x 48	PDCS-40-8MR	127
42 x 48	PDCS-42-8MR	130
48 x 48	PDCS-48-8MR	140



### ERGONOMIC ADJUSTABLE HEIGHT Mobile Pallet Stand

3600 lbs. Capacity

Skid-sized deck is raised to a comfortable work height to lessen bending and back strain. Platform height is adjustable between 24" and 34" in 2" increments to optimize ergonomic height for bending and lifting. Rolls smoothly on 6" swivel casters with phenolic wheels. Dual floor locks keep unit in place when loading and unloading. Available with a 12 gauge solid or open deck. All-welded steel construction is powder coated for durability. Ships fully assembled.

SIZE	SOLID DECK		OPEN DECK	
W x L	Model No.	Wt.	Model No.	Wt.
40 x 48	PDSE4048-6PH2FL	157	PDE-4048-6PH2FL	107
42 x 48	PDSE4248-6PH2FL	163	PDE-4248-6PH2FL	109
48 x 48	PDSE4848-6PH2FL	173	PDE-4848-6PH2FL	114



Model PDE-4848-6PH2FL

### ERGONOMIC ADJUSTABLE HEIGHT Mobile Pallet Stand with Handle

3600 lbs. Capacity

Move pallets without a forklift! This ergonomic pallet dolly features an adjustable height deck to reduce back strain when bending and lifting and a removable pipe handle that extends 14" above the deck. Height is adjustable in 2" increments from 24" – 34". Rolls smoothly on 6" swivel casters with phenolic wheels. Dual floor locks keep unit in place when loading and unloading. Available with an open deck or solid 12 gauge steel deck. Powder coated for durability. Ships fully assembled.

SIZE	SOLID DECK		OPEN DECK	
WxL	Model No.	Wt.	Model No.	Wt.
40 x 48	PDSEH40486PH2FL	169	PDEH4048-6PH2FL	119
42 x 48	PDSEH42486PH2FL	179	PDEH4248-6PH2FL	121
48 x 48	PDSEH48486PH2FL	185	PDEH4848-6PH2FL	126



Model PDEH4848-6PH2FL

### **Fixed Height Mobile Pallet Stand**

3600 lbs. Capacity

All-welded pallet dolly with raised 30" deck height to lessen bending and back strain. Available with an open deck or solid 12 gauge steel deck. 6" swivel casters with phenolic wheels and two floor locks to stop unwanted movement during loading and unloading. All-welded construction with durable gray powder coated finish.

SIZE SOLID DECK			OPEN DECK	
W x L	Model No.	Wt.	Model No.	Wt.
40 x 48	PDFS4048-6PH2FL	152	PDF-4048-6PH2FL	102
42 x 48	PDFS4248-6PH2FL	158	PDF-4248-6PH2FL	104
48 x 48	PDFS4848-6PH2FL	168	PDF-4848-6PH2FL	109



Model PDFS4848-6PH2FL







# ERGONOMIC ADJUSTABLE HEIGHT Mobile Pallet Stand with Lower Deck

3600 lbs. Capacity

Reduce bending and back strain with this Ergonomic Adjustable Height Mobile Pallet Stand. 12 gauge solid deck platform is adjustable between 24" and 34" high in 2" increments to optimize ergonomic height for bending and lifting. Solid lower shelf for additional storage. Shelf clearance is 12" - 22". 6" swivel casters with phenolic wheels. Dual floor locks keep unit in place when loading and unloading. All-welded steel construction is powder coated for durability. Ships fully assembled.

#### With Handle

All the great features of our Adjustable Height Mobile Pallet Stand with an added handle to easily move pallets without the need of a forklift.

<b>Deck Size</b>			With Handle	
WxL	Model No.	Wt.	Model No.	Wt.
40 x 48	2PDSE40486PH2FL	216	2PDSEH40-6PH2FL	228
42 x 48	2PDSE42486PH2FL	225	2PDSEH42-6PH2FL	237
48 x 48	2PDSE48486PH2FL	243	2PDSEH48-6PH2FL	255



Model 2PDFS48486PH2FL

## Fixed Height Mobile Pallet Stand with Lower Deck

3600 lbs. Capacity

All-welded, 12 gauge solid deck dolly with raised 30" deck height to reduce bending and back strain. Solid 12 gauge lower shelf for additional storage. Shelf clearance is 12" - 22". 6" swivel casters with phenolic wheels. Dual floor locks keep unit in place when loading and unloading. All-welded steel construction is powder coated for durability. Ships fully assembled.

Deck Size W x L	Model No.	Wt.
40 x 48	2PDFS40486PH2FL	211
42 x 48	2PDFS42486PH2FL	220
48 x 48	2PDFS48486PH2FL	238



### **Stationary Pallet Stand**

This ergonomic pallet stand is available with a fixed or adjustable height deck. The fixed height deck stands 30" high, while the height of the adjustable unit can be adjusted from 27-1/2" high to 43-1/2" high in 2" increments. Shelf clearance is 18". All-welded, heavy-duty construction with a durable powder coated finish. Ships set up and ready for use.

<b>Deck Size</b>	Fixed Height		Adjustable Height	
WxL	Model No.	Wt.	Model No.	Wt.
40 x 48	SPS-4048	81	SPS-4048-AH	90
42 x 48	SPS-4248	83	SPS-4248-AH	92
48 x 48	SPS-4848	87	SPS-4848-AH	98





#### **Steel Deck Dollies**

1000 lbs. Capacity

Ideal for transporting tote boxes, crates, machinery, etc. Formed solid 12 gauge steel deck is available with flush edges or 1-1/2" retaining lips. Won't warp or splinter. Four swivel casters with 3" x 1-1/4" hard rubber wheels. Durable powder coated finish. Ships set up and ready for immediate use.

Deck Size	Lip Up Models	Models Wt. Lip Down Models		Wt.
18 x 24	MU-1824-3R	23	MD-1824-3R	23
18 x 32	MU-1832-3R	28	MD-1832-3R	28
24 x 36	MU-2436-3R	38	MD-2436-3R	38





#### **Perforated Steel Deck Dollies**

1000 lbs. Capacity

Punched and formed 12 gauge steel dollies are ideal for transporting your small or large loads. The perforated steel deck allows debris and moisture to pass through. Four swivel casters with 3" x 1-1/4" hard rubber wheels for increased mobility. Available with 1-1/2" lip up or flush edges. Durable powder coated gray finish. Fully welded. Ships set up and ready for immediate use.

Deck Size	Lip Up Models	Wt.	Lip Down Models	Wt.
24 x 36	MUP-2436-3R	34	MDP-2436-3R	34



## **Heavy-Duty Steel Deck Dolly**

1200 lbs. Capacity

Oversized 12 gauge steel deck with four swivel casters with 5" non-marking polyurethane wheels. Use for transporting oversized containers or loads. Deck height is 6-3/8" from floor. Available with a flush deck or with a 1-1/2" retaining lip. Durable powder coated gray finish.

Deck Size	Lip Up Models	Wt.	Lip Down Models	Wt.
24 x 48	MU-2448-5PY	43	MD-2448-5PY	43
30 x 48	MU-3048-5PY	50	MD-3048-5PY	50
30 x 60	MU-3060-5PY	59	MD-3060-5PY	59









Standard Foot Kick



**Foldina** Foot Kick



## **60" Tall Hand Truck** with Patented Foot Kick

800 lbs. Capacity

Carry more and make fewer trips with this extended height hand truck. The foot kick gives you extra leverage on heavy loads when starting. Simply tilt the hand truck back while using your foot to push the base forward. Frame stands 60" tall. The large 13-1/2" deep x 1/4" thick nose plate with tapered front edge measures 16" at the back. Frame is made from 1.05" diameter 14 gauge steel tubing and is fully welded for strength and rigidity. Wheel guards protect the wheels from the load. Also available with a folding foot kick, which is designed to fold up and lock out of the way when not in use.

Standard Foot Kick	Wt.	Folding Foot Kick	Wt.	Wheel Description
TF-370-8S	48	TFF-370-8S	48	8" x 2.50" Solid Rubber
TF-370-10	52	TFF-370-10	52	10" x 2.75" Solid Rubber
TF-370-10P	50	TFF-370-10P	50	10" x 3.50" Pneumatic
TF-370-10FF	51	TFF-370-10FF	51	10" x 3.50" Flat-Free



#### **Perforated Deck Hand Truck**

The perforated 48" high deck is ideal for loading boxes when in a horizontal position. The 64" overall height supports large oversized loads. The large 13-1/2" deep x 1/4" thick nose plate measures 16" wide at the back with a tapered front edge which allows it to easily glide under the load. The 1.05" diameter 14 gauge steel tubing frame is fully welded for strength and rigidity. Wheel guards protect the load from the wheels.

Model No.	Wheel Description	Cap. Lbs.	Wt.
T-640-10	10" x 2.75" Solid Rubber	800	65
T-640-10P	10" x 3.50" Pneumatic	800	63
T-640-10FF	10" x 3.50" Flat-Free	800	63



#### Tilt Back Hand Truck

Tilt Back style design provides full support under load, making moving heavy loads a breeze. "Hands-Free" operation allows the operator to open doors without having to lower the load as with typical hand trucks.

Model No.	Wheel Description	Cap. Lbs.	Wt.
T-400-10-4R	10" x 2.75" Solid Rubber Tire	800	51
T-400-10P-4R	10" x 3.50" Pneumatic	800	49
T-400-10FF-4R	10" x 3.50" Flat-Free	800	50



#### **Super-Sized Hand Truck**

Extra large 1/4" thick steel nose plate measures 24"W x 12"D. Oversized frame is 55" tall and constructed of 1-5/16" diameter 12 gauge steel tubing. Pneumatic wheels are 12" x 3-1/2" tube type, with 4 Ply Rating and 1" roller bearings. Durable green powder coated finish.

Model No.	Wheel Description	Cap. Lbs.	Wt.
T-1000-12P	12" x 3.50" Pneumatic	800	85





## **Industrial Strength Hand Trucks**

800 lbs. Capacity


- 8" DEEP x 14" WIDE NOSE PLATE
- 4 CURVED RIBS WITH VERTICAL CENTER STRAP
- HEAVY 1.05" 14 gauge TUBULAR STEEL for added strength to frame and stair glides.
- · EXTRA-HIGH 29" STAIR GLIDES provide rigidity and longer frame life.
- · ZINC PLATED "D" AXLE IS INTERCHANGEABLE IN TRI-HOLE AXLE BRACKET

CONTINUOUS HANDLE - 47" HIGH						
Model No.	Wheel Description	Cap. Ibs.	Wt.			
T-132-8S	8" x 2.50" Solid Rubber Tire	800	33			
T-132-10	10" x 2.75" Solid Rubber Tire	800	37			
T-132-10P	10" x 3.50" Pneumatic	800	35			
T-132-10FF	10" x 3.50" Flat-Free	600	36			

DUAL HANDLE - 49" HIGH						
Model No.	Wheel Description	Cap. lbs.	Wt.			
T-320-8S	8" x 2.50" Solid Rubber Tire	800	33			
T-320-10	10" x 2.75" Solid Rubber Tire	800	37			
T-320-10P	10" x 3.50" Pneumatic	800	35			
T-320-10FF	10" x 3.50" Flat-Free	600	36			

LOOP HANDLE - 49" HIGH						
Model No.	Wheel Description	Cap. Ibs.	Wt.			
T-182-8S	8" x 2.50" Solid Rubber Tire	800	37			
T-182-10	10" x 2.75" Solid Rubber Tire	800	39			
T-182-10P	10" x 3.50" Pneumatic	800	37			
T-182-10FF	10" x 3.50" Flat-Free	600	38			

#### STEEL HAND TRUCKS WITH MUSCLE



#### INTERCHANGEABLE **D-AXLE BRACKET**


Special 3-hole axle bracket allows for placement of axle to accommodate different size wheels. D-shaped axle eliminates turning and wear of axle.



**T-132 SERIES** Continuous Handle, 47" High



ALL









WHEEL NO. 10 SIZE: 10" x 2.75"



WHEEL NO. 10P SIZE: 10" x 3.5"



WHEEL NO. 10FF Flat-Free SIZE: 10" x 3.5"

T-182 SERIES Loop Handle, 49" High









Standard Foot Kick



Folding Foot Kick







T-240-10 Loop Handle, 49" High

#### 12" Reinforced Nose Hand Truck 10 YEAR GUARANTEED NOSE PLATE

800 lbs. Capacity

The 12" deep x 14" wide reinforced nose safely handles larger, bulky loads. Frame and extra high 29" stair glides are 1.05" 14 gauge tubing for strength and rigidity. All frame styles feature 4 curved ribs with vertical center brace and zinc plated adjustable D-Axle. Available with a Continuous, Dual, or Loop handle.

#### **Available with Patented Foot Kick Option**

The foot kick gives you extra leverage on heavy loads when starting. Simply tilt the hand truck back while using your foot to push the base forward. You will be amazed how much easier it is to start out. Your choice of fixed position standard foot kick or folding foot kick which is designed to fold up and lock out of the way when not in use.

CONTINUOUS HANDLE - 47" High							
Wheel Description	Standard Foot Kick	Wt.	Folding Foot Kick	Wt.	Standard	Wt.	
8" x 2.50" Solid Rubber	TF-200-8S	36	TFF-200-8S	36	T-200-8S	34	
10" x 2.75" Solid Rubber	TF-200-10	40	TFF-200-10	40	T-200-10	38	
10" x 3.50" Pneumatic	TF-200-10P	40	TFF-200-10P	40	T-200-10P	36	
10" x 3.50" Flat-Free	TF-200-10FF	38	TFF-200-10FF	38	T-200-10FF	36	

DUAL HANDLE - 49" High								
Wheel Description	Standard Foot Kick	Wt.	Folding Foot Kick	Wt.	Standard	Wt.		
8" x 2.50" Solid Rubber	TF-220-8S	36	TFF-220-8S	36	T-220-8S	34		
10" x 2.75" Solid Rubber	TF-220-10	41	TFF-220-10	41	T-220-10	39		
10" x 3.50" Pneumatic	TF-220-10P	39	TFF-220-10P	39	T-220-10P	37		
10" x 3.50" Flat-Free	TF-220-10FF	39	TFF-220-10FF	39	T-220-10FF	37		

LOOP HANDLE - 47" High						
Wheel Description	Standard Foot Kick	Wt.	Folding Foot Kick	Wt.	Standard	Wt.
8" x 2.50" Solid Rubber	TF-240-8S	37	TFF-240-8S	37	T-240-8S	35
10" x 2.75" Solid Rubber	TF-240-10	42	TFF-240-10	42	T-240-10	40
10" x 3.50" Pneumatic	TF-240-10P	40	TFF-240-10P	40	T-240-10P	38
10" x 3.50" Flat-Free	TF-240-10FF	40	TFF-240-10FF	40	T-240-10FF	38



#### 10 YEAR GUARANTEED NOSE PLATE

12" deep nose plates are structurally reinforced for extra strength and longer life. Heavy-duty stair glides are flattened and extended under the nose plate, which virtually eliminates breakage.





#### **Shovel Nose Hand Truck**

800 lbs. Capacity

Large 1/4" tapered nose plate is 13-1/2" deep, widens to 16" at rear. Beveled leading edge is easier to slide under loads. Frame and extra high 29" stair glides are 1.05" 14 gauge tubing for strength and rigidity. Wheel guards keep loads away from wheels. All frame styles feature 4 curved ribs with vertical center brace and zinc plated adjustable D-Axle. Available with a Continuous, Dual, or Loop handle.

#### **Available with Patented Foot Kick Option**

The foot kick gives you extra leverage on heavy loads when starting. Simply tilt the hand truck back while using your foot to push the base forward. You will be amazed how much easier it is to start out. Your choice of fixed position standard foot kick or folding foot kick which is designed to fold up and lock out of the way when not in use.

CONTINUOUS HANDLE - 47" High							
Wheel Description	Standard Foot Kick	Wt.	Folding Foot Kick	Wt.	Standard	Wt.	
8" x 2.50" Solid Rubber	TF-360-8S	45	TFF-360-8S	45	T-360-8S	43	
10" x 2.75" Solid Rubber	TF-360-10	49	TFF-360-10	49	T-360-10	47	
10" x 3.50" Pneumatic	TF-360-10P	48	TFF-360-10P	48	T-360-10P	46	
10" x 3.50" Flat-Free	TF-360-10FF	48	TFF-360-10FF	48	T-360-10FF	46	

DUAL HANDLE - 49" High							
Wheel Description	Standard Foot Kick	Wt.	Folding Foot Kick	Wt.	Standard	Wt.	
8" x 2.50" Solid Rubber	TF-362-8S	45	TFF-362-8S	45	T-362-8S	43	
10" x 2.75" Solid Rubber	TF-362-10	49	TFF-362-10	49	T-362-10	47	
10" x 3.50" Pneumatic	TF-362-10P	48	TFF-362-10P	48	T-362-10P	46	
10" x 3.50" Flat-Free	TF-362-10FF	48	TFF-362-10FF	48	T-362-10FF	46	

LOOP HANDLE - 47" High							
Wheel Description	Standard Foot Kick	Wt.	Folding Foot Kick	Wt.	Standard	Wt.	
8" x 2.50" Solid Rubber	TF-364-8S	46	TFF-364-8S	46	T-364-8S	44	
10" x 2.75" Solid Rubber	TF-364-10	50	TFF-364-10	50	T-364-10	48	
10" x 3.50" Pneumatic	TF-364-10P	49	TFF-364-10P	49	T-364-10P	47	
10" x 3.50" Flat-Free	TF-364-10FF	49	TFF-364-10FF	49	T-364-10FF	47	





Standard Foot Kick



Folding Foot Kick





TF-360-10FF Continuous Handle, 47" OAH with Foot Kick



T-364-10P Loop Handle, 49" OAH

### **GAS CYLINDER HANDLING**







Dual Handle Model TW-42



Standard Foot Kick



Folding Foot Kick

#### **Gas Cylinder Hand Truck**

800 lbs. Capacity

Single cylinder cart features 1.05" O.D. tubing for strength. Nose plate is full 8" deep x 14" wide. Support chain is securely welded to frame to hold cylinder. Equipped with solid rubber or pneumatic wheels. Overall height 47". Also available with standard or folding foot kick option.

Wheel Description	Standard Foot Kick	Wt.	Folding Foot Kick	Wt.	Standard	Wt.	
Continuous Handle, 47" High							
10" x 2.75" Solid Rubber	TWF-40-10	38	TWFF-40-10	38	TW-40-10	36	
10" x 3.50" Pneumatic	TWF-40-10P	36	TWFF-40-10P	36	TW-40-10P	34	
10" x 3.50" Flat-Free	TWF-40-10FF	37	TWFF-40-10FF	37	TW-40-10FF	35	
Dual Handle, 49" High							
10" x 2.75" Solid Rubber	TWF-42-10	38	TWFF-42-10	38	TW-42-10	36	
10" x 3.50" Pneumatic	TWF-42-10P	36	TWFF-42-10P	36	TW-42-10P	34	
10" x 3.50" Flat-Free	TWF-42-10FF	37	TWFF-42-10FF	37	TW-42-10FF	35	



### 4 Wheel Gas Cylinder Hand Cart

Four-wheel cart holds 2 standard 9" diameter cylinders. Equipped with 2 swivel casters and 2 large load wheels. Includes a removable tool tray measuring 12"W x 4"L x 2"D, 2 rod holders, and safety chains to help secure cylinders. Overall dimensions 21-1/2"W x 36"L x 40"H.

Model No.	Load Wheels	Casters	Wt.
TW-30	10" x 2.75" Solid Cushion Rubber	4" x 1-1/4" Rubber	57



## Tilt-back Gas Cylinder Hand Truck

Tilt-back truck stabilizes the load on 4 wheels for less effort when transporting cylinders. Safety chains secure cylinder to truck. 800 lbs. capacity.

Model No.	Wheel Size	Casters	Wt.
TW-70-8SR-3R	8" x 2.5"	3" x 1-1/4"	48
	Solid Cushion Rubber	Rubber	



### **Dual Gas Cylinder Hand Truck**

Popular double cylinder truck features a 14" x 24" base plate braced underneath with angle iron. Lip on back assists prevention of cylinder movement. Continuous handle is strong and safe. Furnished with large tool tray. Overall height 48".

Model No.	Wheel Size	Load Cap. Lbs.	Wt.
TW-50-10	10" x 2.75" Solid Rubber	800	63
TW-50-12P	12" x 3" Pneumatic	800	66
TW-50-16P	16" x 4" Pneumatic	800	69

#### **GAS CYLINDER STORAGE**



## **Gas Cylinder Storage Units**

All-welded units ship set up. 13 gauge expanded metal for ventilation and visibility. Sloped roof is sheet steel. Angle frame with back panels reinforced for protection against slamming cylinders. Includes padlock hasp. Legs have 1/2" hole for bolting to floor. Helps meet OSHA 1910 requirements and NFPA standards. Yellow powder coated finish.

Model No.	Cylinder Capacity	Overall W x D x H	Wt.				
HOF	HORIZONTAL CYLINDER STORAGE CABINETS						
For 2	For 20-43 lbs. LPG Cylinders Up To 13" Diameter						
GSH-36W-40H	4	36 x 38 x 40	211				
GSH-36W-70H	8	36 x 38 x 70	248				
GSH-72W-70H	16	72 x 38 x 70	410				
U	PRIGHT CYLINDER STOP	RAGE CABINETS					
	For 20-43 lbs. Cylinders	Up To 33" Tall					
GSU-24D-40H	2-3	36 x 26 x 40	133				
GSU-36W-40H	4-6	36 x 38 x 40	165				
	For Upright Cylinders U	Jp To 68" Tall					
GSU-36W-70H	5-15	36 x 38 x 70	188				
GSU-72W-70H	10-30	72 x 38 x 70	316				
COMBINATION UPRIGHT & HORIZONTAL STORAGE							
GSC-72W-70H	8 Horizontal &	72 x 38 x 70	455				
	5-15 Upright						



Model GSH-36W-70H



GSU-36W-40H



Model GSC-72W-70H

### **Gas Cylinder Storage Units**

Two compartments clearly labeled to separate your "Full" and "Empty" gas cylinders. Eliminates costly downtime caused by running out of "full" cylinders or installing an empty cylinder. Each compartment holds 5-15 upright cylinders. All-welded construction with powder coated finish ships set up. Measures 72" W x 38" D x 70" H.

Model No.	Cylinder Capacity	Overall W x D x H	Wt.
GSU2-72W-70H	5-15 Upright in Each	72 x 38 x 70	316
	Compartment 10-30 Total		



GSU2-72W-70H

## **Industrial Gas Cylinder Cage**

Designed to securely store industrial lift-truck propane tanks. All-welded cage has a 12 gauge top. Stores up to 12 cylinders horizontally with lockable door. Accommodates 20, 33, and 44 lb propane tanks. Lag holes in footpads for mounting to floor. Powder coated safety-yellow finish. High-visibility "Danger/Flammable" sign. Helps meet OSHA 1910 requirements.

Cylinder Capacity	DxWxH	Model No.	Wt.
8	36 x 36 x 70	GSC-3636-70	201
12	36 x 48 x 70	GSC-3648-70	251



Model GSC-3636-70

#### GAS CYLINDER STORAGE





Model GST-8-8PH

### **Gas Cylinder Truck**

Capacities (6) or (8) 9-1/4" Cylinders

Move bulky gas cylinders by hand with this heavy-duty steel truck. Thick 7 gauge deck is reinforced with 1-1/2" square tubing and substantial 7 gauge gussets. Square tube uprights support 1/4" thick corral dividers. Heavyduty chain secures the cylinders during transport. Low deck for easy loading and unloading. 2 swivel and 2 rigid casters with 8" phenolic wheels. Loop handle at swivel end. Overall height (empty) is 45".

Cylinder Capacity	Overall W x D	Model No.	Wt.
6	24 x 50	GST-6-8PH	157
8	24 x 60	GST-8-8PH	203



Model GSP-4

### Gas Cylinder Pallet

Capacities (4), (6) or (8) 9-1/4" Cylinders

Load bulky gas cylinders for transport by forklift with this heavy-duty steel platform. Thick 7 gauge formed deck is flanked by solid fork pockets that run the length of the unit. Angle iron uprights with angle gussets for strength. Dividers with loop handles secure the cylinders during transport. Overall height (empty) is 41".

Cylinder Capacity	Overall W x D	Model No.	Wt.
4	33 x 25	GSP-4	93
6	33 x 36	GSP-6	128
8	33 x 47	GSP-8	156



Model GS-1

## Single Gas Cylinder Storage Unit

Securely store your gas cylinder with this all-welded singular gas storage unit. Fits most standard gas cylinders. Safety chain secures cylinder to unit. Tubular base to prevent rocking on uneven floor. Unit comes with lag holes for anchoring to the floor. Helps you comply with OSHA requirements. Durable powder coated gray finish. All-welded, ships set up and ready for immediate use.

Overall		
WxDxH	Model No.	Wt.
18 x 18 x 37-1/2	GS-1	27





#### Welder's Table

This all-welded, heavy-duty Welder's Table is ideal for institutions, maintenence shops or hobbyists with small repairs or projects. The dual-sided bar grating is designed for long-term use and is easily removable for quick clean up of slag & debris from the 4-1/4" deep catch pan below. Ships set up and ready for immediate use. Durable powder coated gray finish. Also available with factory-installed HD drawer measuring 26"W x 20"D x 6"H and includes a padlock hasp.

SIZE D x W x H	With Drawer Model No.	Wt.	Without Drawer Model No.	Wt.
24 x 51 x 34	WG-2451-HD	178	WG-2451	126



## **Heavy-Duty MIG Welding Cart**

Securely store and transport your welding equipment and gas with this heavy-duty welding cart. 12 gauge steel shelves measure 18" wide. Top shelf is 26" long, and bottom shelf is 36" long, allowing ample room for a 9" diameter gas cylinder which is secured by a chain. Bottom shelf has a 1-1/2" retaining lip. The 10" x 2-3/4" puncture-proof solid rubber load wheels and 4" rubber swivel casters make this cart ideal for transport over rough and uneven surfaces. Top shelf height is 21-1/2", handle height is 35". Durable powder coated gray finish. Ships set up and ready for immediate use.

Model No.	Load Wheel	Swivel Caster	Capacity	Wt.
WCK-1836-10SR-4R	10" x 2-3/4"	4" x 1-1/4"	750 lbs	86



**WELDED STEEL** 





MS2-1532-6PH











MS1-1532-6PH

MS3-1532-6PH

MS4-1532-6PH

## **Mobile Storage Bins**

Heavy-duty, all-welded 14 gauge steel construction with powder coated finish for rugged durability. Built with an open hopper front, each level has overall dimensions of 12-1/2"H x 15"D x 32"W. Available with up to 4 permanent storage compartments per level. Heavy 6" x 2" swivel casters with hard tread phenolic wheels for ease of movement. Mobile units allow you to bring the parts to the workspace or reposition with changing requirements.

Overall Dimensions: 32" wide x 45-1/2" high x 20" deep. 800 lbs. capacity per tier. 2400 lbs. overall capacity.

	Openings	Total	OF	PENING SIZ	ZE	
Model No.	per Level	Openings	W	Н	D	Wt.
MS1-1532-6PH	1	3	32"	12-1/2"	15"	173
MS2-1532-6PH	2	6	16"	12-1/2"	15"	180
MS3-1532-6PH	3	9	10-1/2"	12-1/2"	15"	198
MS4-1532-6PH	4	12	8"	12-1/2"	15"	215



MS3-1532-FP







MS1-1532-FP

MS2-1532-FP

MS4-1532-FP

### **Stationary Storage Bins**

Same heavy-duty construction as our popular Mobile Storage Bins, now in a stationary version. All-welded, 14 gauge steel bins with durable gray powder coated finish. The stationary versions have fork pockets to allow easy transport and positioning without having to empty the bins. Fork pockets with 8" x 4" opening are designed for use with either a fork truck or a standard pallet jack.

Available with 1, 2, 3, or 4 compartments per level. Overall dimensions 32" wide x 42" high x 20" deep. Shelf capacity - 800 lbs. Total Capacity - 2400 lbs.

	Openings	Total	OF	PENING SIZ	ZE	
Model No.	per Level	Openings	W	Н	D	Wt.
MS1-1532-FP	1	3	32"	12-1/2"	15"	169
MS2-1532-FP	2	6	16"	12-1/2"	15"	176
MS3-1532-FP	3	9	10-1/2"	12-1/2"	15"	194
MS4-1532-FP	4	12	8"	12-1/2"	15"	211



### **Bin Cart with Pegboard Tool Storage**

Easily organize, store, and transport your small parts with one efficient cart. This dual-sided bin transport cart features a 16 gauge pegboard on the handle end and center mounted double-sided louvered panel to securely hang your polypropylene bins in any combination with easy-access from either side. Heavy-duty, 12 gauge steel shelves have 1-1/2" retaining lips for small parts. 34" overall height. 2 rigid and 2 swivel, 5" non-marking polyurethane wheels with total lock brakes. All-welded. Ships set up and ready for use. Bins not included.

Size	Model No.	Wt.
24 x 36	BC-2436-TL-PB	79

#### **SMALL PARTS STORAGE**



#### **WELDED STEEL**

### **Mobile Storage Bins**

Heavy-duty, all-welded 14 gauge steel construction with powder coated finish for rugged durability. Built with an open hopper front, each level has overall dimensions of 12-1/2"H x 15"D x 32"W. Available with up to 8 permanent storage compartments per level. Heavy 6" x 2" swivel casters with hard tread phenolic wheels for ease of movement. Mobile units allow you to bring the parts to the workspace or reposition with changing requirements.

Overall Dimensions: 64" wide x 45-1/2" high x 20" deep. 800 lbs. capacity per tier. 2400 lbs. overall capacity.

	Openings	Total	OF	PENING SIZ	ZE	
Model No.	per Level	Openings	W	Н	D	Wt.
MS2-1564-6PH	2	6	32"	12-1/2"	15"	332
MS4-1564-6PH	4	12	16"	12-1/2"	15"	346
MS6-1564-6PH	6	18	10-1/2"	12-1/2"	15"	382
MS8-1564-6PH	8	24	8"	12-1/2"	15"	416



MS4-1564-6PH









MS6-1564-6PH



MS8-1564-6PH

## **Sloped Shelf Bin Cart**

Store, organize, and transport your bins (not included) with this dualsided bin transport cart. Heavy-duty, all-welded construction. The 14 gauge, solid steel shelves with 1-1/2" retaining lips are sloped at a 15° angle. The shelves are 35-1/2" wide and will accommodate bins up to 11-7/8" deep and 8" high. Shelf clearance is 8-1/4". 6 shelves on each side for a combined total of 12 shelves. 2 swivel, 2 rigid 6" non-marking polyurethane casters.

Size	Model No.	Wt.
30 x 36	6BC-3036-6PY	328



6BC-3036-6PY Bins not included









# Model IF-2436-5PYTL Double Sided Frame Shown with: (1) IF-PB-36 (front) (2) IF-SHELF-LU-36 (back) (1) IF-SHELF-36 (front) (1) IF-LP-36 (back)

(2) IF-BR-36 (front)





### **Heavy-Duty Mobile Work Center**

1200 lbs. Capacity

From mobile workstand to tool and small parts storage and everything in between, this fully customizable multi-purpose stand can be adjusted to fit your shop's ever growing needs. The 60" high uprights feature adjustable slots on 2" centers. All accessories and shelves are purchased separately.

Available in a single-sided or double-sided unit.

#### **Double Sided Unit**

This double-sided unit features a full bottom shelf measuring 24" x 36".

#### **Single Sided Unit**

This single sided unit features an open base design allowing you to either step in to the unit for easy access to all your parts or tools, or pull up a stool to use as a workstation.

Frame Only	Overall D x W x H	Model No.	Wt.
Double Sided Frame	24 x 36 x 66-1/2	IF-2436-5PYTL	85
Single Sided Frame	24 x 39 x 66-1/2	IF1S-2436-5PYTL	50

#### **Available Accessories - All Purchased Separately**

**Shelf - Flush Edge:** Lip down on all 4 sides 11" x 33-3/4".

**Shelf - 1-1/2" Lips:** Retaining lips on all 4 sides 11" x 33-3/4".

**Pegboard Panel:** 24" high 16 gauge formed steel panel with holes on 1" centers.

on i centers.

**Louvered Panel:** 24" high 16 gauge formed steel panel. **Bin Rail:** 16 gauge louvered panel. Single row 6" high.

Description	Model No.	Size	Wt.
Flush Shelf	IF-SHELF-36	11"D x 34"W	24
Lipped Shelf	IF-SHELF-LU-36	11"D x 34"W	24
Pegboard Panel	IF-PB-36	24"D x 34"W	20
Louvered Panel	IF-LP-36	24"D x 34"W	20
Bin Rail	IF-BR-36	6"D x 34"W	7

Model
IF1S-2436-5PYTL
Single Sided Frame
Shown with:
(1) IF-PB-36
(1) IF-LP-36
(1) IF-SHELF-36







## **Double Sided Pegboard** or Louvered Panel Cart

This all-welded, heavy gauge cart features double sided pegboard or louvered panels making it an ideal solution for your tool and small parts storage needs. The cart rolls smoothly on 2 swivel and 2 rigid 6" x 2" non-marking polyurethane wheels. The floor lock can be activated to securely lock the cart in place once at your destination. A tubular steel handle allows a comfortable grip for the operator.

Deck Size	Pegboard Panels	Wt.	Louvered Panels	Wt.
30 x 36	IPB-6PYFL	175	ILP-6PYFL	175







Model ILP-6PYFL

## **Stationary Pegboard or Louvered Panel Storage**

This all-welded, heavy gauge stand features your choice or either 16 gauge pegboard or louvered panels. Your choice of 36" or 48" wide panels allows ample storage for all your tool and small parts. 24" long foot pads with a 5/8" lag hole provides a solid base that can be anchored to the floor. 66-1/2" overall height.

Width	Pegboard Panels	Wt.	Louvered Panels	Wt.
36	S1S-PB-36	61	S1S-LP-36	62
48	S1S-PB-48	73	S1S-LP-48	74



#### **5S Lean Cart**

Efficiently organize, store and transport with this all in one 5S Lean Cart. This all-welded cart features 24" wide x 55" tall pegboard panel on each end of the double sided louvered panels for all your tool and small parts storage needs. The center mounted louvered panels measure 36" wide by 48" tall. 2 swivel and 2 rigid 6" x 2" non-marking polyurethane wheels provide easy maneuverability. Floor lock can be activated to securely position the cart.


Size	Model No.	Wt.
24 x 38	BCPB-2438-6PYFL	212





Model BCPB-2438-6PYFL







Model AFPBLP-2436-5PY

### Mobile A-Frame – Lean Tool Cart

1200 lbs. Capacity

Use in your Lean Manufacturing facility to transport and efficiently organize tools and parts. Visually locate items in seconds. Use tool shadowing on the pegboards to know immediately if a tool, accessory, or part is missing. The 16 gauge pegboard has holes on 1" centers that accept most standard hooks. Louvered panels accommodate all sizes of hanging bins. Pegboard or louvered panels are 48" high. Overall truck height is 56". This all-welded, heavy-duty unit features a durable powder coated gray finish. Ships fully assembled. 2 rigid and 2 swivel 5" polyurethane casters make it easy to safely transport to the work area. (Pegs and bins not included.)



			Louvered		1 Pegboard Side & 1 Louvered Side	k	Combo Pegboard/Louvered Panel on Both Sides	
Size	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.
24 x 36	AFPB-2436-5PY	120	AFLP-2436-5PY	120	AFPBLP-2436-5PY	120	AFCP-2436-5PY	120
24 x 48	AFPB-2448-5PY	143	AFLP-2448-5PY	143	AFPBLP-2448-5PY	143	AFCP-2448-5PY	143
24 x 60	AFPB-2460-5PY	170	AFLP-2460-5PY	170	AFPBLP-2460-5PY	170	AFCP-2460-5PY	170



### **Mobile Pegboard A-Frame – 60" Tall**

1200 lbs. Capacity

Efficiently organize, store, and transport your tools with this Little Giant lean tool cart. 60" tall x 48" wide 16 gauge pegboard panels provide ample storage for all of your tools and feature holes on 1" centers that accept most standard hooks. 5" non-marking polyure-thane wheels with 2 rigid and 2 swivel casters with total lock brakes to keep the unit stationary. 68" overall height. Available as a single or double-sided unit. (Pegs and bins not included.)

A-Frame	Model No.	Wt.
Single-sided	AFPB1S2448-TL60	107
Double-sided	AFPB2S2448-TL60	163



## Mobile Pegboard with Back Shelf Storage

2000 lbs. Capacity

Combine the great features of our 48" high A-Frame Pegboard with 4 storage shelves on the back side to store larger parts or tools. Pegboard is 16 gauge steel with 1/4" diameter holes. 2 rigid and 2 swivel casters with 6" polyurethane wheels mean smooth transport through your facility. A floor lock is mounted on the swivel caster end to securely position the unit. 60" overall height.

Size	Model No.	Wt.
24 x 36	AFPBS2436-6PYFL	186
24 x 48	AFPBS2448-6PYFL	224
24 x 60	AFPBS2460-6PYFL	262



#### **Mobile Workstation**

1200 lbs. Capacity

Top shelf is 34" high with a 1-1/2" retaining lip on 3 sides. Bottom and middle shelves are lip up on all 4 sides. 12 gauge shelves. Powder coated finish. 5" polyurethane casters, 2 rigid and 2 total lock swivel casters.

	2-SHELF 24-1/2" Clearance		3-SHELF 11-1/2' Clearance		
Size	Model No.	Wt.	Model No.	Wt.	
24 x 36	MW-2436-5TL	84	3MW-2436-5TL	115	
24 x 48	MW-2448-5TL	103	3MW-2448-5TL	150	

**PEGBOARD OR LOUVERED PANEL -** Available with a bolton 16 gauge pegboard or louvered panel. Panels are 24"H. Gray powder coated finish. (Pegs and bins not included.)

	2-SHELF 24-1/2" Clearance	)	3-SHELF 11-1/2' Clearance		
Size	Model No.	Wt.	Model No.	Wt.	
24 x 36	MW-2436-5TL-PB	102	3MW-2436-5TL-PB	122	
24 x 48	MW-2448-5TL-PB	127	3MW-2448-5TL-PB	162	

For Louvered Panel, replace PB with LP



## Mobile Workstation with Storage Drawer

Available with 1 or 2 locking drawers (keyed alike). Drawers measure  $13^{\circ}W \times 17^{\circ}D \times 4-1/2^{\circ}H$ . Shelf clearance is  $18^{\circ}$  below drawer. Non-marking  $5^{\circ}$  polyurethane casters, 2 rigid and 2 total lock swivels that lock both wheel and swivel at the same time. Gray powder coated finish.

Shelf Size	1-DRAWER Model No.	Wt.	2-DRAWER Model No.	Wt.
24 x 36	MW-2436-5TL-DR	97	MW-2436-5TL-2DR	114
24 x 48	MW-2448-5TL-DR	116	MW-2448-5TL-2DR	129
with Peg	board Panel			
24 x 36	MW2436-5TL-DRPB	115	MW2436-5TL2DRPB	128
24 x 48	MW2448-5TL-DRPB	140	MW2448-5TL2DRPB	153

For Louvered Panel, replace  $\ensuremath{\textbf{PB}}$  with  $\ensuremath{\textbf{LP}}$ 



## Maintenance Workstation with Pegboard or Louvered Storage

1200 lbs. Capacity

This maintenance workstation features 16 gauge pegboard or louvered panel on the handle end, convenient for storing small parts or tools. The top shelf is 34" high with a 1-1/2" retaining lip on 3 sides. 2 rigid and 2 swivel 5" non-marking polyurethane casters make it easy to transport this directly to the job. Total lock swivel casters lock both the wheel and the swivel to keep the unit stationary while in use. Durable powder coated finish.

	Shelf Size	Model No.	Wt.
Louvered Panel	24 x 36	MWLP-2436-5TL	102
Pegboard Panel	24 x 36	MWPB-2436-5TL	102











## STATIONARY Steel Workstation

2000 lbs. Capacity

Top shelf has a flush front edge and 1-1/2" retaining lips on sides and back. Available in a 2 or 3 shelf model. Available factory installed options include pegboard panel, louvered panel, or storage drawer. Heavy-duty leg levelers allow you to adjust the top shelf height from 39" - 42".

	2-SHELF 33" Clearance		3-SHELF 15-1/2" Clearance		
Size	Model No.	Wt.	Model No.	Wt.	
24 x 36	SW-2436-LL	78	3SW-2436-LL	109	
24 x 48	SW-2448-LL	97	3SW-2448-LL	144	

**PEGBOARD OR LOUVERED PANEL -** Available with 24"H 16 gauge pegboard or louvered panel. (Pegs and bins not included.)

		2-SHELF 33" Clearance		3-SHELF 15-1/2" Clearance	€
	Size	Model No.	Wt.	Model No.	Wt.
Pegboard	24 x 36	SW-2436-LL-PB	106	3SW-2436-LL-PB	127
Panel	24 x 48	SW-2448-LL-PB	115	3SW-2448-LL-PB	167
Louvered	24 x 36	SW-2436-LL-LP	106	3SW-2436-LL-LP	127
Panel	24 x 48	SW-2448-LL-LP	115	3SW-2448-LL-LP	167

**LOCKING STORAGE DRAWER -** Available with 1 or 2 - 13 W x 17"D x 4-1/2"H locking drawers.

		1-DRAWER		2-DRAWER	
	Size	Model No.	Wt.	Model No.	Wt.
Drawers	24 x 36	SW-2436-LL-DR	91	SW-2436-LL-2DR	108
Only	24 x 48	SW-2448-LL-DR	110	SW-2448-LL-2DR	123
Pegboard	24 x 36	SW-2436-LLPBDR	109	SW-2436-LLPB2DR	126
Panel	24 x 48	SW-2448-LLPBDR	128	SW-2448-LLPB2DR	141
Louvered	24 x 36	SW-2436-LLLPDR	109	SW-2436-LLLP2DR	126
Panel	24 x 48	SW-2448-LLLPDR	128	SW-2448-LLLP2DR	141



## Work-Height Mobile Workstation with writing shelf, drawers, and pegboard

12 gauge top shelf is 42" high, making this a perfect standing work-station. 16 gauge steel pegboard extends 24" above workbench. Pegboard holes are on 1" centers and accept most standard hooks. Louvered panel available in place of pegboard. Two locking storage drawers. Writing shelf measures 21" wide x 12" deep and has a sloped storage pocket underneath. Two swivel and two rigid total lock casters with 5" polyurethane wheels. Total lock casters keep the unit locked in place when in use. (Bins and hooks not included.)

Size D x W	Model No.	Wt.
24 x 36	QC2436-TL2DRPB	163
24 x 48	QC2448-TL2DRPB	187
24 x 60	QC2460-TL2DRPB	212

For Louvered Panel, replace PB with LP



#### **Shop Desk**

All-welded construction with comfortable height as a standing desk/workstation. Riser shelf is 10" deep and 10" above desk surface. Locking storage drawer is 13"W x 17"D x 4-1/2"H and comes with two keys. Lower shelves have 1-1/2" retaining lips and 11-3/4" shelf clearance. Durable powder coated finish.

#### **Stationary Models**

Leg levelers allow height adjustment of desk surface from 39"- 42" high. 2000 lbs. capacity.

#### **Mobile Models**

3" swivel brake casters with rubber wheels, 42" high desk surface. 1000 lbs. capacity.

Overall D x W	Stationary Model No.	Wt.	Mobile Model No.	Wt.
22 x 24	PSR-2224-LLDR	99	PSR-2224-3RBKDR	104
24 x 36	PSR-2436-LLDR	134	PSR-2436-3RBKDR	139





## **Enclosed Shop Desk**

Enclosed cabinet with 13 gauge expanded metal provides visibility of the contents. All-welded construction ensures items stay secure. All models include locking storage drawer. Riser shelf is 10" deep and 10" above writing surface.

#### **Stationary Models**

Leg levelers allow height adjustment of desk surface from 39"- 42" high. 2000 lbs. capacity.

#### **Mobile Models**

3" swivel brake casters with rubber wheels, 42" high desk surface. 1000 lbs. capacity.

Overall D x W	Stationary Model No.	Wt.	Mobile Model No.	Wt.
22 x 24	PSX-2224-LLDR	136	PSX-2224-3RBKDR	141
24 x 36	PSX-2436-LLDR	171	PSX-2436-3RBKDR	176



5727

Model PSX-2224-LLDR



Model MNC-1D-1824-TL



### **Compact Mobile Bench Cabinet**

This compact mobile storage cabinet is ideal for providing secure storage where space is an issue. The cabinet features 12 gauge steel top work surface with 1-1/2" retaining lips on the sides and back, and a locking door to secure all your belongings. Rolls smoothly on 5" non-marking polyurethane wheels. 2 rigid and 2 swivel casters with total lock brakes keep the unit locked in place. Welded unit has a powder coated finish and ships fully assembled.

	Overall D x W x H	Model No.	Wt.
Locking Door	24-1/8 x 18-1/8 x 36-1/4	MNC-1D-1824-TL	111
Storage Drawer	24-1/8 x 18-1/8 x 36-1/4	MNC-1824-DR-TL	107

**Receiving Station** 

to almost any uneven floor surface.

2000 lbs. Capacity

Overall D x W

24 x 36

24 x 36



Model MNC-1824-DR-TL



Available with Total Lock Casters



Model RS3-2436-LL



RS3-2436-LL

## **Receiving Station - with Locking Doors**

Without Center Shelf

With Center Shelf

All-welded, 12 gauge construction. Top surface, measuring 24" deep x 36" wide, is enclosed on three sides with flush front edge to provide an open writing surface. The height can be set from 39-1/2" - 42-1/2" above the floor. The 3 shelf version has 13" of clearance between the three

shelves and the 2 shelf station has 27" of clearance. Riser

Model No.

RS-2436-LL

RS3-2436-LL

Wt.

159

192

measures 10" deep and is 12" above the writing surface, allowing storage of most 3 ring binders. Floor glides adjust

2 locking doors feature a 3-point latching system and keyed locking handle to keep your items secure.

Overall D x W		Model No.	Wt.
24 x 36	Without Center Shelf	RS-2D-2436-LL	182
24 x 36	With Center Shelf	RS3-2D-2436-LL	215

Model RS-2D-2436-LL



### **Counter Height Bench Cabinets**

All-welded, 12 gauge construction. The top work surface measures 24" x 48", is 41" high and is surrounded by retaining lip on three sides. Available in 3 standard work top surfaces. Keyed handle and 3-point latching mechanism. Fixed center shelf. Clearview doors provide ventilation and visibility. Heavy-duty leg levelers adjust for up to 3" of additional height. Durable powder coated gray finish. Also available with a factory installed louvered or pegboard panel.

## Bench Cabinet with Welded 12 gauge Center Shelf

Interior shelf clearance 13" High.

	Solid Doors		Clearview Door	s
Top Surface	Model No.	Wt.	Model No.	Wt.
Powder Coated Steel	MB3-LL-2D-2448	305	MBP3-LL-2D-2448	294
1-3/4" Butcher Block	MJ3-LL-2D-2448	355	MJP3-LL-2D-2448	344
1/4" Hardboard	MH3-LL-2D-2448	313	MHP3-LL-2D-2448	302

For Pegboard Panel, add: -PB For Louvered Panel, add: -LP

## Bench Cabinet with Heavy-Duty Storage Drawer

Extra large, padlockable storage drawer measures 26"W x 20"D x 6"H, 250 lb. capacity. (No center shelf). Inside height clearance 18-3/4".

	Solid Doors		Clearview Doors	s
Top Surface	Model No.	Wt.	Model No.	Wt.
Powder Coated Steel	MB-LL-2D-2448HD	305	MBP-LL-2D-2448HD	294
1-3/4" Butcher Block	MJ-LL-2D-2448HD	355	MJP-LL-2D-2448HD	344
1/4" Hardboard	MH-LL-2D-2448HD	313	MHP-LL-2D-2448HD	302

For Pegboard Panel, add: **-PB** For Louvered Panel, add: **-LP** 







**Clearview Doors** 



MB-LL-2D-2448HD

## Stationary Shop Cabinets

Top, center, and bottom shelves are 12 gauge steel, with 14 gauge sides and back. Top shelf has a 2" retaining lip around 3 sides. Locking handle with 2 keys. Leg levelers allow 3" of overall height adjustment. Height to top shelf is adjustable from 31"-34". 12-1/2" shelf clearance. Ships fully assembled.

Size D x W	Model No.	Doors	Wt.
18 x 18	MC3-1D-1818-LL	1	98
24 x 24	MC3-2D-2424-LL	2	141
24 x 36	MC3-2D-2436-LL	2	187



## **MOBILE BENCH CABINETS**











#### **VISIBLE CONTENT** 48" Wide Mobile Bench Cabinets

3600 lbs. Capacity

All-welded, 12 gauge construction. Clearview doors secure contents with keyed handle and 3 point latching mechanism. The top work surface measures 24" x 48", is 41" high and is surrounded by retaining lip on three sides. Available in 4 standard work top surfaces. 2 swivel, 2 rigid non-marking polyurethane wheels. Available with optional pegboard or louvered panel. Floor lock on the handle end securely positions the workbench. Durable powder coated gray finish.

#### WITH FULL CENTER SHELF

Interior shelf clearance 13" high.

	Without Louvered Panel		With Louvered Pa	nel
Top Surface	Model No.	Wt.	Model No.	Wt.
Powder Coated Steel	MBP3-2D-2448-FL	316	MBP3-2D-FL-LP	341
1-3/4" Butcher Block	MJP3-2D-2448-FL	366	MJP3-2D-FL-LP	391
1/4" Hardboard	MHP3-2D-2448-FL	323	MHP3-2D-FL-LP	348
Non-Slip Vinyl	MMP3-2D-2448-FL	320	MMP3-2D-FL-LP	345

For Pegboard Panel, replace -LP with -PB

#### WITHOUT CENTER SHELF

Cabinet interior height clearance 28".

	Without Louvered Panel		With Louvered Pa	nel
Top Surface	Model No.	Wt.	Model No.	Wt.
Powder Coated Steel	MBP2D-2448-FL	275	MBP2D-FL-LP	300
1-3/4" Butcher Block	MJP2D-2448-FL	325	MJP2D-FL-LP	350
1/4" Hardboard	MHP2D-2448-FL	283	MHP2D-FL-LP	308
Non-Slip Vinyl	MMP2D-2448-FL	279	MMP2D-FL-LP	304

For Pegboard Panel, replace -LP with -PB

#### WITH HEAVY-DUTY DRAWER

Large 250 lb. capacity storage drawer measures 26"W x 20"D x 6"H and features a full-width recessed handle and a padlock hasp. Cabinet interior clearance 20" high.

	Without Louvered Panel		With Louvered Pa	nel
Top Surface	Model No.	Wt.	Model No.	Wt.
Powder Coated Steel	MBP2D-2448-HDFL	314	MBP2D-HDFL-LP	339
1-3/4" Butcher Block	MJP2D-2448-HDFL	369	MJP2D-HDFL-LP	394
1/4" Hardboard	MHP2D-2448-HDFL	322	MHP2D-HDFL-LP	347
Non-Slip Vinyl	MMP2D-2448-HDFL	318	MMP2D-HDFL-LP	343

For Pegboard Panel, replace -LP with -PB

#### WITH DOUBLE STORAGE DRAWERS

2 storage drawers measuring 12" W x 17"D x 4-1/2"H with cylinder locks and keys. Cabinet interior clearance 21-1/2" high.

	Without Louvered Panel		With Louvered Pa	nel
Top Surface	Model No.	Wt.	Model No.	Wt.
Powder Coated Steel	MBP2D-2448-2DRFL	305	MBP2D-2DRFL-LP	330
1-3/4" Butcher Block	MJP2D-2448-2DRFL	355	MJP2D-2DRFL-LP	380
1/4" Hardboard	MHP2D-2448-2DRFL	313	MHP2D-2DRFL-LP	338
Non-Slip Vinyl	MMP2D-2448-2DRFL	309	MMP2D-2DRFL-LP	334

For Pegboard Panel, replace -LP with -PB



#### 48" Wide Mobile Bench Cabinets

3600 lbs. Capacity

All-welded, 12 gauge construction. The top work surface measures 24" x 48", is 41" high and is surrounded by a retaining lip on three sides. Available in 4 standard work top surfaces. Non-marking 6" polyurethane casters, 2 rigid and 2 swivel, provide smooth rolling performance. Floor lock on the handle end securely positions the workbench.

	Without Center	Shelf	With Center Shel		
Top Surface	Model No.	Wt.	Model No.	Wt.	
Powder Coated Steel	MB-2448-FL	241	MB3-2448-FL	282	
1-3/4" Butcher Block	MJ-2448-FL	291	MJ3-2448-FL	332	
1/4" Hardboard	MH-2448-FL	248	MH3-2448-FL	289	
Non-Slip Vinyl	MM-2448-FL	245	MM3-2448-FL	286	

For Pegboard Panel, add: -PB For Louvered Panel, add: -LP

#### WITH LOCKING DOORS

3600 lbs. Capacity

Secure 3-point latching system with keyed handle locks the doors at top, center, and bottom. Available with and without center shelf.

	Without Center	Shelf	With Center Shelf		
Top Surface	Model No.	Wt.	Model No.	Wt.	
Powder Coated Steel	MB-2D-2448-FL	292	MB3-2D-2448-FL	333	
1-3/4" Butcher Block	MJ-2D-2448-FL	342	MJ3-2D-2448-FL	383	
1/4" Hardboard	MH-2D-2448-FL	299	MH3-2D-2448-FL	340	
Non-Slip Vinyl	MM-2D-2448-FL	296	MM3-2D-2448-FL	337	

For Pegboard Panel, add: **-PB** For Louvered Panel, add: **-LP** 

#### WITH HEAVY-DUTY DRAWER

3600 lbs. Capacity

Large heavy-duty drawer measures 26"W x 20"D x 6"H and features a full-width recessed handle and padlock hasp. Available with and without locking doors.

	Without Locking	Doors	With Locking Doors		
Top Surface	Model No.	Wt.	Model No.	Wt.	
Powder Coated Steel	MB-2448-HDFL	280	MB-2D-2448-HDFL	331	
1-3/4" Butcher Block	MJ-2448-HDFL	330	MJ-2D-2448-HDFL	381	
1/4" Hardboard	MH-2448-HDFL	287	MH-2D-2448-HDFL	338	
Non-Slip Vinyl	MM-2448-HDFL	284	MM-2D-2448-HDFL	335	

For Pegboard Panel, add: **-PB** For Louvered Panel, add: **-LP** 

#### WITH DOUBLE STORAGE DRAWERS

3600 lbs. Capacity

2 Locking storage drawers measuring 13"W x 17"D x 4-1/2"H. Available with and without locking doors.

	Without Locking Doors		With Locking Do	ors
Top Surface	Model No.	Wt.	Model No.	Wt.
Powder Coated Steel	MB-2448-2DRFL	271	MB2D-2448-2DRFL	322
1-3/4" Butcher Block	MJ-2448-2DRFL	321	MJ2D-2448-2DRFL	372
1/4" Hardboard	MH-2448-2DRFL	278	MH2D-2448-2DRFL	329
Non-Slip Vinyl	MM-2448-2DRFL	275	MM2D-2448-2DRFL	326

For Pegboard Panel, add: **-PB** For Louvered Panel, add: **-LP** 















MB-2448-PBD-FL



## MB-2448-LPD-FL



MB-PBD-FL-PB



Model MB-LPD-FL-LP

## 48" Wide Mobile Bench Cabinets with Pegboard or **Louvered Panel Doors**

16 gauge pegboard securely welded to the inside of the doors provides an ideal and secure solution to storing and organizing your tools. The doors feature a 3-point latching system with keyed handle that locks the doors at the top, center, and bottom. All-welded, 12 gauge construction. Available with your choice of 4 standard work surfaces. Also available with a factory installed top mounted louvered or pegboard panel.

Pegboard Doors				
Top Surface	Model No.	Wt.		
Powder Coated Steel	MB-2448-PBD-FL	314		
1-3/4" Butcher Block	MJ-2448-PBD-FL	364		
1/4" Hardboard	MH-2448-PBD-FL	321		
Non-Slip Vinyl	MM-2448-PBD-FL	318		

Louvered Panel Doors				
Top Surface	Model No.	Wt.		
Powder Coated Steel	MB-2448-LPD-FL	315		
1-3/4" Butcher Block	MJ-2448-LPD-FL	365		
1/4" Hardboard	MH-2448-LPD-FL	321		
Non-Slip Vinyl	MM-2448-LPD-FL	318		

#### WITH PEGBOARD OR LOUVERED TOP PANEL

Available with a bolt-on 16 gauge pegboard or louvered panel. Panels are 24"H. Gray powder coated finish.

Pegboard Doors with Top Pegboard Panel				
Top Surface	Model No.	Wt.		
Powder Coated Steel	MB-PBD-FL-PB	336		
1-3/4" Butcher Block	MJ-PBD-FL-PB	386		
1/4" Hardboard	MH-PBD-FL-PB	343		
Non-Slip Vinyl	MM-PBD-FL-PB	340		

Louvered Panel Doors with Top Louvered Panel				
Top Surface	Model No.	Wt.		
Powder Coated Steel	MB-LPD-FL-LP	337		
1-3/4" Butcher Block	MJ-LPD-FL-LP	387		
1/4" Hardboard	MH-LPD-FL-LP	344		
Non-Slip Vinyl	MM-LPD-FL-LP	341		





#### 36" Wide Mobile Bench Cabinets

1200 lbs. Capacity

12 gauge shelves 36"W x 24"D and are enclosed on three sides, with a flush front edge. Center & bottom shelves have 1-1/2" lip front edge. 36" top shelf height, 38" overall height. Non-marking 5" polyurethane casters, 2 rigid and 2 swivel with total lock brakes. Available with steel or butcher block work top surface.

	Without Center	Shelf	With Center S	helf
Top Surface	Model No.	Wt.	Model No.	Wt.
Powder Coated Steel	MC-2436TL	140	MC3-2436TL	170
1-3/4" Butcher Block	MCJ-2436TL	178	MCJ3-2436TL	208

#### **Mobile Cabinet with 2 Drawers**

Locking storage drawers under top shelf measuring 13"W x 17"D x 4-1/2"H are keyed alike.

	2 Drawers		
Top Surface	Model No.	Wt.	
Powder Coated Steel	MC-2436-2DRTL	167	
1-3/4" Butcher Block	MCJ-2436-2DRTL	205	





## Mobile Bench Cabinet with Heavy-Duty Drawer

1200 lbs. Capacity

Large heavy-duty drawer measures 26"W x 20"D x 6"H and features a full-width recessed handle and padlock hasp.

Top Surface	Model No.	Wt.
Powder Coated Steel	MC-2436-HDTL	179
1-3/4" Butcher Block	MCJ-2436-HDTL	217



## **Mobile Bench Cabinet** with Drawers and Door

Available in 1, 2, or 4 locking storage drawers that measure 13"W x 17"L x 4-1/2"H. Locking door with 27"H storage area. 12 gauge shelves are 36"W x 24"D and are enclosed on 3 sides with 14 gauge steel.

	1 Drawer		2 Drawers		4 Drawers	
Top Surface	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.
Powder Coated Steel	MC1D2436-1DRTL	186	MC1D2436-2DRTL	198	MC1D2436-4DRTL	221
1-3/4" Butcher Block	MCJ1D2436-1DRTL	224	MCJ1D2436-2DRTL	236	MCJ1D2436-4DRTL	259



MC1D2436-4DRTL











## 36" Wide Mobile Bench Cabinets with Locking Doors

1200 lbs. Capacity

12 gauge, 24"D x 36"W top shelf has a retaining lip on 3 sides and a flush front edge. Bottom shelf has 1-1/2" lip front edge. 36" top shelf height, 38" overall height. Secure 3 point latching system with keyed handle anchors the doors at top, center, and bottom. Doors open a full 180 degrees to allow full access. Available with and without center shelf. Non-marking 5" polyurethane casters, 2 rigid and 2 swivel with total lock brakes.

	Without Center	Shelf	With Center S	helf
Top Surface	Model No.	Wt.	Model No.	Wt.
Powder Coated Steel	MC-2D-2436-TL	167	MC3-2D-2436-TL	199
1-3/4" Butcher Block	MCJ-2D-2436-TL	205	MCJ3-2D-2436-TL	237

#### **Mobile Cabinet with Locking Doors & Drawers**

Locking storage drawers measuring 13"W x 17"D x 4-1/2"H are keyed alike.

	2 Drawers		
Top Surface	Model No.	Wt.	
Powder Coated Steel	MC2D2436-2DRTL	194	
1-3/4" Butcher Block	MCJ2D2436-2DRTL	232	

#### **Mobile Bench Cabinet with Doors** and Heavy-Duty Drawer

Large heavy-duty drawer measures 26"W x 20"D x 6"H and features a full-width recessed handle and padlock hasp. Protected by 2 doors with 3-point locking latch.

Top Surface	Model No.	Wt.
Powder Coated Steel	MC2D-2436-HDTL	206
1-3/4" Butcher Block	MCJ2D-2436-HDTL	244



## **Mobile Bench Cabinet** with Heavy-Duty Drawer

1200 lbs. Capacity

Large 26"W x 20"D x 6"H heavy-duty drawer located above locking cabinet for independent access to each feature. Drawer features full-width recessed handle and padlock hasp. Cabinet features 3-point locking latch and 27" cabinet clearance. 12 gauge surface is 24"D x 36"W with a retaining lip on 3 sides. 5" non-marking polyurethane wheels with total lock brakes. 46-1/2" work surface height.

Top Surface	Model No.	Wt.
Powder Coated Steel	MTC-2436-TL	254
1-3/4" Butcher Block	MTCJ-2436-TL	296





#### **Mobile Tables**

1000 lbs. Capacity

All-welded steel construction means years of rugged service and no assembly. This single shelf model with open style cross-arm base serves as a workbench where seating is required. This mobile table has a 34" overall height and features 4 swivel casters for increased mobility and 5" non-marking polyurethane wheels with wheel brakes.

Size	Model No.	Wt.
18 x 32	IP-1832RM-BRK	59
24 x 36	IP-2436RM-BRK	65
24 x 48	IP-2448RM-BRK	77
24 x 60	IP-2460RM-BRK	94
30 x 48	IP-3048RM-BRK	92
30 x 60	IP-3060RM-BRK	104
30 x 72	IP-3072RM-BRK	118



Available with Total Lock Casters replace **-BRK** with **-TL** 



#### **Mobile Tables - 2 Shelf**

1000 lbs. and 3600 lbs. Capacity

All-welded, 12 gauge steel construction. Available with either 5" or 6" non-marking polyurethane casters. 4 swivel casters provide increased mobility. 34" overall height. Available in a 1200 lb. capacity (24-1/2" shelf clearance) or 3600 lb. capacity (23" shelf clearance). Durable gray powder coated finish. Ships set up and ready for immediate use.

	1200 LBS. CAPACITY 4 Swivel Casters		3600 LBS. CAPACITY 4 Swivel Casters		3600 LBS. CAPACITY 2 Rigid 2 Swivel/w Floor Lock	
Size	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.
18 x 32	IP-1832-2	67	_	-	_	-
24 x 36	IP-2436-2	87	IP-2436-2-6PY	113	IP2436-2R-6PYFL	118
24 x 48	IP-2448-2	107	IP-2448-2-6PY	133	IP2448-2R-6PYFL	138
24 x 60	IP-2460-2	127	IP-2460-2-6PY	144	IP2460-2R-6PYFL	164
30 x 48	IP-3048-2	125	IP-3048-2-6PY	154	IP3048-2R-6PYFL	159
30 x 60	IP-3060-2	151	IP-3060-2-6PY	179	IP3060-2R-6PYFL	184
30 x 72	IP-3072-2	177	IP-3072-2-6PY	193	IP3072-2R-6PYFL	223
36 x 72	_	-	IP-3672-2-6PY	233	IP3672-2R-6PYFL	238

Wheel Brakes: 5" add: **-BRK**; 6" add: **-BK**Total Lock Casters: add: **-TL** (5" only)





#### **Mobile Tables - 3 Shelf**

All-welded, heavy-duty, 12 gauge construction, this mobile table is built to last. 3 shelves for plenty of additional storage. Available with 5" or 6" non-marking polyurethane wheels. 4 swivel casters provide greater maneuverability. Available in a 1200 lb. capacity (11" shelf clearance) or 3600 lb. capacity (10-1/2" shelf clearance). 34" overall height with durable powder coated finish.

	1200 LBS. CAPACITY 4 Swivel Casters		3600 LBS. CAPACITY 4 Swivel Casters		3600 LBS. CAPACITY 2 Rigid 2 Swivel/w Floor Lock	
Size	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.
24 x 36	3IP-2436-5PY	124	3IP-2436-6PY	150	3IP2436-2R6PYFL	155
24 x 48	3IP-2448-5PY	154	3IP-2448-6PY	180	3IP2448-2R6PYFL	185
24 x 60	3IP-2460-5PY	186	3IP-2460-6PY	203	3IP2460-2R6PYFL	208
30 x 48	3IP-3048-5PY	182	3IP-3048-6PY	210	3IP3048-2R6PYFL	215
30 x 60	-	-	3IP-3060-6PY	249	3IP3060-2R6PYFL	254

Wheel Brakes: 5" add: -BRK; 6" add: -BK







## Extra-Heavy-Duty 7 Gauge Mobile Table

5000 lbs. Capacity

Top is formed from 7 gauge steel and reinforced with 2" angle iron to withstand the most punishing applications. 2" angle corner posts and additional side braces increase stability. Special heavy service casters to handle extra capacity. Maneuvers on 4 swivel casters with 8" x 2" phenolic wheels and wheel brakes. Overall height 34".

WxL	Model No.	Wt.
30 x 48	IPH-3048-8PHBK	211
30 x 60	IPH-3060-8PHBK	237
36 x 60	IPH-3660-8PHBK	261
36 x 72	IPH-3672-8PHBK	290







4 Position Swivel Lock

Floor Lock

#### **Heavy-Duty Mobile Table**

5000 lbs. Capacity

Formed 12 gauge shelves with extra reinforcement are welded to 2" x 2" corner angles. Special heavy-duty kingpinless casters. Four swivel casters provide maximum maneuverability. Two 4-position swivel locks on one end will convert swivel casters into rigid. Floor lock on other end prevents unwanted movement when necessary. Overall height 36". Powder coated finish.

Overall		
W x D	Model No.	Wt.
24 x 36	IPG2436-8PHFLPL	160
24 x 48	IPG2448-8PHFLPL	175
24 x 60	IPG2460-8PHFLPL	185
30 x 48	IPG3048-8PHFLPL	193
30 x 60	IPG3060-8PHFLPL	219
30 x 72	IPG3072-8PHFLPL	259
36 x 72	IPG3672-8PHFLPL	280



### **Mobile Instrument Table**

1200 lbs. Capacity

Maneuvers over rough surfaces with 4 swivel casters and 9" pneumatic wheels. Available with non-slip vinyl shelf surfaces, or smooth steel. Welded construction for maximum durability. Top shelf height 34", shelf clearance 19-1/2". Powder coated gray finish.

Shelf Size	Model No.	Wt.
Non-Slip	Vinyl Shelf Surfaces	
24 x 36	IP-2436-9PM	96
24 x 48	IP-2448-9PM	112
30 x 48	IP-3048-9PM	131
Without \	/inyl Shelf Surfaces	
24 x 36	IP-2436-9P	92
24 x 48	IP-2448-9P	107
30 x 48	IP-3048-9P	124

Wheel brakes on swivel casters option, add: -BK





### **Heavy-Duty Workbenches**

Up to 10,000 lbs. Capacity

Heavy-duty, welded workbenches have an extra strong 7 gauge reinforced steel top with rounded comfort edges that can support up to 10,000 lbs. uniformly distributed load. Heavy 2" x 2" angle legs are 1/4"-thick with welded 7 gauge gussets. The stationary models have footpads with a 5/8"-diameter anchor hole. A sturdy 12 gauge lower shelf has a 500 lbs. capacity for added storage. All models are welded and ship set up, ready for immediate use.

#### FIXED HEIGHT BENCHES - 34" High

ADJUSTABLE HEIGHT - 28" to 37" high on 1" centers.

SIZE FIXED HEIGHT		ADJUSTABLE HEIGHT		
D x W	Model No.	Wt.	Model No.	Wt.
30 x 36	WW-3036	151	WW-3036-ADJ	176
30 x 48	WW-3048	187	WW-3048-ADJ	212
30 x 60	WW-3060	220	WW-3060-ADJ	245
30 x 72	WW-3072	263	WW-3072-ADJ	288
36 x 60	WW-3660	250	WW-3660-ADJ	275
36 x 72	WW-3672	287	WW-3672-ADJ	312
42 x 84	WW-4284	421	WW-4284-ADJ	446

Also available with heavy-duty drawer, add: -HD



3600 lbs. and 5000 lbs. Capacity

#### With Casters & Floor Lock

Move these heavy-duty workbenches easily with two swivel and two rigid phenolic casters. When in the desired position, engage the floor lock between the swivel casters to avoid unwanted movement. 7 gauge reinforced steel top with rounded comfort edges. Heavy 2" x 2" angle legs are 1/4" thick with 7 gauge welded gussets.

	6" x 2" PHENOLI 34" Bench Top Hei 3600 lbs. Capaci	8" x 2" PHENOLIC 36" Bench Top Height 5000 lbs. Capacity		
Size D x W	Model No.	Wt.	Model No.	Wt.
30 x 36	WW-3036-6PHFL	194	WW-3036-8PHFL	201
30 x 48	WW-3048-6PHFL	231	WW-3048-8PHFL	238
30 x 60	WW-3060-6PHFL	263	WW-3060-8PHFL	270
30 x 72	WW-3072-6PHFL	289	WW-3072-8PHFL	296
36 x 60	WW-3660-6PHFL	297	WW-3660-8PHFL	304
36 x 72	WW-3672-6PHFL	334	WW-3672-8PHFL	341
42 x 84	WW-4284-6PHFL	471	WW-4284-8PHFL	478









Floor lock between swivel casters stops unwanted movement.

## Extra-Heavy-Duty Welded Steel Workbench

15,000 lbs. Capacity

These all-welded, extra heavy-duty workbenches are designed for heavy-duty uses. The workbench top is 7 gauge steel and is supported by a frame of 3" x 1-1/2" structural C channel. The legs are constructed from the 3" C channel and are welded to the top with 7 gauge gussets. 12 gauge lower shelf is 22" deep on 36" models and 28" deep on 42" Models. Holds 500 lbs. Foot pads with 5/8" diameter anchor holes. Clearance below the lower shelf is 5-1/2" to allow fork access. Top height is 34". Gray powder coated finish.

Size D x W	Capacity	Model No.	Wt.
36 x 60 x 34	15,000	WX-3660-34	348
36 x 72 x 34	15,000	WX-3672-34	396
42 x 84 x 34	15,000	WX-4284-34	532





Underside supporting frame







### **Heavy-Duty Cabinet Workbench**

10,000 lbs. Capacity

34"H top is reinforced 7 gauge steel with edges formed to a comfortable radius. Legs are 2" x 2" x 1/4" angle with footpads & lag holes. Doors and enclosure are 12 gauge. Keyed locking handle and 3-point locking mechanism for security. Each 250 lb. capacity drawer measures 26"W x 20"D x 6"H, has heavy-duty rollers, a padlock hasp and full-width recessed handle. Clearance under drawers is 16"H. Durable gray powder coated finish.



Тор	Cabinet Inside	Cabine Only	t	Cabinet with 1 Drawer Centered		Cabinet with 2 Drawers Centered		Cabinet with Center Shelf	
D x W	WxD	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.	Model No	Wt.
30 x 48	43 x 25	WWC-3048	318	WWC-3048-HD	357	_	_	WWC2-3048	349
30 x 60	55 x 25	WWC-3060	371	WWC-3060-HD	410	_	_	WWC2-3060	411
30 x 72	67 x 25	WWC-3072	430	WWC-3072-HD	469	WWC-3072-2HD	508	WWC2-3072	479
36 x 72	67 x 31	WWC-3672	476	WWC-3672-HD	515	WWC-3672-2HD	554	WWC2-3672	537



## **Mobile Heavy-Duty Cabinet Workbench**

3,600 lbs. Capacity

This heavy-duty mobile cabinet features a 37-1/2"H reinforced 7 gauge steel top with comfort edges, and 2" x 2" x 1/4" angle legs. Doors and enclosure are 12 gauge with a keyed locking handle and 3-point locking mechanism for security. Also available with 250 lb. capacity drawer which measures 26"W x 20"D x 6"H, has heavy-duty rollers, a padlock hasp and full-width recessed handle. Clearance under drawers is 16"H. 2 rigid and 2 swivel 6" phenolic wheels with a floor lock to stop unwanted movement while in use. Durable gray powder coated finish.



Includes Floor Lock

Тор	Cabinet Cabinet Only		Cabinet with 1 Drawer Centered		Cabinet with 2 Drawers Centered		Cabinet with Center Shelf		
D x W	WxD	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.	Model No	Wt.
30 x 48	43 x 25	WWC-3048-6PHFL	362	WWC3048-HD6PHFL	401	_	_	WWC2-3048-6PHFL	393
30 x 60	55 x 25	WWC-3060-6PHFL	415	WWC3060-HD6PHFL	454	_	-	WWC2-3060-6PHFL	455
30 x 72	67 x 25	WWC-3072-6PHFL	474	WWC3072-HD6PHFL	513	WWC30722HD6PHFL	552	WWC2-3072-6PHFL	523
36 x 72	67 x 31	WWC-3672-6PHFL	533	WWC3672-HD6PHFL	572	WWC36722HD6PHFL	611	WWC2-3672-6PHFL	594



### **All-Welded Cabinet Workbench**

3000 lbs. Capacity

All-welded, heavy-duty 12 gauge steel construction. Keyed handle with secure 3-point locking system locks doors at the top, center, and bottom. Doors swing open a full 180 degrees to allow complete access. Durable powder coated gray finish. Ships set up and ready for immediate use.

Тор	No Center Shelf		Center Shelf	
D x W x H	Model No.	Wt.	Model No.	Wt.
24 x 48 x 36	WSTC-2448	220	WSTC2-2448	262
30 x 48 x 36	WSTC-3048	248	WSTC2-3048	299
30 x 60 x 36	WSTC-3060	293	WSTC2-3060	356
30 x 72 x 36	WSTC-3072	337	WSTC2-3072	411



#### **Welded Steel Workbenches**

Capacities to 5000 lbs. UDL

Smooth, 12 gauge steel top is double-reinforced with angle iron on the underside and gussets in the corners for exceptional strength and rigidity. These all-welded units ship fully assembled and ready for immediate use. Available with half lower shelf or open base. Also available with 16 gauge pegboard or louvered panel.



SIZE		with Lower Shelf		with Open Base	
D x W	Cap.	Model No.	Wt.	Model No.	Wt.
24 x 48	5000	WST2-2448-AH	111	WST1-2448-AH	89
24 x 60	4500	WST2-2460-AH	138	WST1-2460-AH	111
30 x 48	5000	WST2-3048-AH	126	WST1-3048-AH	100
30 x 60	4500	WST2-3060-AH	155	WST1-3060-AH	123
30 x 72	4000	WST2-3072-AH	188	WST1-3072-AH	144
36 x 60	4500	WST2-3660-AH	176	WST1-3660-AH	138
36 x 72	4000	WST2-3672-AH	203	WST1-3672-AH	159
36 x 84	3000	WST2-3684-AH	225	WST1-3684-AH	179

#### With Added Pegboard or Louvered Panel

SIZE		with Lower Shelf		with Open Base	
D x W	Cap.	Model No.	Wt.	Model No.	Wt
24 x 48	5000	WST2-2448-AH-PB	136	WST1-2448-AH-PB	114
24 X 60	4500	WST2-2460-AH-PB	168	WST1-2460-AH-PB	141
30 x 48	5000	WST2-3048-AH-PB	161	WST1-3048-AH-PB	125
30 x 60	4500	WST2-3060-AH-PB	185	WST1-3060-AH-PB	153
30 x 72	4000	WST2-3072-AH-PB	225	WST1-3072-AH-PB	181
36 X 60	4500	WST2-3660-AH-PB	206	WST1-3660-AH-PB	168
36 x 72	4000	WST2-3672-AH-PB	240	WST1-3672-AH-PB	196

Also available with Louvered Panel, replace -PB with -LP

**Fixed Height Workbenches -** 36" overall height. Legs and lower braces are 1-1/2" x 1-1/2" x 3/16" thick angle iron. Legs have footpads with 5/8" hole for mounting to the floor.

SIZE		with Lower Shelf		with Open Base	
D x W	Cap.	Model No.	Wt.	Model No.	Wt.
24 x 48	5000	WST2-2448-36	109	WST1-2448-36	87
24 x 60	4500	WST2-2460-36	136	WST1-2460-36	109
30 x 48	5000	WST2-3048-36	124	WST1-3048-36	98
30 x 60	4500	WST2-3060-36	153	WST1-3060-36	121
30 x 72	4000	WST2-3072-36	186	WST1-3072-36	142
36 x 60	4500	WST2-3660-36	174	WST1-3660-36	136
36 x 72	4000	WST2-3672-36	201	WST1-3672-36	157
36 x 84	3000	WST2-3684-36	224	WST1-3684-36	177

#### With Added Pegboard or Louvered Panel

SIZE		with Lower Shelf		with Open Base	
D x W	Cap.	Model No.	Wt.	Model No.	Wt.
24 x 48	5000	WST2-2448-36-PB	134	WST1-2448-36-PB	112
24 X 60	4500	WST2-2460-36-PB	166	WST1-2460-36-PB	139
30 x 48	5000	WST2-3048-36-PB	159	WST1-3048-36-PB	123
30 x 60	4500	WST2-3060-36-PB	183	WST1-3060-36-PB	151
30 x 72	4000	WST2-3072-36-PB	223	WST1-3072-36-PB	179
36 X 60	4500	WST2-3660-36-PB	204	WST1-3660-36-PB	166
36 x 72	4000	WST2-3672-36-PB	238	WST1-3672-36-PB	194

Also available with Louvered Panel, replace -PB with -LP

















## **Welded Steel Workbench** with Hardboard Top

Capacities to 5000 lbs. UDL

1/4" hardboard surface, attached directly over 12 gauge steel top, helps to deaden the sound of heavy blows and metal to metal contact. 12 gauge steel top is double-reinforced with angle iron on the underside and gussets in the corners for exceptional strength and rigidity. These all-welded units ship fully assembled and ready for immediate use.

SIZE		with Lower Shelf		with Open Base				
D x W	Cap.	Model No.	Wt.	Model No.	Wt			
<b>Fixed Heigh</b>	Fixed Height Models - 36" Overall Height							
24 x 48	5000	WSH2-2448-36	116	WSH1-2448-36	94			
30 x 48	5000	WSH2-3048-36	132	WSH1-3048-36	106			
30 x 60	4500	WSH2-3060-36	186	WSH1-3060-36	147			
36 x 72	4000	WSH2-3672-36	216	WSH1-3672-36	172			
36 x 84	3000	WSH2-3684-36	244	WSH1-3684-36	197			
<b>Adjustable</b>	Height	Models - 27" - 41"	High	in 2" Increments				
24 x 48	5000	WSH2-2448-AH	118	WSH1-2448-AH	96			
30 x 48	5000	WSH2-3048-AH	134	WSH1-3048-AH	108			
30 x 60	4500	WSH2-3060-AH	188	WSH1-3060-AH	149			
36 x 72	4000	WSH2-3672-AH	218	WSH1-3672-AH	174			
36 x 84	3000	WSH2-3684-AH	246	WSH1-3684-AH	199			



#### **Stainless Steel Top Welded Workbenches**

Combine the strength of a welded steel table with corrosion resistance of Stainless Steel! 16 gauge Type 304 Stainless Steel with a #4 finish is applied securely to the 12 gauge steel top. The lower shelf and remaining components have a durable gray powder coat finish. The stainless steel surface provides superior chemical, corrosion, and rust resistance without sacrificing overall strength.

SIZE D x W	Cap.	Model No.	Wt.				
<b>Fixed Heigh</b>	Fixed Height Models - 36" Overall Height						
30 x 48	5000	WSS2-3048-36	153				
30 x 60	4500	WSS2-3060-36	188				
30 x 72	4000	WSS2-3072-36	229				
Adjustable I	Height	Models - 27" - 41" High in 2" Increments					
30 x 48	5000	WSS2-3048-AH	155				
30 x 60	4500	WSS2-3060-AH	190				
30 x 72	4000	WSS2-3072-AH	231				



WSL2-2448-36

## **Welded Steel Workbenches** with Back and End Stops

12 gauge steel top workbench with angle iron reinforcements give these workbenches capacity to 5000 lbs. 1-1/2" raised edge on back and each side to keep parts and components contained. Fully welded and shipped set up, ready for use. Footpads have mounting holes ready for anchoring to your floor. Durable gray powder coat finish.

SIZE	FIXED HEIGHT 36" Top Height		ADJUSTABLE HEIGH 27"-41" High in 2" Incren	_	
D x W	Cap.	Model No.	Wt.	Model No.	Wt.
24 x 48	5000	WSL2-2448-36	114	WSL2-2448-AH	116
24 x 60	4500	WSL2-2460-36	146	WSL2-2460-AH	148
30 x 48	5000	WSL2-3048-36	134	WSL2-3048-AH	136
30 x 60	4500	WSL2-3060-36	164	WSL2-3060-AH	166
30 x 72	4000	WSL2-3072-36	198	WSL2-3072-AH	200
36 x 60	4500	WSL2-3660-36	187	WSL2-3660-AH	189
36 x 72	4000	WSL2-3672-36	215	WSL2-3672-AH	217
36 x 84	3000	WSL2-3684-36	239	WSL2-3684-AH	240

## **WORKBENCHES & SHOP TABLES**

## **Welded Workbenches** with Backstops

3000 lbs. Capacity UDL

Formed 12 gauge steel tops are double reinforced and have a 3" high backstop. Half-depth lower shelf is 12 gauge with a 3" lip at rear. Ships fully assembled. Durable powder coated finish. Available with a welded locking storage drawer.

STATIONARY MODELS - 3000 lbs. Capacity Adjustable from 27" to 41" high in 2" increments. Fixed Heights are 36" high with angle iron legs and have footpads with 5/8" lag hole.

Size	ADJUSTABLE HE	IGHT	FIXED HEIGHT	
D x W	Model No.	Wt.	Model No.	Wt.
28 x 48	WA-2848	119	WB-2848	106
28 x 60	WA-2860	138	WB-2860	126
28 x 72	WA-2872	158	WB-2872	155

Also available with locking drawer, add: -DR



5" swivel polyurethane casters with total locks. 36" high with angle iron legs.

Size	NO DRAWER		WITH DRAWER	
D x W	Model No.	Wt.	Model No.	Wt.
28 x 48	WM-2848	138	WM-2848-DR	161
28 x 60	WM-2860	157	WM-2860-DR	180
28 x 72	WM-2872	176	WM-2860-DR	199

Factory Installed Options (add code to Workbench Model)

- -E End Stops: 1-1/2" high formed 12 gauge.
- -PB Pegboard: 24" high 16 gauge pegboard panel.
- -LP Louvered Panel: 24" high 16 gauge panel.
- -R Riser Shelf: 12" high x 10" deep.
- -DR Locking Drawer: Measures 13"W x 17"L x 4-1/2" H inside.





### Welded Workbench with Monitor Mount

3000 lbs. Capacity UDL

This Welded Workbench features a universal steel VESA mount for both 75mm and 100mm square patterns. It can be installed into any of the three positions (left, right, or center) and rotated 360 degrees and then secured in the desired position. VESA mount supports up to 35lb, monitors. Formed 12 gauge steel top is double-reinforced and features a 3" high backstop. 12 gauge half-depth lower shelf also features a 3" high backstop. Ships fully assembled and ready for immediate use. Durable powder coated finish.

Size	ADJUSTABLE HEIGHT 27" - 41" High in 2" Increm	FIXED HEIGHT 36" Overall Height		
D x W	Model No. Wt.		Model No.	Wt.
28 X 48	WA-2848-VM	125	WB-2848-VM	122
28 X 60	WA-2860-VM	144	WB-2860-VM	142
28 X 72	WA-2872-VM	164	WB-2872-VM	161



## **WORKBENCHES & SHOP TABLES**







Legs Folded

## Folding Leg Welded Workbenches

3000 lbs. Capacity

Folding legs are hinged and welded to the top, and can be folded down for transport or storage by removing wing nut that secures leg braces. Legs adjust in 2" increments.

**Steel Top** – Welded 12 gauge steel tops are channel reinforced for added strength and durability. 28" to 42" high.

D x W	Model No.	Wt.
30 x 72	WF-3072-AH	139
36 x 72	WF-3672-AH	152
36 x 84	WF-3684-AH	171

**Hardboard over Steel Top** – 1/4" hardboard over 12 gauge steel. 28-1/4" to 42-1/4" high.

D x W	Model No.	Wt.
36 x 72	WFH-3672-AH	167
36 x 84	WFH-3684-AH	192

#### **Butcher Block Top**

3000 lbs. Capacity

1-3/4" thick. 29-3/4" to 43-3/4" high.

D x W	Model No.	Wt.
30 x 72	WFJ-3072-AH	147



## Continuous Width Production Tables

3000 lbs. Capacity

Ideal for assembly lines. No stringer means working from both sides!

Heavy-duty 12 gauge tops are available in either 30" or 36" depth with reinforced understructure and strengthening gussets. Tops come in 4, 5, and 6 ft. widths to allow for an infinitely continuous work surface in 1 ft. increments (excludes 7 ft.). Starter kit includes (1) table top, (2) leg sets, and (4) gussets. Each additional Add-on kit includes (1) table top, (1) leg set and (4) gussets. Legs and gussets bolt to table-tops with included hardware. Ships flat. Overall height is 36". Gray powder coated finish.



STARTER KIT includes (1) table top, (2) leg sets, and (4) gussets			include	-	ADD-ON KIT top (1) leg set, and (4) guss	sets	
Depth	Width	Model No.	Wt.	Depth	Width	Model No.	Wt.
	4 ft.	WSE3048-STARTER	126		4 ft.	WSE3048-ADDON	126
30"	5 ft.	WSE3060-STARTER	138	30"	5 ft.	WSE3060-ADDON	138
	6 ft.	WSE3072-STARTER	153		6 ft.	WSE3072-ADDON	153
	4 ft.	WSE3648-STARTER	140		4 ft.	WSE3648-ADDON	140
36"	5 ft.	WSE3660-STARTER	154	36"	5 ft.	WSE3660-ADDON	154
	6 ft.	WSE3672-STARTER	170		6 ft.	WSE3672-ADDON	170





## **Butcher Block Top Tables**

These 1-3/4" thick butcher block tops have a two-coat catalyzed varnish finish, and are attached to an all-welded, angle steel frame for unmatched rigidity and strength. The impact resistant, hardwood tops are nonconductive, resist damage from heavy blows, and provide an extremely durable, yet "forgiving" work surface. All models are fully assembled and ready for immediate use.

**LEG LEVELER MODELS** – Adjustable from 32" to 35" high. 2000 lbs. capacity.

SIZE	OPEN BASE		LOWER SHELF	
D x W	Model No.	Wt.	Model No.	Wt.
24 x 24	WT-2424-LL	59	WTS-2424-LL	69
24 x 36	WT-2436-LL	78	WTS-2436-LL	95
24 x 48	WT-2448-LL	97	WTS-2448-LL	121
30 x 48	WT-3048-LL	114	WTS-3048-LL	146
30 x 60	WT-3060-LL	134	WTS-3060-LL	177
30 x 72	WT-3072-LL	154	WTS-3072-LL	208
36 x 72	WT-3672-LL	179	WTS-3672-LL	243

Add for Locking Storage Drawer Options (Right Side Mount)

-DR Single -2DR Double (Stacked)

Drawer measures 13"W x 17"D x 4-1/2"H

**SWIVEL CASTER MODELS** – 3" x 1-1/4" hard rubber casters with wheel brakes 35" high. 1000 lbs. capacity.

SIZE	OPEN BASE		LOWER SHELF	
D x W	Model No.	Wt.	Model No.	Wt.
24 x 24	WT-2424-3R	63	WTS-2424-3R	73
24 x 36	WT-2436-3R	82	WTS-2436-3R	99
24 x 48	WT-2448-3R	101	WTS-2448-3R	125
30 x 48	WT-3048-3R	118	WTS-3048-3R	150
30 x 60	WT-3060-3R	138	WTS-3060-3R	181
30 x 72	WT-3072-3R	160	WTS-3072-3R	212
36 x 72	WT-3672-3R	183	WTS-3672-3R	247

Add for Locking Storage Drawer Options (Right Side Mount)

-DR Single -2DR Double (Stacked)

Drawer measures 13"W x 17"D x 4-1/2"H





## **Heavy-Duty Butcher Block Top Mobile Table**

3000 lbs. Capacity

Heavy-duty, 12 gauge construction. 1-3/4" thick butcher block top provides an impact resistant, nonconductive work surface. Butcher block resists damage from heavy blows, and provides an extremely durable, yet "forgiving" work surface. All models are fully assembled and ready for immediate use. Your choice of 4 swivel casters with wheel brakes or 2 swivel and 2 rigid caster with a floor lock. All models roll smoothly with 6" non-marking polyurethane wheels.

TOP SIZE	2 Rigid, 2 Swivel with Floor Lock		4 Swivel with Wheel Brakes	
DxWxH	Model No.	Wt.	Model No.	Wt.
24 x 36 x 34	IPJ2436-2R6PYFL	129	IPJ-2436-6PYBK	126
24 x 48 x 34	IPJ2448-2R6PYFL	155	IPJ-2448-6PYBK	152
30 x 48 x 34	IPJ3048-2R6PYFL	175	IPJ-3048-6PYBK	172
30 x 60 x 34	IPJ3060-2R6PYFL	214	IPJ-3060-6PYBK	211
30 x 72 x 34	IPJ3072-2R6PYFL	246	IPJ-3072-6PYBK	243
36 x 72 x 34	IPJ3672-2R6PYFL	284	IPJ-3672-6PYBK	281













Model WT1-2448-LL-42

### **Welded Steel Workbenches** with Butcher Block Tops

3000 lbs. Capacity

Butcher Block top is 1-3/4" thick, helps deaden sound, and absorbs impact. Replaceable top is attached to an all-welded steel frame. Half lower shelf constructed of 12 gauge steel with 3" high lip at rear. Available in fixed and adjustable heights, and with optional factory installed locking drawer that measures 13"W x 17"D x 4-1/2"H (right side mount); add: - DR

**FIXED HEIGHT MODELS** – 37-3/4" overall height. Legs and lower braces are 1-1/2" x 1-1/2" x 3/16" angle with footpads for anchoring to the floor

SIZE	SIZE WITHOUT DRAWER		WITH DRAWER		
D x W	Model No.	Wt.	Model No.	Wt.	
24 x 48	WSJ2-2448-36	125	WSJ2-2448-36-DR	148	
30 x 48	WSJ2-3048-36	141	WSJ2-3048-36-DR	164	
30 x 60	WSJ2-3060-36	169	WSJ2-3060-36-DR	194	
30 x 72	WSJ2-3072-36	202	WSJ2-3072-36-DR	228	
36 x 72	WSJ2-3672-36	223	WSJ2-3672-36-DR	250	

#### ADJUSTABLE HEIGHT MODELS – 28-3/4" to 42-3/4" High in 2" increments

SIZE	WITHOUT DRAWER		WITH DRAWER	
D x W	Model No.	Wt.	Model No.	Wt.
24 x 48	WSJ2-2448-AH	125	WSJ2-2448-AH-DR	148
30 x 48	WSJ2-3048-AH	141	WSJ2-3048-AH-DR	164
30 x 60	WSJ2-3060-AH	169	WSJ2-3060-AH-DR	194
30 x 72	WSJ2-3072-AH	202	WSJ2-3072-AH-DR	228
36 x 72	WSJ2-3672-AH	223	WSJ2-3672-AH-DR	250

## **Counter Height Work Table** with Butcher Block Top

The 1-3/4" thick butcher block top work surface is 42" high. Heavy-duty leg levelers provide up to an additional 3" of height. Butcher block tops are attached to an all-welded, powder coated steel frame and ship fully assembled.

Overall W x D	Model No.	Wt.
24 x 48	WT1-2448-LL-42	105
30 x 48	WT1-3048-LL-42	121
30 x 60	WT1-3060-LL-42	137
30 x 72	WT1-3072-LL-42	160
36 x 72	WT1-3672-LL-42	184



## **Conference Room Table** with Butcher Block Top

This attractive table is suitable for both industrial and in-office applications and features inset legs for easy and comfortable seating. The 1-3/4" thick butcher block top is impact resistant, nonconductive, and extremely durable. The welded steel frame is constructed of 1-1/2" square tubing with a 1/8" thick wall and a durable powder coated finish. The unit ships fully assembled and ready for immediate use. Heavy-duty leg levelers adjust for 31"-34" overall height.

Overall D x W	Model No.	Wt.
36 x 72	CRT-3672-LL	170





## Work Center Cabinet with Butcher Block Top

1-3/4" butcher block top provides a durable, yet forgiving work surface. The nonconductive butcher block top is securely attached to the all-welded, heavy-duty, 14 gauge steel cabinet. Features a keyed handle with a 3-point locking mechanism. 37" overall height. 26" high interior cabinet clearance. Fully assembled and ready for immediate use. Durable powder coated finish.

Overall		
WxD	Model No.	Wt.
24 x 36	WTC-2D-2436-LL	166
24 x 48	WTC-2D-2448-LL	218
30 x 48	WTC-2D-3048-LL	230
30 x 60	WTC-2D-3060-LL	265
30 x 72	WTC-2D-3072-LL	302



## **Compact Work Center Cabinet** with Locking Door

This Compact Work Center Cabinet features a 1-3/4" butcher block top measuring 24"D x 24"W, and a keyed handle with a 3-point locking mechanism. 34" overall height. Leg levelers allow adjustment on uneven floors, as well as 3" overall height adjustment. Durable powder coated finish. Ships fully assembled and ready for immediate use.

Overall W x D	Model No.	Wt.
24 x 24	WTC-1D-2424-LL	134



## Compact Work Center Cabinet with Drawer

1-3/4" thick butcher block top table enclosed on three sides with heavy-duty 14 gauge steel sides. The top measures 24" x 24" and stands 34" tall. Leg levelers allow adjustment on uneven floors, as well as 3" overall height adjustment. Locking storage drawer is 13"W x 17"D x 4-1/2"H and comes with two keys. Durable powder coated finish. Ships fully assembled and ready for immediate use.

Overall W x D	Model No.	Wt.
24 x 24	WTC-2424-LL-DR	134



## **WORKBENCHES & SHOP TABLES**







#### MOBILE VERSION AVAILABLE

Swivel casters with wheel brakes,

3" rubber wheels (9 lbs.), add: **-3R** to Model No.

Note: Models with casters are same overall height as those without casters on Single Shelf Models. Capacity 500 lbs.

### **Steel-Top Machine Tables**

2000 lbs. Capacity

12 gauge smooth steel top won't warp or splinter. Legs and braces are 1-1/2" x 1-1/2" angle iron. All-welded units ship set up and ready for immediate use. Available in a variety of sizes and heights.

Тор		Machine Table		Machine Table with Dra	wer
D x W	Height	Model No.	Wt.	Model No.	Wt.
	18	MT1-1824-18	31	-	-
	24	MT1-1824-24	33	-	-
18 x 24	30	MT1-1824-30	35	-	-
	36	MT1-1824-36	37	_	-
	42	MT1-1824-42	44	-	-
	18	MT1-2436-18	48	MT1-2436-18-ED	73
	24	MT1-2436-24	50	MT1-2436-24-ED	75
24 x 36	30	MT1-2436-30	52	MT1-2436-30-ED	77
	36	MT1-2436-36	55	MT1-2436-36-ED	80
	42	MT1-2436-42	58	MT1-2436-42-ED	83
	18	MT1-2448-18	75	MT1-2448-18-ED	101
	24	MT1-2448-24	78	MT1-2448-24-ED	104
24 x 48	30	MT1-2448-30	82	MT1-2448-30-ED	108
	36	MT1-2448-36	86	MT1-2448-36-ED	112
	42	MT1-2448-42	89	MT1-2448-42-ED	115



#### **Multi-Shelf Machine Tables**

2000 lbs. Capacity

All-welded units have 12 gauge shelves. Top shelf has flush edges, and reinforcement on larger sizes. Lower shelves have 1-1/2" retaining lip to contain small parts. Angle iron legs are 3/16" thick with 2-1/2" footpads. 32-1/2" top height.

Size D x W x H	2 Shelves 22" clearance	Wt.	3 Shelves 10-1/4" clearance	Wt.
18 x 24 x 32-1/2	MT1824-2	53	MT1824-3	70
18 x 32 x 32-1/2	MT1832-2	60	MT1832-3	81
24 x 36 x 32-1/2	MT2436-2	80	MT2436-3	111
24 x 48 x 32-1/2	MT2448-2	100	MT2448-3	140
24 x 60 x 32-1/2	MT2460-2	131	MT2460-3	183
30 x 48 x 32-1/2	MT3048-2	130	MT3048-3	180

Accessory Drawer -  $13\text{"W} \times 15\text{"D} \times 5\text{"H}$ , add **-ED** to Model No. (not available on 18" deep models)

#### **OPTIONS AVAILABLE**

## Swivel casters with wheel brakes,

3" rubber wheels (9 lbs.), add: -3R to Model No. (Add 4" to overall height on Multi-Shelf models.) 500 lbs. Capacity



#### Adjustable Height

Leg Levelers - Adjusts standard table height from +1" to +4", add -LL to Model No. 2000 lbs. Capacity







## **Heavy-Duty Machine Tables**

10,000 lbs. Capacity

Top is formed from 3/16" thick steel for the heaviest applications, and reinforced with 2" x 2" x 3/16" angle iron. Legs are 2" x 2" x 1/4" angle and have 2-1/2" footpads with 5/8" diameter lag holes. All-welded construction. Available with open base or full flush steel lower shelf.

Тор		OPEN BASE	<u> </u>	LOWER SHELF	
D x W	Height	Model No.	Wt.	Model No.	Wt.
	24	MTH1-1630-24	96	MTH2-1630-24	113
16 x 30	30	MTH1-1630-30	103	MTH2-1630-30	120
	36	MTH1-1630-36	109	MTH2-1630-36	127
	24	MTH1-2230-24	102	MTH2-2230-24	127
22 x 30	30	MTH1-2230-30	108	MTH2-2230-30	134
	36	MTH1-2230-36	114	MTH2-2230-36	141
	24	MTH1-2830-24	116	MTH2-2830-24	149
28 x 30	30	MTH1-2830-30	122	MTH2-2830-30	156
	36	MTH1-2830-36	128	MTH2-2830-36	163
	24	MTH1-3036-24	134	MTH2-3036-24	178
30 x 36	30	MTH1-3036-30	140	MTH2-3036-30	185
	36	MTH1-3036-36	147	MTH2-3036-36	192
	24	MTH1-3048-24	164	MTH2-3048-24	225
30 x 48	30	MTH1-3048-30	170	MTH2-3048-30	232
	36	MTH1-3048-36	179	MTH2-3048-36	239
	24	MTH1-3060-24	191	MTH2-3060-24	268
30 x 60	30	MTH1-3060-30	197	MTH2-3060-30	275
	36	MTH1-3060-36	203	MTH2-3060-36	282





## **Adjustable Height Heavy-Duty Machine Table**

10,000 lbs. Capacity

7 gauge steel top and heavy 2" x 2" leg construction are used to make a heavy-duty machine table that will meet the most demanding application. Adjustable legs allow table height positioning from 30" to 37" high with 1" increments.

Size	Model No.	Wt.
16 x 30	MTH1-1630-AH	115
22 x 30	MTH1-2230-AH	124
28 x 30	MTH1-2830-AH	141
30 x 36	MTH1-3036-AH	159
30 x 48	MTH1-3048-AH	188
30 x 60	MTH1-3060-AH	212



## 7 Gauge Mobile Machine Table

3600 lbs. Capacity

This mobile version of our heaviest machine table has 4 swivel 6" x 2" phenolic casters for ease of movement when the need arises, and wheel brakes to keep it stationary the rest of the time. Top is formed from 3/16" thick steel. Legs are 2" x 2' x 1/4" structural angle iron. Welded – no assembly required.

Тор			
D x W	Height	Model No.	Wt.
22 x 30	30	MTH2230-6PHBK30	133
22 X 30	36	MTH2230-6PHBK36	139
28 x 30	30	MTH2830-6PHBK30	150
20 X 30	36	MTH2830-6PHBK36	156
30 x 36	30	MTH3036-6PHBK30	168
30 X 30	36	MTH3036-6PHBK36	174
30 x 48	30	MTH3048-6PHBK30	197
30 X 40	36	MTH3048-6PHBK36	203





#### Wheel Selection Guide

**Polyurethane Wheels** Load Capacity Range: 300 - 1,000 lbs.

**Characteristics:** Easier rolling for higher capacities, long-lasting, chemical resistant, non-marking and quiet operation.

A polyurethane tread is superior for industrial, warehouse, and institutional applications with a great combination of easy rolling and maneuverability under heavy load capacity while able to quietly roll over rough floor surfaces.

**Phenolic Wheels** Load Capacity Range: 900 - 1,250 lbs.

Characteristics: Best rolling for heavy load capacities, long-lasting, chemical resistant, high temperature, non-marking for smooth floor surface.

A solid one piece wheel that is high pressure molded with reinforced fiber-filled phenolic resin. Offers the least rolling resistance on smooth floors, but does not absorb vibration over rough surfaces.

#### Mold-On Rubber Wheels

Load Capacity Range: 500 - 600 lbs.

**Characteristics:** Better load capacity, long-lasting, cushion tread, absorbs shock and vibration, floor protection and guiet operation.

Rubber tread vulcanized to metal core. A good combination of load capacity and cushion tread that quietly rolls over rough floors. A great wheel choice for heavy industrial and warehouse applications.

**Solid Rubber Wheels** Load Capacity Range: 300 - 400 lbs.

Characteristics: Good load capacity, great for rough floor surfaces, puncture-proof, floor protection and quiet operation.

Cushioned rubber tire that is more stable and easier to roll under heavy loads than pneumatic wheels. These wheels are a rugged, maintenancefree (no air pressure to maintain) alternative to pneumatic wheels.

**Pneumatic Wheels** Load Capacity Range: 300 - 400 lbs.

Characteristics: Great cushion ride over rough floor surfaces, best option for traveling over small obstructions or outdoor applications. Best shock and vibration absorption.

An air filled rubber tire on a metal hub is able to easily roll over uneven surfaces and bumps but does require air pressure management. Under heavy loads, the pneumatic tire profile will compress, creating greater rolling resistance. Ideal for handling fragile loads over rough surfaces.

**Flat Free Hand Truck Wheels** Load Capacity Range: 400 lbs.

Characteristics: Wide rubber tread disperses the load better over irregular or softer surfaces. Less tread compression than pneumatic or solid rubber tires and ball bearings improve rollability of heavier loads.

### Wheel Specifications

Wheel Diameter	Tread Width	Wheel Type	Bearing I.D.	Centered Hub Model No.	Offset Hub Model No.
5	1-1/4	Polyurethane	3/8" Ball	WHMP-05114	_
6	2	Mold-On Rubber	3/4" Roller	WHMS-0620	-
		Polyurethane	1/2" Ball	WHMP-0620	_
		Phenolic	3/4" Roller	WHPL-0620	_
8	2	Mold-On Rubber	3/4" Roller	WHMS-0820	_
		Polyurethane	1/2" Ball	WHMP-0820	_
		Phenolic	3/4" Roller	WHPL-0820	_
8	2-1/2	Solid Rubber	5/8" Ball	-	WHSP-0825-0
9	3	Pneumatic 2.80/2.50-4	5/8" Ball	WHPN-0830	-
10	2-3/4	Solid Rubber	5/8" Ball	WHSP-1027P-C	WHSP-1027-P
10	3-1/2	Pneumatic 4.10/3.50-4	5/8" Ball	WHPN-1035-C	WHPN-1035
10	3-1/2	Flat Free 4.10/3.50-4	5/8" Ball		WHFF-1035
12	2-1/2	Mold-On Rubber	1" Roller	WHMS-12250	-
12	3-1/2	Pneumatic 4.10/3.50-6	5/8" Ball	WHPN-1235	-
		Pneumatic 4.10/3.50-6	1" Roller	WHPN-1235-RB	_
16	4	Pneumatic 4.80/4.00-8	1" Roller	WHPN-1640	-



#### **Model Number Index**

2,3G/GL6	
2LDWP29	
2PD72	
2RP230	
2RP3S/4S/3X/4X36	
3,4,5M/ML12	
3,4,5MLP29	
3,4,5SH-A50	
3DS8	
3ERLG/ERLGL7	
3GH5	
3IP97-98	
3LG/LGL4.11.14	
3MW87	
3SW88	
4,5,6SH(P)50	
5LML13	
5SE	
6BC83	
- <b>A</b> -	
ABR64	
ABS	
AF67	
AFPB/LP/CP/PBLP86	
AFS60	
AM13	
APT/APTP65-66	
ASR66	
BB19	
BC13,82	
BCPB85	
BOP67	
BR62	
BRT61	
BTS/BTX38	
-C-	
CA(RD)(WD)33	
CBR62	
CC21	
CD25	
CH26	
CRT106	
CS/CSW24	

CT......25

-D-	
DC/DCB	68
DET	30
DR/DRB	22
DS	8-10
DT	63
-E-	
EA	14
ERBST	61
ERG/ERGL	7
ERLG/ERLGL	7
-F-	
FRDB	52
- <b>G</b> -	
G/GL	.5,6,11
GCK	15
GF/GLF	
GH	
GLK	
GS	
-H-	0 00
HC	49
HE	
HEE	- ,
HRS	49
HT	39
- -	
IBCS	55
IF/IF1S	
IJP	105
IP	97
IPB/ILP	85
IPH/IPG	98
-L-	
LC/LCP	64
LG/LGL	4,11
LGK/LGLK	15
LGLP	14,28
LK/LKL	,
LW/ LDW/ LWP	,
LWRW	
-M-	
MB/MJ/MH/MM (P)	91-94
MC/MCJ91	
	,

MD/MU(P)	73
MIC	
MNC	90
MS	82-83
MT	108
MTC	96
MTH	109
MW/MWLP/MWPB	87
-N-	
NB6W	23
NBB1	18-19,22
NBH	19
NBP	63
NBX3	21
NCB	18
NLB	18
NP/NP2	28
-0-	
OE	63
OT/OTL	34
-P-	
PD	69-72
PPT	32
PSR/PSX	
PT/PTC	68
-Q-	
QC	88
-R-	
R	
RC/RCS	
RCM	
RCPB	
RD/RDP	
RDC/RDCB	
RDCP	
RDS	
RL	
RNB/RNH/RNL	
RP3S/4S/3X/4X	
RPDS/DX	
RR	
RS/RS3	
RT3/RT4	58-59

S1/S2/S3       31-32,34         S1S       85         SB(S)       41         SC/SCN/SC2/SC-A       40, 42-43,45         SGS/SGH       52         SL       43-46         SPS       72         SR       66         SSB       53-54         SSF       53         SSL       46-48         SSLP       48         SSP       54         SS-RD       53         SST       54-55         SSW       47         ST       42         SW       88         -T-         T(F/FF) Hand Trucks       74-77         T1/T2/T3       31-32,34         T500/T700       20-21         T800       29         TB       61         TT       10         TW       78         -W-         WA/WB/WM       103         WCK       81         WF       104         WG       81         WF       104         WSL2       102         WSS2       102         WST1/WST2       101     <	-S-		
SB(S)	S1/S2/S3	.31-32,34	
SC/SCN/SC2/SC-A40, 42-43,45         SGS/SGH       52         SL	S1S	85	
SGS/SGH       52         SL       43-46         SPS       72         SR       66         SSB       53-54         SSF       53         SSL       46-48         SSLP       48         SSP       54         SS-RD       53         SST       54-55         SSW       47         ST       42         SW       88         -T-         T(F/FF) Hand Trucks       74-77         T1/T2/T3       31-32,34         T500/T700       20-21         T800       29         TB       61         TT       10         TW       78         -W-         WA/WB/WM       103         WCK       81         WF       104         WG       81         WSE       104         WSH1/WSH2       102         WSS2       102         WST1/WST2       101         WSTC       100         WT/WTS       105-106         WTC       100			
SL       43-46         SPS       72         SR       66         SSB       53-54         SSF       53         SSL       46-48         SSLP       48         SSP       54         SS-RD       53         SST       54-55         SSW       47         ST       42         SW       88         -T-         T(F/FF) Hand Trucks       74-77         T1/T2/T3       31-32,34         T500/T700       20-21         T800       29         TB       61         TT       10         TW       78         -W-         WA/WB/WM       103         WCK       81         WF       104         WG       81         WSE       104         WSH1/WSH2       102         WSS2       102         WST1/WST2       101         WSTC       100         WT/WTS       105-106         WTC       100	SC/SCN/SC2/SC-A40,	42-43,45	
SPS       72         SR       66         SSB       53-54         SSF       53         SSL       46-48         SSLP       48         SSP       54         SS-RD       53         SST       54-55         SSW       47         ST       42         SW       88         -T-         T(F/FF) Hand Trucks       74-77         T1/T2/T3       31-32,34         T500/T700       20-21         T800       29         TB       61         TT       10         TW       78         -W-         WA/WB/WM       103         WCK       81         WF       104         WG       81         WSE       104         WSH1/WSH2       102         WSS2       102         WST1/WST2       101         WSTC       100         WT/WTS       105-106         WTC       100	SGS/SGH	52	
SR	SL	43-46	
SSB	SPS	72	
SSF	SR	66	
SSL	SSB	53-54	
SSLP 48 SSP 54 SS-RD 53 SST 54-55 SSW 47 ST 42 SW 88 -T- T(F/FF) Hand Trucks 74-77 T1/T2/T3 31-32,34 T500/T700 20-21 T800 29 TB 61 TT 10 TW 78 -W- WA/WB/WM 103 WCK 81 WF 104 WG 81 WSE 104 WSH1/WSH2 102 WSJ2 106 WSL2 102 WSS2 102 WST1/WST2 101 WSTC 107 WW 99 WWC 100	SSF	53	
SSP       54         SS-RD       53         SST       54-55         SSW       47         ST       42         SW       88         -T-         T(F/FF) Hand Trucks       74-77         T1/T2/T3       31-32,34         T500/T700       20-21         T800       29         TB       61         TT       10         TW       78         -W-         WA/WB/WM       103         WCK       81         WF       104         WG       81         WSE       104         WSH1/WSH2       102         WSJ2       106         WSL2       102         WSS2       102         WST1/WST2       101         WSTC       100         WT/WTS       105-106         WTC       100	SSL	46-48	
SS-RD	SSLP	48	
SST	SSP	54	
SSW	SS-RD	53	
ST	SST	54-55	
SW	SSW	47	
TT- T(F/FF) Hand Trucks	ST	42	
T(F/FF) Hand Trucks	SW	88	
T1/T2/T3			
T500/T700			
T800	T1/T2/T3	.31-32,34	
TB 61 TT 10 TW 78 -W- WA/WB/WM 103 WCK 81 WF 104 WG 81 WSE 104 WSH1/WSH2 102 WSJ2 106 WSL2 102 WSJ2 106 WSL2 102 WSS2 102 WSS2 102 WST1/WST2 101 WSTC 100 WT/WTS 105-106 WTC 107 WW 99 WWC 100			
TT			
TW			
-W- WA/WB/WM 103 WCK 81 WF 104 WG 81 WSE 104 WSH1/WSH2 102 WSJ2 106 WSL2 102 WSS2 102 WSS2 102 WST1/WST2 101 WSTC 100 WT/WTS 105-106 WTC 107 WW 99 WWC 100	Π	10	
WA/WB/WM       103         WCK       81         WF       104         WG       81         WSE       104         WSH1/WSH2       102         WSJ2       106         WSL2       102         WSS2       102         WST1/WST2       101         WSTC       100         WT/WTS       105-106         WTC       107         WW       99         WWC       100		78	
WCK 81 WF 104 WG 81 WSE 104 WSH1/WSH2 102 WSJ2 106 WSL2 102 WSS2 102 WST1/WST2 101 WSTC 100 WT/WTS 105-106 WTC 107 WW 99 WWC 100			
WF			
WG			
WSE			
WSH1/WSH2	WG	81	
WSJ2			
WSL2			
WSS2	WSJ2	106	
WST1/WST2			
WSTC			
WT/WTS			
WTC	WSTC	100	
WW			
WWC100			
WX99			
	WX	99	

## For more information on Little Giant products visit LittleGiant-USA.com

**SPECIFICATIONS:** If any particular dimension or specification is critical, it should be verified at time of order placement.

**CAPACITIES:** All capacities are based on Uniformly Distributed Loads (UDL). Do not exceed load capacities.

**WARRANTY:** Any product that has been subjected to normal use for which it is intended and is shown to be defective within one (1) year from date of purchase will be repaired or replaced at seller's option, provided such defect is reported promptly to the manufacturer. Authorization is required prior to returning.



Manufactured by

Brennan Equipment & Mfg. Inc.

730 Central Ave. University Park, IL 60484 Phone (708) 534-5500 FAX (708) 534-5520 www.LittleGiant-USA.com









#### Little Giant Products

Manufactured by

Brennan Equipment & Mfg. Inc.
730 Central Ave., University Park, IL 60484
Phone (708) 534-5500 • Fax (708) 534-5520
www.LittleGiant-USA.com • sales@littlegiant-usa.com

#### **SOLD ONLY THROUGH DEALERS**

Contact your local Industrial Distributor, or visit our website to locate a Distributor in your area.





