



BRADDICK SNIPER DIVISION



BRADDICK Mk. XII SFS .308 RIFLE

Standard Weapon Physical:

Empty Weight: 6700g
 Max. Length: 1200mm
 Zero Scope Height: 200mm
 Width: 80mm
 Coating: End-User Specified

Performance:

Mechanical Static Accuracy: Sub 0.2MOA in Controlled Laboratory Conditions – Proof Supplied with Weapon.

Standard Accessories:

2 Magazines
 Suppressor
 Muzzle Break
 Baseline Spares
 Rear-Monopod
 User Specified Bipod

Advanced Attachment Accessories:

Braddick Sniping Thermal
 Hensoldt IRV900 Sniping Thermal
 Hensoldt NSV1000 Sniping
 Night Vision / Image Intensifier

Optional Accessories:

Two Point or Biathlon Sling
 Anti-Mirage Strap

Standard Configuration [Special Bush Warfare]:

Sierra 7 Bipod
 Extended Main Tactical Picatinny Rail
 [For Thermal & Night Vision Attachments]
 Camouflage Cerakoting

Braddick Equipment:

Although Braddick recommends certain equipment, it is at the full discretion of the End-User to specify all equipment on their Braddick Sniping Systems, which Braddick will install and test for the End-User.

Scope: Hensoldt 3.5-26 X 56 FF Scope

Bipods: Sirra 7 // Phoenix Tactical // Atlas

Frame, Barrel & Action:

Barrel: 416R Stainless Steel Treated to 36 Rockwell
 Length: 26in//6604mm
 Rifling: 6 Grooves, 1 in 12" Twist
 Action: N350 Stainless Steel Treated to 37 Rockwell
 Bolt: 2 Locking Lugs
 Barrel is Threaded for Muzzle & Suppressor
 Fluting: Specified by End-User
 Chassis & Rails: Aircraft Grade 7075 Aluminium Alloy – Anodized

Braddick will always further customise and modify our weapons to perfectly meet the requirements of the snipers and End-Users who use our systems.



Office: +27(0) 12 663 2209
 Email: info@braddick.com
 Cel: +27 (0) 82 923 0580