



BRADDICK SNIPER DIVISION

BRADDICK Mk. XII SFS .50 RIFLE



Standard Weapon Physical:		Performance:
Empty Weight:	11500g	Mechanical Static Accuracy: Sub 0.2MOA in Controlled Laboratory Conditions – Proof Supplied with Weapon.
Max. Length:	1360mm	
Zero Scope Height:	240mm	
Width:	114mm	
Coating:	End-User Specified	
Standard Accessories:	Advanced Attachment Accessories:	
2 Magazines	Braddick Sniping Thermal	
Suppressor	Hensoldt IRV900 Sniping Thermal	
Muzzle Break	Hensoldt NSV1000 Sniping	
Baseline Spares	Night Vision / Image Intensifier	
Rear-Monopod		
User Specified Bipod		
Optional Accessories:		
Two Point or Biathlon Sling		
Anti-Mirage Strap		
Standard Configuration [Special Bush Warfare]:		
Sierra 7 Bipod		
Extended Main Tactical Picatinny Rail		
[For Thermal & Night Vision Attachments]		
Camouflage Cerakoting		

Braddick Equipment:
Although Braddick recommends certain equipment, it is at the full discretion of the End-User to specify all equipment on their Braddick Sniping Systems, which Braddick will install and test for the End-User.
Scope: Hensoldt 3.5-26 X 56 FF Scope
Bipods: Sirra 7 // Phoenix Tactical // Atlas

Frame, Barrel & Action:
Barrel: 416R Stainless Steel Treated to 36 Rockwell
Length: 31in//7870mm
Rifling: 6 Grooves, 1 in 15" Twist
Action: N350 Stainless Steel Treated to 37 Rockwell
Bolt: 3 Locking Lugs
Barrel is Threaded for Muzzle & Suppressor
Fluting: Specified by End-User
Chassis & Rails: Aircraft Grade 7075 Aluminium Alloy – Anodized

Braddick will always further customise and modify our weapons to perfectly meet the requirements of the snipers and End-Users who use our systems.

Office: +27(0) 12 663 2209 // Email: info@braddick.com // Cel: +27 (0) 82 923 0580

WWW.BRADDICKSNIPER.COM // WWW.BRADDICKOPTICS.COM