

Captivating. Powerful.  
Connected.

# M440



Beautifully Verifone's newest member of multilane devices, the Verifone M440 is flexible enough to support many use cases indoor attended, integrated or semi-integrated, WiFi, Ethernet, or USB. The vibrant display is perfect for promoting your brand, showcasing seasonal promotions, encouraging loyalty, and even training team members. Expand your eCommerce capabilities by accepting Advanced Payment Methods like Affirm or Klarna, providing your customers the convenience of buy online return in store, and more.

- Stunning 8" capacitive touchscreen
- Full-motion video support with high-quality audio
- 5MP camera ideal for scanning and accepting alternative payment methods

- Leverages MX 9xx stands
- Utilizes the power of Verifone Cloud Services for further customization and to add revenue building streams like eCommerce, Pay by Link, Advanced Payment Methods, and more.

<b>Display</b>	8" Color LCD   Capacitive Multi-touch   LED Backlight   Resolution: 1280 x 800
<b>Multimedia</b>	Audio Jack   Buzzer Speaker   Video & Audio Playback
<b>User Interface</b>	Backlit Keypad   Tactile 15 Key Keypad
<b>Camera   Barcode Scanner</b>	Barcode + OCR + QR Decode   Front 5 MP Fixed Focus
<b>Card Readers</b>	Magstripe ISO 7810, 7811, 7813   Smart Card EMVCo Approved
<b>Contactless</b>	EMVCo Approved   MiFare   Supports Advanced Payment Methods   Supports Major NFC/Contactless Schemes
<b>Connectivity</b>	Bluetooth® v4.2   WiFi 2.4GHz + 5GHz 802.11 a/b/g/n
<b>Memory</b>	Android 2GB RAM + 16GB Flash   Engage 512MB RAM + 512MB Flash
<b>Operating System</b>	Verifone Secure OS, Engage VOS2   AVOS Based on Android 8.1
<b>Processor</b>	Android Processor ARM Cortex A7, Quad Core, 1.1 GHz   Secure Processor ARM Cortex A9, 600 MHz
<b>Security</b>	PCI 5.x Approved
<b>Connections</b>	LAN 10/100 Base-T   RS232   USB RJ45 for Host/Device   USB Type-C
<b>Power</b>	Rating 12V, 1A, DC Jack
<b>Physical</b>	211mm L x 202mm W x 30mm H   Weight 692g
<b>Environmental</b>	IK06   IP Rating IP53   Operating Temperature 0° to 50° C (32° to 122° F)   Storage Temperature -20° to 60° C (-4° to 140° F)   Relative Humidity Max 90%, Non-condensing
<b>Other Standard Features</b>	Card Slots 2 SAM
<b>Accessories</b>	Mounting Plate   Mounting Pole   Privacy Shield   Stylus

