

Designed for performance & security.

# P400



Bring color to your business with a PIN pad that emboldens your brand. Boasting a dazzling touchscreen display, the Verifone P400 commands attention with its full-color multimedia support, making it ideal for video or image offers. Benefit from the Linux-based OS, an ultra-fast processor, ample memory and best-in-class security, with a PIN pad that keeps your customer's experience delightful and secure.

- Intuitive user interface with 3.5" color touch screen and greater pixel resolution to accommodate the latest multimedia innovations
- Accepts the full range of payment options and processes transactions quickly, for higher customer throughput and greater satisfaction
- Models with and without Wi-Fi + Bluetooth® available
- Delivers unsurpassed security using Verifone's Engage payment engine
- Utilizes the power of Verifone Cloud Services for customization and estate management

<b>Display</b>	3.5" Color LCD   Capacitive Multi-touch Screen   LED Backlight   Resolution: 320 x 480 HVGA	<b>Connections</b>	LAN 10/100 Base-T   RS232   USB RJ45 for Host/Device   Verifone 28 Pin PIN pad
<b>Multimedia</b>	Speaker	<b>Power</b>	Rating 5-12V 500mA, DC Jack, PoUSB 5V 500mA
<b>User Interface</b>	Backlit Keypad   Tactile 15 Key Keypad	<b>Physical</b>	167mm L x 80mm W x 44mm H   280g
<b>Card Readers</b>	Magstripe ISO 7810, 7811, 7813   Smart Card EMVCo Approved	<b>Environmental</b>	IK Rating IK04   IP Rating IP53   Operating Temperature: 0° to 50° C (32° to 122° F)   Storage Temperature: -20° to 60° C (-4° to 14° F)   Relative Humidity: 5% to 90%, Non-condensing
<b>Contactless</b>	EMVCo Approved   MiFare   Supports Major NFC/Contactless Schemes	<b>Other Standard Features</b>	Card Slots 2 SAM
<b>Memory</b>	128MB RAM + 256MB Flash   Micro SD   Optional 512MB RAM + 512MB Flash	<b>Accessories</b>	Mounting Plate   Mounting Pole   Privacy Shield   Stylus
<b>Operating System</b>	Verifone Secure OS, Engage VOS2		
<b>Processor</b>	ARM Cortex A9, 600 MHz		
<b>Security</b>	PCI PTS 5.x Approved		

